

# Accessories and Spare Parts

## Accessories for 3RT, 3RH contactors and contactor relays



3RT19 24-5A.01    3RT19 34-5A.01    3RT19 44-5A.01    3RT19 45-5A.01    3RT19 45-5A.02    3RT19 55-5A.    3RT19 55.5N..

For contactors		Rated control supply voltage $U_c$		Screw terminals	Weight per PU approx.	Rated control supply voltage $U_c$		Screw terminals	Weight per PU approx.			
Size	Type			Order No.	kg	Type			Order No.	kg		
<b>Magnetic Coils - AC operation</b>						<b>Magnetic Coils - DC operation</b>						
S0	3RT10 2..	24V	50/60 Hz	3RT19 24-5AC21	0.100							
	3RT13 2..	110V	50/60 Hz	3RT19 24-5AG21	0.100							
	3RT15 2..	230V	50/60 Hz	3RT19 24-5AL21	0.100							
		400V	50 Hz	3RT19 24-5AV21	0.100							
S2	3RT10 34	24V	50/60 Hz	3RT19 34-5AC21	0.120	3RT10 3	24V DC	3RT19 34-5BB41	0.650			
		110V	50/60 Hz	3RT19 34-5AG21	0.120	3RT13 3	110V DC	3RT19 34-5BF41	0.650			
		230V	50/60 Hz	3RT19 34-5AL21	0.120	3RT15 3	220V DC	3RT19 34-5BM41	0.650			
		400V	50 Hz	3RT19 34-5AV21	0.120							
	3RT10 35	24V	50/60 Hz	3RT19 35-5AC21	0.120							
		110V	50/60 Hz	3RT19 35-5AG21	0.120							
		230V	50/60 Hz	3RT19 35-5AL21	0.120							
		400V	50 Hz	3RT19 35-5AV21	0.120							
	S3	3RT10 44	24V	50/60 Hz	3RT19 44-5AC21	0.190	3RT10 4	24V DC	3RT19 44-5BB41	1.000		
			110V	50/60 Hz	3RT19 44-5AG21	0.190	3RT13 4	110V DC	3RT19 44-5BF41	1.000		
			230V	50/60 Hz	3RT19 44-5AL21	0.190	3RT15 4	220V DC	3RT19 44-5BM41	1.000		
			400V	50 Hz	3RT19 44-5AV21	0.190	3RT15 4					
3RT10 45		24V	50/60 Hz	3RT19 45-5AC21	0.190							
		110V	50/60 Hz	3RT19 45-5AG21	0.190							
		230V	50/60 Hz	3RT19 45-5AL21	0.190							
		400V	50 Hz	3RT19 45-5AV21	0.190							
<b>Withdrawable coils</b>												
<b>Conventional operating mechanism</b>					<b>Solid-state operating mechanism</b>			<b>For 24V DC PLC output</b>				
S6		3RT10 5	110...127V AC/DC		3RT19 55-5AB31	0.650		3RT10 5	96...127V AC/DC		3RT19 55-5NF31	0.650
		3RT14 5	220...240V AC/DC		3RT19 55-5AF31		3RT14 5	200...277V AC/DC		3RT19 55-5NP41	0.650	
S10	3RT10 6	110...127V AC/DC		3RT19 65-5AB31	0.850	3RT10 6	96...127V AC/DC		3RT19 55-5NF31	0.900		
		220...240V AC/DC		3RT19 65-5AF31			200...277V AC/DC		3RT19 55-5NP31			
	3RT14 6	110...127V AC/DC		3RT19 66-5AB31	1.000	3RT14 6	96...127V AC/DC		3RT19 66-5NF31	0.650		
		220...240V AC/DC		3RT19 66-5AF31			200...277V AC/DC		3RT19 66-5NP31			
<b>For 24 V DC PLC output/PLC relay output, with remaining lifetime indicator (RLT)</b>												
(Withdrawable coil with lateral solid-state module)												
S6	3RT10 5	96...127V AC/DC		3RT19 55-5PF31	0.650							
	3RT14 5	200...277V AC/DC		3RT19 55-5PP31		0.650						
S6	3RT10 6	96...127V AC/DC		3RT19 65-5PF31	1.300							
	3RT14 6	200...277V AC/DC		3RT19 65-5PP31		1.300						
S612	3RT10 7	96...127V AC/DC		3RT19 75-5PF31	1.300							
	3RT14 7	200...277V AC/DC		3RT19 75-5PP31		1.300						