





• Revised •
11/15/14

Pushbutton Units and Indicator Lights

30mm Water, Oil Tight & Corrosion Resistant – Class 52

Special devices

Selection and ordering data

Version	Ohms / color	Order no.	Pack		
 <p>Potentiometer operator 2 Watts, 500 V AC/DC (NEMA Type 4)</p>	50	52MA3B01	1		
	150	52MA3B03			
	250	52MA3B04			
	500	52MA3B06			
	750	52MA3B07			
	1 K	52MA3B08			
	2.5 K	52MA3B10			
	5 K	52MA3B12			
	10 K	52MA3B14			
	15 K	52MA3B15			
	25 K	52MA3B16			
	50 K	52MA3B18			
	100 K	52MA3B20			
	150 K	52MA3B21			
	250 K	52MA3B22			
	500 K	52MA3B24			
	1 M	52MA3B26			
1.5 M	52MA3B27				
2 M	52MA3B28				
5 M	52MA3B31				
 <p>2 Button maintained operator</p> <p>Button remains depressed when pushed</p>	black (flush) / red (flush)	52MA2A1A2	1		
	black (flush) / red (extended)	52MA2A1B2			
	black (flush) / yellow (mushroom)	52MA2A1D4			
	green (flush) / red (flush)	52MA2A3A2			
	green (flush) / red (extended)	52MA2A3B2			
	green (flush) / red (mushroom)	52MA2A3D2			
	green (flush) / green (mushroom)	52MA2A3D3			
	less caps	52MA2			
	 <p>Wobble stick 2.5" operator For use with 52BAJ (NC) contact block</p>	red		52ABW2 ^①	1
		green		52ABW3 ^①	
grey		52ABW6 ^①			
 <p>Maintained toggle operator</p>		52ABT	1		

① For use with 52BAJ (NC) contact block