

SIMATIC DP, 5 ELECTRON. MODULES FOR ET 200S, 4 DI
STANDARD 24V DC, 15 MM WIDTH, 5 PIECES PER PACKAGING
UNIT



Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> • 24 V DC 	Yes; From power module
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Type of output voltage	min. L+ (-0.5 V), under load
Output current	
<ul style="list-style-type: none"> • nominal 	500 mA
<ul style="list-style-type: none"> • permissible range 	0 to 500 mA
Power loss	
Power loss, typ.	0.7 W
Address space per module	
<ul style="list-style-type: none"> • with packing 	4 bit

- without packing

1 byte

Digital inputs

Number of digital inputs	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	+15 to +30V
Input current	
• for signal "1", typ.	7 mA; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
— Parameterizable	No
— at "0" to "1", min.	2 ms; typically 3 ms
— at "0" to "1", max.	4.5 ms
— at "1" to "0", min.	2 ms; typically 3 ms
— at "1" to "0", max.	4.5 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m

Encoder

Connectable encoders	
• 2-wire sensor	
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Diagnostic messages	
• Diagnostic functions	No
Diagnostics indication LED	
• Group error SF (red)	No
• Status indicator digital input (green)	Yes; per channel

Parameter

Remark	1 byte
--------	--------

Potential separation

Potential separation digital inputs	
• between the channels	No
• between the channels and the backplane bus	Yes

Permissible potential difference

between different circuits	75V DC/60V AC
----------------------------	---------------

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Dimensions

Width	15 mm
-------	-------

Height	81 mm
--------	-------

Depth	52 mm
-------	-------

Weights

Weight, approx.	35 g
-----------------	------

last modified:	17.07.2015
-----------------------	------------