

Product type designation
Product description

IE FC RJ45 Plug 180 (4x2)
RJ45 data connector
IE FC RJ45 PLUG 180 4X2, RJ45 CONNECTOR
(10/100/1000MBIT/S) WITH ROBUST METAL HOUSING FC
CONNECTING METHOD, FOR IE FC CABLE 4X2 (AWG24) 180
DGR OUTGOING CABLE 1 PACKAGE = 1 PIECE



Suitability for use	For connection to IE FC TP cables 4x2, suitable for fast assembly with the FastConnect system
---------------------	---

Transmission rate

Transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
---	------------------------------------

Interfaces

Number of electrical connections	
<ul style="list-style-type: none"> for Industrial Ethernet FC TP cables 	8
<ul style="list-style-type: none"> for network components or terminal equipment 	1
Type of electrical connection	
<ul style="list-style-type: none"> for Industrial Ethernet FC TP cables 	integrated cut-and-clamp contacts for 8-wire TP FC installation cable
<ul style="list-style-type: none"> for network components or terminal equipment 	RJ45 connector
Type of electrical connection / FastConnect	Yes

Mechanical data

Material / of the enclosure	metal
Number of reuses	10
Locking mechanism design	other

Design, dimensions and weight	
Type of cable outlet	180° cable outlet
Width	13.7 mm
Height	16 mm
Depth	55 mm
Net weight	35 g
Connectable cable cross-section	8 ... 8 mm

Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operation 	-40 ... +85 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> during transport 	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Product properties, functions, components / general	
Product feature	
<ul style="list-style-type: none"> PoE capability 	Yes
<ul style="list-style-type: none"> PoE+capability 	Yes
<ul style="list-style-type: none"> silicon-free 	Yes
Product component	
<ul style="list-style-type: none"> strain relief 	Yes

Standards, specifications, approvals	
Certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes
<ul style="list-style-type: none"> UL approval 	Yes
<ul style="list-style-type: none"> cULus approval 	Yes
<ul style="list-style-type: none"> Railway application in accordance with EN 50155 	No
Standard for structured cabling	Cat6

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com

last modified:

07.01.2016