### Rittal - The System.

Faster – better – everywhere.

# Compact enclosures AE Stainless steel – AE 1007.600

Date : Jul 6, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Spare parts - Compact enclosures AE Stainless steel – AE 1007.600

created: 06.07.2017 on www.rittal.com/com-en



#### **Product description**

Material: Enclosure: Stainless steel

Door: Stainless steel, all-round foamed-in PU seal

Mounting plate: Sheet steel Stainless steel 1.4301 (AISI 304) Lock insert: Die-cast zinc, nickel-plated

**Surface finish:** Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm

Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4X

IK Code:

IK08

Supply includes:

Enclosure with door(s)
Mounting plate

Lock: 3 mm double-bit

**Product modification:** 

From August 2016, surface grinding will change from grain size 240 to grain size 400. The visually refined grinding finish will also enhance the enclosure's cleaning properties.

Basic material: Stainless steel

#### **Product features**

Dimensions: Width: 500 mm

Height: 500 mm

© Rittal 2017

Depth: 210 mm

Mounting plate: Width: 449 mm Height: 470 mm

1 Number of doors:

Cam Lock version:

2 Number of locks:

Lock insert: 3 mm double-bit

Packs of: 1 pc(s).

Weight/pack: 15.7 kg

EAN: 4028177000254

**Customs tariff** number:

94032080

ETIM 6.0: EC000261

ETIM 5.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 7.0/7.1: 27180101

27180101 eCl@ss 6.0/6.1:

27180102 eCl@ss 5.1/5.1.4:

**Product description** (long):

AE Compact enclosure, WHD: 500x500x210 mm, Stainless steel 1.4301, with mounting plate, single-door, with two cam locks

#### **Approvals**

Approvals: **Bureau Veritas** 

CSA DNV GL

Lloyds Register of Shipping

NA

Russian Maritime Register of Shipping

UL + C-UL ΤÜV

EAC **Certificates:** 

IK-Code

Protection category

© Rittal 2017 2 **Declarations:** 

Declaration of conformity

2017 © Rittal GmbH & Co. KG

© Rittal 2017 3