PICO®

CABLE TIES

ONE PIECE SELF-LOCKING CABLE TIE. NO METAL BARBS. WRAP TIE AROUND CABLE, SLIP TAIL THROUGH HEAD & PULL TIGHT. TIE LOCKS IN PLACE AUTOMATICALLY. SNIP OFF: EXCESS TAIL. CABLE TIE MEET UL 94V-2 FLAMMABILITY RATINGS. TEMPERATURE RATING:-40F TO 185F GENERAL PURPOSE NYLON 6/6 IS SUITABLE FOR USE IN MOST PRACTICAL APPLICATIONS AT A CONTINUOUS TEMPERATURE UP TO 150F. UV STABILIZED NYLON 6/6 IS USED IN CONTINUOUS OR EXTENDED EXPOSURE TO OUTDOOR USE. THE NYLON CABLE TIE IS A WEATHER RESISTANT GRADE, ENDURING ADDITIONAL ULTRA-VIOLET (UV) LIGHT. UV STABILIZED CABLE TIES ARE AVAILABLE ONLY IN BLACK. RoHS COMPLIANT

4" MINIATURE 18LB

WIDTH 2.41MM THICKNESS 1.06MM BUNDLE DIAMETER .875

25 PC	100 PC	1000 PC		MILITARY SPEC	25 PC	100 PC		MILITARY SPEC
7063-PK	7063-C	7063-M	NATURAL	MS3367-4-9	7063-4-PK	7063-4-C	ORANGE	MS3367-4-3
7063-0-PK	7063-0-C	7063-0-M	UV BLACK	MS3367-4-0	7063-5-PK	7063-5-C	RED	MS3367-4-2
7063-1-PK	7063-1-C		BLUE	MS3367-4-6	7063-7-PK	7063-7-C	YELLOW	MS3367-4-4
7063-2-34	7063-2-36		BROWN	MS3367-4-1	7063-8-34	7063-8-36	GREY	MS3367-4-8
7063-3-PK	7063-3-C		GREEN	MS3367-4-5	7063-9-PK	7063-9-C	PURPLE	MS3367-4-7

6" INTERMEDIATE 40LB

WIDTH 3.55MM THICKNESS 1.24MM BUNDLE DIAMETER 1.437

25 PC	100 PC	1000 PC		MILITARY SPEC	25 PC	100 PC		MILITARY SPEC
7065-PK	7065-C	7065-M	NATURAL	MS3367-5-9	7065-4-PK	7065-4-C	ORANGE	MS3367-5-3
7065-0-PK	7065-0-C	7065-0-M	UV BLACK	MS3367-5-0	7065-5-PK	7065-5-C	RED	MS3367-5-2
7065-1-PK	7065-1-C		BLUE	MS3367-5-6	7065-7-PK	7065-7-C	YELLOW	MS3367-5-4
7065-2-PK	7065-2-C		BROWN	MS3367-5-1	7065-8-PK	7065-8-C	GREY	MS3367-5-8
7065-3-PK	7065-3-C		GREEN	MS3367-5-5	7065-9-PK	7065-9-C	PURPLE	MS3367-5-7

7.5" STANDARD 50LB

WIDTH 4.57MM THICKNESS 1.32MM BUNDLE DIAMETER 1.875

25 PC	100 PC	1000 PC		MILITARY SPEC	25 PC	100 PC	1000 PC		MILITARY SPEC
7066-PK	7066-C	7066-M	NATURAL	MS3367-1-9	7066-4-PK	7066-4-C	7066-4-M	ORANGE	MS3367-1-3
7066-0-PK	7066-0-C	7066-0-M	UV BLACK	MS3367-1-0	7066N4-PK	7066N4-C		NEON ORANGE	
7066-1-PK	7066-1-C	7066-1-M	BLUE	MS3367-1-6	7066-5-PK	7066-5-C	7066-5-M	RED	MS3367-1-2
7066N1-PK	7066N1-C		NEON BLUE		7066-7-PK	7066-7-C	7066-7-M	YELLOW	MS3367-1-4
7066-2-PK	7066-2-C	7066-2-M	BROWN	MS3367-1-1	7066N7-PK	7066N7-PK		NEON YEL	
7066-3-PK	7066-3-C	7066-3-M	GREEN	MS3367-1-5	7066-8-PK	7066-8-C	7066-8-M	GREY	MS3367-1-8
7066N3-PK	7066N3-C		NEON GREEN		7066-9-PK	7066-9-C	7066-9-M	PURPLE	MS3367-1-7
					7066N9-PK	7066N9-C		NEON PINK	

8" INTERMEDIATE 40LB

WIDTH 3.55MM THICKNESS 1.24MM BUNDLE DIAMETER 2.375

25 PC	100 PC	1000 PC		MILITARY SPEC	25 PC	100 PC	1000 PC		MILITARY SPEC
7066L-PK	7066L-C	7066L-M	NATURAL	MS3367-5-9	7066L0-PK	7066L0-C	7066L0-M	UV BLACK	MS3367-5-0

11" STANDARD 50LB

WIDTH 4.57MM THICKNESS 1.32MM BUNDLE DIAMETER 3.062

25 PC	100 PC	1000 PC		MILITARY SPEC	25 PC	100 PC		MILITARY SPEC
7067-PK	7067-C	7067-M	NATURAL	MS3367-7-9	7067-4-PK	7067-4-C	ORANGE	MS3367-7-3
7067-0-PK	7067-0-C	7067-0-M	UV BLACK	MS3367-7-0	7067-5-PK	7067-5-C	RED	MS3367-7-2
7067-1-PK	7067-1-C		BLUE	MS3367-7-6	7067-7-PK	7067-7-C	YELLOW	MS3367-7-4
7067-2-PK	7067-2-C		BROWN	MS3367-7-1	7067-8-PK	7067-8-C	GREY	MS3367-7-8
7067-3-PK	7067-3-C		GREEN	MS3367-7-5	7067-9-PK	7067-9-C	PURPLE	MS3367-7-7

14" STANDARD 50LB

WIDTH 4.52MM THICKNESS 1.32MM BUNDLE DIAMETER 4

25 PC	100 PC	1000 PC		MILITARY SPEC	25 PC	100 PC		MILITARY SPEC
7068-PK	7068-C	7068-M	NATURAL	MS3367-2-9	7068-4-34	7068-4-C	ORANGE	MS3367-2-3
7068-0-PK	7068-0-C	7068-0-M	UV BLACK	MS3367-2-0	7068-5-PK	7068-5-C	RED	MS3367-2-2
7068-1-PK	7068-1-C		BLUE	MS3367-2-6	7068-7-PK	7068-7-C	YELLOW	MS3367-2-4
7068-2-34	7068-2-36		BROWN	MS3367-2-1	7068-8-34	7068-8-36	GREY	MS3367-2-8
7068-3-34	7068-3-36		GREEN	MS3367-2-5	7068-9-34	7068-9-36	PURPLE	MS3367-2-7
						7068N9-36	NEON PINK	

STANDARD CABLE TIE ASSORTMENTS

RoHS COMPLIANT

20-CS	NATURAL 400 PC	200-4", 100-8", 100-11"
21-CS	BLACK 400 PC	200-4", 100-8", 100-11"
7160-PK	NATURAL & BLACK 60 PC	10-4" NATURAL & BLACK, 10-6" NATURAL & BLACK 10-8" NATURAL & BLACK
7166-PK	NATURAL 25 PC	8-4" NATURAL, 8-6" NATURAL, 9-8" NATURAL

PICO®

RoHS COMPLIANT

RELEASABLE NATURAL 50LB CABLE TIES

TEMPORARILY OR PERMANENT BUNDLING ALLOWS FOR QUICK ADDITION OR REMOVAL OF WIRES OR ITEMS STRAP FINGER RELEASE LATCH ALLOWS EASY ACCESS

25 PC	100 PC	LENGTH INCH	LENGTH MM	WIDTH INCH	WIDTH MM	THICKNESS INCH	THICKNESS MM	BUNDLE DIAMETER
7092-PK	7092-C	5.9	150.	.29	7.6	.050	1.27	1.37
7093-PK	7093-C	7.8	200.	.29	7.6	.053	1.34	1.96
7094-PK	7094-C	11.8	300.	.29	7.6	.053	1.34	3.15

RoHS COMPLIANT

CLAMP CABLE TIES

CLAMP TIE HAS TRIANGULAR SHAPED TABS EXTENDING BENEATH THE HEAD, ALLOWING FOR OPTIMAL SURFACE CONTACT & COMPLETE CIRCUMFRENTIAL COMPRESSION TO 360 DEGREES RECOMMENDED FOR SOFT RUBBER HOSE APPLICATIONS INCLUDING FUEL,WATER & AIR VACUUM LINES. UL94 V2 OPERATING TEMP -40C TO 105C CONTINUOUS

NATURAL POLYAMIDE 6.6 (PA66) 25 PC	100 PC	LENGTH INCH	LENGTH MM	TIE TENSILE	WIDTH INCH	WIDTH MM	BUNDLE DIAMETER	UV BLACK POLYAMIDE 6.6 HEAT STABILIZED 25 PC	100 PC
7164-PK	7164-C	4	100	20 LB	.10	2.5	.5	7164-0-PK	7164-0-C
7168-PK	7168-C	8	205	60 LB	.19	4.7	1.77	7168-0-PK	7168-0-C

RoHS COMPLIANT 7.5"ONLY

LOW PROFILE CABLE TIES

REDUCED HEAD HEIGHT COMPARED TO STANDARD HEAD DESIGNS INCREASED SAFETY, ELIMINATES SNAGS, CUTS & ABRASIONS TO CABLES, HOSES, PRODUCTS & USERS NO SHARP TAIL CUTOFFS REMAINING TAIL SLIPS BACK INTO HEAD OF TIE LEAVING NO EXPOSED SHARP EDGES QUICK & SAFE REMOVAL SIMPLY CUT & PRY TOP CROSSBAR TO RELEASE CABLE TIE, ELIMINATING DAMAGE TO WIRES, TUBING, ETC. FLEXIBLE HEAD DESIGN ALLOWS THE HEAD TO EASILY FLEX AROUND THE TOTAL CIRCUMFERENCE OF TUBING OR BUNDLED WIRES TAMPER PROOF PAWL LOCATED UNDER THE TIE'S HEAD, MAKES IT INACCESSIBLE WHEN BUNDLED EASY HANDLING FINGER GRIPS ON THE TAIL PROVIDES A NO SLIP GRIP DURING INSERTION & TENSIONING

NATURAL 50 LB 25 PC	100 PC	LENGTH INCH	LENGTH MM	WIDTH INCH	WIDTH MM	THICKNESS INCH	THICKNESS MM	BUNDLE DIAMETER	UV BLACK 50 LB 25 PC	100 PC
7176-PK	7176-C	7.5	190.5	.17	4.49	.053	1.34	1.75	7176-0-PK	7176-0-C
7177-34	7177-36	11	288.2	.17	4.49	.053	1.34	3.06	7177-0-34	7177-0-36
7179-34	7179-36	14	372.1	.17	4.49	.053	1.34	4.06	7179-0-34	7179-0-36
NATURAL 120 LB									UV BLACK 120 LB	
7178-34	7178-36	16.	406.4	.30	7.62	.075	1.90	4.06	7178-0-34	7178-0-36

METAL PAWL UV BLACK CABLE TIES

BUNDLED EASY UV STABILIZED TEMPERATURE –40C TO 85C MATERIAL NYLON 66 (PA66) UL94-2V FLAME

25 PC	100 PC	LENGTH INCH	TIE TENSILE	WIDTH MM	THICKNESS INCH	THICKNESS MM	BUNDLE DIAMETER
7253-34	7253-36	4	18 LB	2.5	.045	1.15	.87"
7256-34	7256-36	7.50	50 LB	4.8	.051	1.30	1.93"
7257-34	7257-36	11	50 LB	4.8	.051	1.30	3.09"
7258-34	7258-36	14	50 LB	4.8	.051	1.30	4.05"

RoHS COMPLIANT

HEAT STABILIZED 50LB BLACK CABLE TIES

100 PC	1000 PC	LENGTH INCH	LENGTH MM	WIDTH INCH	WIDTH MM	THICKNESS INCH	THICKNESS MM	BUNDLE DIAMETER
7266-36	7266-39	7.5	192.	.180	4.57	.052	1.32	1.675
7267-36	7267-39	11.2	285.	.180	4.57	.052	1.32	3.062

RoHS COMPLIANT

PUSH MOUNT HEAT STABILIZED BLACK NYLON CABLE TIES

FIR TREE GRIPS TO INSIDE OF HOLE USED WITH METAL, WOOD, PASTIC OR CAST IRON

25 PC	100 PC	LENGTH	TIE TENSILE	WIDTH	THICKNESS	BUNDLE DIAMETER
7250-34	7250-36	8.39"	50 LB	.19"	.05"	2"

PICO®

7.5" 40LB CHROME CABLE TIES

	5 PC	25 PC	100 PC	WIDTH INCH	BUNDLE DIAMETER
SILVER	7186-34	7186-35	7186-36	3.6	57MM
BLUE	7186-1-34	7186-1-35	7186-1-36	3.6	57MM
RED	7186-5-34	7186-5-35	7186-5-36	3.6	57MM

SEE PAGE 60 FOR CHROME LOOM

ECONOMY CABLE TIES

RoHS COMPLIANT

NATURAL 100 PC	NATURAL 1000 PC	LENGTH INCH	LENGTH MM	WIDTH INCH	WIDTH MM	BUNDLE DIAMETER	TIE TENSILE	BLACK 100 PC	BLACK 1000 PC
7063K-36	7063K-39	4	100	.10	2.5	30MM	18	7063K0-36	7063K0-39
7065K-36	7065K-39	5.9	150	.13	3.2	38MM	40	7065K0-36	7065K0-39
7066K-36	7066K-39	7.9	200	.19	4.8	56MM	50	7066K0-36	7066K0-39
7067K-36	7067K-39	11.3	286	.19	4.8	72MM	50	7067K0-36	7067K0-39
7068K-36	7068K-39	14.5	368	.19	4.8	109MM	50	7068K0-36	7068K0-39
7068HDK-36	7068HDK-39	14.5	368	.30	7.6	109MM	120	7068HK0-36	7068HK0-39
7069K-36	7069K-39	27.6	368	.35	8.8	702MM	175	7069K0-36	7069K0-39
7150K-36	7150K-39	36.0	914	.35	8.8	702MM	175	7150K0-36	7150K0-39

CABLE TIES HEAVY DUTY

HEAVY DUTY 120LB

WIDTH 7.62MM THICKNESS 1.93MM *NOT CSA APPROVED RoHS COMPLIANT



LENGTH	NATURAL 25 PC	NATURAL 100 PC	MILITARY SPEC	BUNDLE DIAMETER	UV BLACK 25 PC	UV BLACK 100 PC	MILITARY SPEC
8.7"	7066HD-PK	7066HD-C		2.06	7066HD0-PK	7066HD0-C	
15."	7068HD-PK	7068HD-C	MS3367-3-9	4.06	7068HD0-PK	7068HD0-C	MS3367-3-0
28.5"	7070-PK*	7070-C*		8.	7070-0-PK*	7070-0-C*	

EXTRA HEAVY DUTY 175LB

WIDTH 8.63MM THICKNESS 2.28MM RoHS COMPLIANT



LENGTH	NATURAL 25 PC	NATURAL 100 PC	MILITARY SPEC	BUNDLE DIAMETER	UV BLACK 25 PC	UV BLACK 100 PC	MILITARY SPEC
25.2"	7069-PK	7069-C	MS3367-10-9	7.18	7069-0-PK	7069-0-C	MS3367-10-0
37.2"	7150HD-PK	7150HD-C	MS3367-13-9	11.00	7150HD0-PK	7150HD0-C	MS3367-13-0
48.5"	7152HD-PK	7152HD-C	MS3367-16-9	14.50	7152HD0-PK	7152HD0-C	MS3367-16-0

EXTRA HEAVY DUTY 250LB

RoHS COMPLIANT

LENGTH	NATURAL 25 PC	NATURAL 100 PC	WIDTH	BUNDLE DIAMETER	LENGTH	UV BLACK 25 PC	UV BLACK 100 PC
9"	7140HD-PK	7140HD-C	12.5MM	.55			
			12.5MM	145	20"	7141HD0PK	7141HD0-C

MOUNTING TAB CABLE TIES

CABLE TIE MEET UL 94V-2 FLAMMABILITY RATINGS. TEMPERATURE RATING:-40F TO 185F GENERAL PURPOSE NYLON 6/6 IS SUITABLE FOR USE IN MOST PRACTICAL APPLICATIONS AT A CONTINUOUS TEMPERATURE UP TO 150F. UV STABILIZED NYLON 6/6 IS USED IN CONTINUOUS OR EXTENDED EXPOSURE TO OUTDOOR USE.

30LB #8 SCREW HOLE

RoHS COMPLIANT

LENGTH	NATURAL 25 PC	NATURAL 100 PC	NATURAL 1000 PC	WIDTH INCH	WIDTH MM	THICKNESS INCH	THICKNESS MM	BUNDLE DIAMETER	UV BLACK 25 PC	UV BLACK 100 PC	UV BLACK 1000 PC
5.8"	7071-PK	7071-C	7071-M	.138	3.50	.045	1.14	1.25	7071-0-PK	7071-0-C	7071-0-39

50LB # 10 SCREW HOLE

WIDTH 4.49MM 8"ONLY RoHS COMPLIANT

LENGTH	NATURAL 25 PC	NATURAL 100 PC	NATURAL 1000 PC	THICKNESS INCH	THICKNESS MM	BUNDLE DIAMETER	UV BLACK 25 PC	UV BLACK 100 PC	UV BLACK 1000 PC
8"	7072-PK	7072-C	7072-M	.052	1.32	1.75	7072-0-PK	7072-0-C	7072-0-M
11.5"	7075-PK	7075-C	7075-M	.053	1.34	3.00	7075-0-PK	7075-0-C	7075-0-M
14.5"	7076-PK	7076-C	7076-M	.053	1.34	4.00	7076-0-PK	7076-0-C	7076-0-M

PICO®

RoHS COMPLIANT

15" ONLY

MOUNTING TAB CABLE TIES 120LB

NATURAL		SCREW HOLE	WIDTH		THICKNESS		BUNDLE DIAMETER	LENGTH	UV BLACK	
25 PC	100 PC		INCH	MM	INCH	MM			25 PC	100 PC
7077-PK	**7077-C**	1/4"	.298	7.5	.075	1.9	4.06	15.7"	**7077-0-PK**	**7077-0-C**
7078-PK	**7078-C**	1/4"	.310	7.9	.083	2.1	6.00	22"	**7078-0-PK**	**7078-0-C**
7079-PK	**7079-C**	1/4"	.310	7.9	.083	2.1	8.00	29"		

RoHS COMPLIANT

ECONOMY MOUNTING TAB CABLE TIES

NATURAL		SCREW HOLE	WIDTH		TIE TENSILE	BUNDLE DIAMETER	LENGTH	UV BLACK	
100 PC	1000 PC		INCH	MM	LBS.		INCH	100 PC	1000 PC
7071K-36	**7071K-39**	# 8	.14	3.6	40	35MM	5.9"	**7071K0-36**	**7071K0-39**
7072K-36	**7072K-39**	# 10	.14	3.6	50	50MM	8"	**7072K0-36**	**7072K0-39**
7075K-36	**7075K-39**	# 10	.19	4.8	50	75MM	11.8"	**7075K0-36**	**7075K0-39**
7076K-36	**7076K-39**	# 10	.19	4.8	50	109MM	14.5"	**7076K0-36**	**7076K0-39**
7077K-36	**7077K-39**	1/4"	.30	7.6	120	100MM	14.5"	**7077K0-36**	**7077K0-39**

RoHS COMPLIANT

MOUNTING PADS

SAVES CABLE TIE CINCHING TIME PATENTED STAY-N-PLACE TAB KEEPS CABLE TIE HEAD FROM SLIDING DOWN BEHIND BUNDLE DURING VERTICAL APPLICATIONS & MAINTAINS PLACEMENT DURING HORIZONTAL APPLICATIONS EASY INSERTION OF CABLE TIES PATENTED LEAD-N-FEATURE FUNNELS CABLE TIES INTO POSITION & COUNTERSUNK SCREW HOLE ALLOWS CABLE TIE TO EASILY PASS OVER SCREW HEAD SAVES POSITIONING TIME WITH THE 4 SIDED ENTRY & CENTER SCREW HOLE UL/CSA APPROVED FOR INDOOR USE DESIGNED FOR USE WITH 50LB OR LIGHTER CABLE TIES

NATURAL		SCREW HOLE	LENGTH		HEIGHT		ADHESIVE	UV BLACK	
25 PC	100 PC		INCH	MM	INCH	MM		25 PC	100 PC
7082-PK	**7082-C**	#6	.74	18.7	.19	4.8	RUBBER	**7082-0-34**	**7082-0-36**
7080-PK	**7080-C**	#4	.99	25.1	.20	5.0	NONE	**7080-0-34**	**7080-0-36**
7081-PK	**7081-C**	#6	.99	25.1	.20	5.0	RUBBER	**7081-0-34**	**7081-0-36**
7085-34	**7085-36**	#6	.99	25.1	.20	5.0	ACRYLIC	**7085-0-34**	**7085-0-36**

RoHS COMPLIANT

SCREW MOUNTS

SECURE SUPPORT DEEP CRADLE DESIGN PROVIDES MAXIMUM SUPPORT FOR LARGER BUNDLES & TUBING EASY INSERTION OF CABLE TIES DEEP RECESSED SCREW HOLE ALLOWS CABLE TIES TO PASS OVER SCREW HEAD

NATURAL		SCREW HOLE	LENGTH		HEIGHT		WIDTH		USE WITH CABLE TIE	BLACK	
25 PC	100 PC		INCH	MM	INCH	MM	INCH	MM		25 PC	100 PC
7084-34	**7084-36**	#6	.59	14.98	.27	6.8	.37	9.39	50 LB	**7084-0-34**	**7084-0-36**
7183-6-34	**7183-6-36**	#8	.60	15.4	.37	9.4	.60	15.4	50 LB	**7183-0-34**	**7183-0-36**
7083-34	**7083-36**	1/4"	.87	22.09	.38	9.6	.63	16.0	120 LB	**7083-0-34**	**7083-0-36**

SEE PAGE 38 FOR TOOLS

SEE PAGE 3-5 FOR KITS