Yellow 77® Plus Wire Pulling Lubricant

- Rapid Glide™ polytetrafluoroethylene additive provides greater lubricity than other wax-based lubricants — great for tough pulls
- Safe to use with all cable types
- Clings to cable throughout long runs, even where moisture is present
- Remains stable in high temperatures — usable from 30°F to 190°F (-1°C to 88°C)
- Dries slowly to a thin, non-conductive film that won't harden in conduit
- Easy to apply by hand or by brush
- Creamy texture applies easily and uniformly
- Homogeneous blend requires no mixing
- Won't dry out – surface coat forms to control evaporation
- Environmentally safe – non-toxic, non-flammable and non-corrosive

Description	Cat. No.
1-qt. Squeeze bottle	**31-398**
1-gal. Bucket	**31-391**
5-gal. Bucket	**31-395**

UL LISTED

Yellow 77® Wire Pulling Lubricant

- The #1 brand of wire pulling lubricant since 1959 — the perfect general purpose lube
- Wax-based formula provides superior lubricity
- Safe to use with most cable types except low-density polyethylene and semi-conducting jackets
- Clings to cable throughout long pulls, even where moisture is present
- Won't break down or separate after repeated exposure to freezing temperatures
- Dries to a thin, non-conductive film
- Easy to apply by hand or by brush
- Creamy texture applies easily and uniformly
- Homogeneous blend requires no mixing
- Won't dry out — surface coat forms to control evaporation
- Environmentally safe — non-toxic, non-flammable and non-corrosive

Description	Cat. No.
1-qt. Squeeze bottle	**31-358**
1-qt. Tub	**31-350**
1-gal. Bucket	**31-351**
5-gal. Bucket	**31-355**
55-gal. Drum	**31-365**

UL LISTED