

VoltAware[™] Non-Contact Voltage Tester

- Indicates presence of voltage from 40-1000VAC
- Visual indication of voltage
- Selectable audible indication of voltage
- Sleek, compact design
- Green LED indicates power on
- Low battery indicator
- Battery replacement (AAA size)
- 2-year warranty



Volt-Sensor® Non-Contact Voltage Tester

- Tests for voltage from 40-600VAC
- Audible and visual indication
- Locates breaks along live insulated wires
- Tests for energized circuits
- Battery replacement (LR44/61-201)
- 1-year warranty



Ŭ	1112000	Ŭ	
Descript	tion		
Volt-Sens	sor® Non-Contact V	oltage Tester	

Continuity Tester

- Checks continuity of dead circuits and ground on conduit systems and identifies wires in multi-wire cables
- Light signal indicates completed circuit
- Bulb-in end can serve as flashlight
- Pocket clip functions as probe
- Removable 4-ft. test lead with alligator clip

1-year warranty

Description	Cat. No.
Continuity Tester	61-030

Description	Cat. No.
VoltAware™ Non-Contact Voltage Tester	61-025

61-051

m

E-Z Check[®] Circuit Testers Tests for correct wiring, open ground, reverse polarity, open hot, open neutral, hot on

- neutral, hot and ground reversed with open hot, and ground fault interruption in 3-wire, 120VAC circuits
- No-slip ergonomic design maximizes comfort
- Premium neon lamps prevent false readings
- Tough, impact-resistant case

2-year warranty	
-----------------	--

Description	Cat. No.
E-Z Check [®] Plus GFCI Circuit Tester	61-051
E-Z Check [®] Circuit Tester	61-035

Receptacle Testers

 Warns against faulty wiring in 3-wire receptacles 	61-501	
For use on 120VAC circuits		
1-year warranty		cŲLus
Description		Cat. No.

Description	Cat. No.
GFCI Receptacle Tester	61-501
Receptacle Tester	61-500

Test-Glo[™] Circuit Tester

Industrial-quality tester checks voltage from 80V to 600V AC/DC Neon test lamp at front of probe Resistors reduce voltage reaching leads 24-in. lead — rated 1,000V 1-year warranty Description Cat. No. Test-Glo™ Circuit Tester 61-040





voltage indication on or off.

Cat. No.

61-063

Test & Measurement

Digital Light Meter

- Auto or manual ranging
- Measures in four ranges up to 20,000 FC or 200,000 Lux
- +/- 3% basic accuracy
- Data hold mode
- Max reading mode
- Auto zero adjustment
- Low battery indication
- Auto power off
- Remote sensor with 59 in. (1.5m) cable



Infrared Thermometer

- Measurement range: -76°F to 932°F
- Distance spot: 12:1
- Modes: Ave., Difference, Hi/Lo limits w/alarm, Max, Min, Lock
- Emissivity Range: Adjustable from 0.1 to 1
- Precision K-type thermocouple (optional)
- Backlight
- Auto power off
- Low battery indicator
- 2-year warranty



Description	Cat. No.
Digital Light Meter	61-686

Includes: Carrying Case.



	Description	Cat. No.
	Infrared Thermometer	61-685
	Includes: Carrying Case.	
Access	ories	
Optiona	I	

Optional		
K-type Thermocouple	61-461	

Specifications	Range & Resolution	Accuracy
	61-	685
Object Temperature	-27 to 932°F (33 to 500°C)	+/- 2% or +/- 4°F (+/-2°C)
Ambient Temperature	73 +/-5°F (23 +/-3 °C)	of reading whichever is greater

3-Phase/Motor Rotation Tester

- Identifies three-phase sequence
- Indicates motor rotation
- Checks for open phases
- For use up to 600V
- 2-year warranty
 Includes carrying case



C	C	N12966	

Description	Cat. No.
3-Phase/Motor Rotation Tester	61-521

3-Phase Sequence Test	er 🥢
For use up to 600V	
Color-coded insulators over alligator clips	
Shock resistant housing	

- Easy to read
- 2-year warranty

Includes carrying case



Description	Cat. No.
3-Phase Sequence Tester	61-520