

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

**Picture
Not Available**

For more Information
please call

1-800-Belden1



General Description:

Access Control Cable, Riser-CMR, 4-18 AWG conductors, 6-22 AWG conductors with Beldfoil® shield, 4-22 AWG conductors, 4-22 AWG conductors, All conductors stranded bare copper with FR-PVC insulation, Each cable has PVC jacket, Banana Peel® No overall jacket

Usage (Overall)

Suitable Applications: Access Control

Twisted Pair

Physical Characteristics
Individual Shield

Multi Conductor

Physical Characteristics
Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
4	22	7x30	BC - Bare Copper	0.030
4	22	7x30	BC - Bare Copper	0.030
6	22	7x30	BC - Bare Copper	0.030
4	18	7x26	BC - Bare Copper	0.047

Insulation

Insulation Material:

Insulation Material	Dia. (in.)	AWG
F-R PVC - Flame Retardant Polyvinyl Chloride	0.049	22
F-R PVC - Flame Retardant Polyvinyl Chloride	0.066	

Insulation Color Code Chart:

Number	Color	Description
1	Black	Door Contact 1
2	Red	Door Contact 2
3	White	Door Contact 3
4	Green	Door Contact 4
5	Black	Rex/Spare 1
6	Red	Rex/Spare 2
7	White	Rex/Spare 3
8	Green	Rex/Spare 4
9	Black	Lock/Power 1
10	Red	Lock/Power 2
11	White	Lock/Power 3
12	Green	Lock/Power 4
13	Red	Card Reader 1
14	White	Card Reader 2
15	Green	Card Reader 3
16	Yellow	Card Reader 4
17	Orange	Card Reader 5
18	Black	Card Reader 6

Individual Shield

Outer Shield

Outer Shield Material:

AWG	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
22	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Card Reader

Outer Shield Drain Wire AWG:

Component	AWG	Stranding	Drain Wire Conductor Material
Card Reader	24	Solid	TC - Tinned Copper

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Outer Jacket

Outer Jacket Diameter:

Component #	Nom. Dia. (in.)
Door Contact	0.140
Rex/Spare	0.161
Reader	0.189
Lock/Power Card	0.202

Outer Jacket Ripcord: Yes

Outer Jacket Color Code Chart:

Number	Color	Description
1	White	Door Contact
2	Blue	Rex/Spare
3	Orange	Card Reader
4	Gray	Lock/Power

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Description	Freq. (MHz)	Capacitance (pF/ft)
Card Reader	1.000	56.000

Nom. Capacitance Conductor to Conductor:

Description	Freq. (MHz)	Capacitance (pF/ft)
Door Contact	1.000	46.000
Rex/Spare	1.000	46.000
Card Reader	1.000	31.000
Lock Power	1.000	38.000

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Door Contact	16.100
Rex/Spare	16.100
Card Reader	16.300
Lock Power	6.500

Nom. Inner Shield DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Card Reader	13.900

Max. Operating Voltage - Other:

Voltage
300 V RMS

Max. Recommended Current:

Description	Current
Door Contact	2.8 Amps @ 25C ambient (10C temperature rise)
Rex/Spare	2.8 Amps @ 25C ambient (10C temperature rise)
Card Reader	2.0 Amps @ 25C ambient (10C temperature rise)
Lock Power	4.0 Amps @ 25C ambient (10C temperature rise)

Physical Characteristics (Overall)

Conductor

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Overall Cable

Overall Nominal Diameter: 0.425 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 94 lbs/1000 ft.

Max. Recommended Pulling Tension: 217 lbs.

Min. Bend Radius/Minor Axis: 4.250 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Applicable Patents:

Country

www.belden.com/p

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 658GMS

Notes (Overall)

Notes: Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
558GMS 0001000	1,000 FT	103.000 LB	NONE	C	4C18 + 4C22 + 6C22 SHLD + 4C22

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 02-28-2014

© 2014 Belden, Inc.
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.