

## 9265 Composite - ENG, EFP and CCTV Cable

		<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
---	--	---

### Description:

22 AWG stranded (7x30) conductors, foam polyethylene insulation (coax) and PVC (Pairs) insulation, coax w/BC braid shield (95% coverage), (1) twisted pair w/Beldfoil® shield, 22 AWG drain wire, PVC jacket.

### PHYSICAL CHARACTERISTICS:

#### COAX:

Number of Coax	1
RG Type (Single Coax)	59/U

#### CONDUCTOR :

Coax AWG	22
Coax Stranding	7x30
Coax Conductor Diameter	.030 in.
Coax Conductor Material	BC - Bare Copper

#### INSULATION :

Coax Insulation Material	FPE - Foam Polyethylene
Coax Insulation Diameter	.146 in.

#### INNER SHIELD :

Coax Inner Shield Type	Braid
Coax Inner Shield Material	BC - Bare Copper
Coax Inner Shield % Coverage	95 %

#### TWISTED PAIR CABLE(S):

#### CONDUCTOR :

Number of Pairs	1
Twisted Pair AWG	22
Twisted Pair Stranding	7x30
Twisted Pair Conductor Diameter	.030 in.
Twisted Pair Conductor Material	TC - Tinned Copper

#### INSULATION :

Twisted Pair Insulation Material	PVC - Polyvinyl Chloride
Twisted Pair Insulation Diameter	.054 in.

#### INNER SHIELD :

Twisted Pair Inner Shield Material Trade Name	Beldfoil® (Z-Fold®)
---	---------------------

**9265 Composite - ENG, EFP and CCTV Cable**

Twisted Pair Inner Shield Type	Tape
Twisted Pair Inner Shield Material	Aluminum Foil-Polyester Tape
Twisted Pair Inner Shield % Coverage	100 %
Twisted Pair Inner Shield Drain Wire AWG	22
Twisted Pair Inner Shield Drain Wire Stranding	7x30
Twisted Pair Inner Shield Drain Wire Diameter	.030 in.
Twisted Pair Inner Shield Drain Wire Cond.Material	TC - Tinned Copper

**INNER JACKET :**

Twisted Pair Inner Jacket Color Code Chart	Black, Red
--	------------

**OVERALL CABLING:**

**OUTER JACKET :**

Overall Cabling Outer Jacket Material	PVC - Polyvinyl Chloride
---------------------------------------	--------------------------

**OVERALL DIAMETER :**

Overall Composite Cabling Nominal Diameter	.242 x .470 in.
--	-----------------

**MECHANICAL CHARACTERISTICS:**

**OVERALL CABLING:**

Overall Cabling Operating Temperature Range	-40°C To +60°C
Overall Cabling Non-UL Temperature Rating	60°C
Overall Cabling Bulk Cable Weight	58 lbs/1000 ft.
Overall Cabling Max. Recommended Pulling Tension	68 lbs.
Overall Cabling Min. Bend Rad.(Install)/Minor Axis	2.5 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**COAX:**

**APPLICABLE STANDARDS :**

Coax EU CE Mark (Y/N)	No
-----------------------	----

**OVERALL CABLING:**

**APPLICABLE STANDARDS :**

Overall Cabling NEC/(UL) Specification	CL2
Overall Cabling AWM Specification	UL Style 20006
Overall Cabling EU RoHS Compliant (Y/N)	Yes
Overall Cabling EU RoHS Compliance (mm/dd/yyyy):	04/01/2005

**FLAME TEST :**

Overall Cabling UL Flame Test	UL1685 UL Loading
-------------------------------	-------------------

**PLENUM/NON-PLENUM :**

Overall Cabling Plenum (Y/N)	N
------------------------------	---

**ELECTRICAL CHARACTERISTICS:**

**COAX:**

**9265 Composite - ENG, EFP and CCTV Cable**

Coax Nom. Characteristic Impedance	75 Ohms
Coax Nom. Inductance	.09 µH/ft
Coax Nom. Capacitance Conductor to Shield	17.3 pF/ft
Coax Nominal Velocity of Propagation	78 %
Coax Nominal Delay	1.3 ns/ft
Coax Nom. Conductor DC Resistance @ 20 Deg. C	15.0 Ohms/1000 ft
Coax Nom. Inner Shield DC Resistance	2.6 Ohms/1000 ft
Coax Nom. Attenuation :	

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.3
	5			.7
	10			1.0
	50			2.1
	100			3.0

Coax Other Electrical Characteristic 1 Coax Nominal Voltage Breakdown Jacket (Shield to Ground) = 22kV RMS

**MULTICONDUCTOR CABLE(S):**

Multi-Conductor Nom. Characteristic Impedance	35 Ohms
Multi-Conductor Nom. Cap. Cond. to Shield @ 1 KHz	95.5 pF/ft
Multi-Conductor Nom. Cap. Cond. to Cond. @ 1 kHz	51.0 pF/ft
Multi-Conductor Nominal Velocity of Propagation	58 %
Multi-Conductor Nominal Outer Shield DC Resistance	11 Ohms/1000 ft
Multi-Conductor Other Electrical Characteristic 1	Twisted Pair Nominal Voltage Breakdown Jacket (Shield to Ground) = 19kV RMS

**OVERALL CABLING:**

Overall Cabling Max. Operating Voltage - UL 30 V RMS

**NOTES:**

**OVERALL CABLING:**

Overall Cabling Notes Siamese Type Construction

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9265 0101000	1 SH PR#22,1 75 OHM COAX	1000	62	BLACK	C
9265 010500	1 SH PR#22,1 75 OHM COAX	500	32.5	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 06-28-2006

---

## 9265 Composite - ENG, EFP and CCTV Cable

---

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.