

General Purpose Multi-Conductor Stranded Conductor



SPECIFICATIONS



APPLICATIONS

- Audio
- Control
- Instrumentation

CONSTRUCTION

Conductor: Stranded tinned copper
 Insulation: SR-PVC
 Outer Jacket: PVC, grey
 Temperature: -20°C to 105°C
 Options: Stranded bare copper conductors
 Other coloured outer jacket and constructions available upon request

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (lb/km)	Colour Code Chart
	No.	AWG Size	Stranding				
52-224-2202	2	22	7/30	0.131	600	12	Black/Red
52-224-2203	3	22	7/30	0.139	600	17	Black/Red/Green
52-224-2204	4	22	7/30	0.152	600	18	1
52-224-2205	5	22	7/30	0.160	600	24	1
52-224-2206	6	22	7/30	0.192	600	33	1
52-224-2207	7	22	7/30	0.203	600	34	1
52-224-2208	8	22	7/30	0.215	600	39	1
52-224-2209	9	22	7/30	0.225	600	43	1
52-224-2210	10	22	7/30	0.234	600	47	1
52-224-2212	12	22	7/30	0.251	600	55	1
52-224-2215	15	22	7/30	0.275	600	65	2
52-224-2220	20	22	7/30	0.323	600	87	2
52-224-2225	25	22	7/30	0.354	600	105	2
52-224-2240	40	22	7/30	0.432	600	160	2
52-224-2250	50	22	7/30	0.493	600	195	2
52-224-2002	2	20	7/28	0.146	600	18	Black/Red
52-224-2003	3	20	7/28	0.154	600	18	1
52-224-2004	4	20	7/28	0.189	600	32	1
52-224-2005	5	20	7/28	0.197	600	35	1
52-224-2007	7	20	7/28	0.225	600	49	1
52-224-2009	9	20	7/28	0.249	600	62	1
52-224-2012	12	20	7/28	0.279	600	71	1
52-224-2015	15	20	7/28	0.306	600	104	2
52-224-2019	19	20	7/28	0.338	600	114	2
52-224-2025	25	20	7/28	0.380	600	146	2
52-224-1802	2	18	16/30	0.195	600	26	Black/Red
52-224-1803	3	18	16/30	0.207	600	34	1
52-224-1804	4	18	16/30	0.226	600	45	1
52-224-1805	5	18	16/30	0.237	600	51	1