

General Purpose Multi-Conductor Cont'd
Overall Foil Shield 105°C

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (LB/MFT)	Colour Code Chart
	No.	AWG Size	Stranding				
52-442-2006	6	20	7/28	0.222	600	44	1
52-442-2007	7	20	7/28	0.232	600	51	1
52-442-2008	8	20	7/28	0.253	600	54	1
52-442-2009	9	20	7/28	0.255	600	59	2
52-442-2012	12	20	7/28	0.287	600	75	2
52-442-2015	15	20	7/28	0.324	600	90	2
52-442-2019	19	20	7/28	0.354	600	114	2
52-442-2025	25	20	7/28	0.407	600	141	2
52-442-1802	2	18	16/30	0.197	600	27	1
52-442-1803	3	18	16/30	0.212	600	37	1
52-442-1804	4	18	16/30	0.232	600	45	1
52-442-1805	5	18	16/30	0.248	600	54	1
52-442-1807	7	18	16/30	0.270	600	70	1
52-442-1809	9	18	16/30	0.315	600	87	2
52-442-1812	12	18	16/30	0.369	600	110	2
52-442-1815	15	18	16/30	0.402	600	125	2
52-442-1819	19	18	16/30	0.430	600	163	2
52-442-1825	25	18	16/30	0.503	600	232	2
52-442-1830	30	18	16/30	0.534	600	254	2
52-442-1840	40	18	16/30	0.635	600	345	3
52-442-1602	2	16	26/30	0.235	600	41	1
52-442-1603	3	16	26/30	0.249	600	53	1
52-442-1604	4	16	26/30	0.278	600	66	1
52-442-1605	5	16	26/30	0.304	600	79	2
52-442-1607	7	16	26/30	0.341	600	102	2
52-442-1609	9	16	26/30	0.405	600	128	2
52-442-1612	12	16	26/30	0.440	600	165	2
52-442-1615	15	16	26/30	0.494	600	200	2
52-442-1619	19	16	26/30	0.525	600	248	2
52-442-1402	2	14	41/30	0.302	600	58	1
52-442-1404	4	14	41/30	0.350	600	94	1
52-442-1405	5	14	41/30	0.383	600	112	2
52-442-1407	7	14	41/30	0.418	600	147	2
52-442-1409	9	14	41/30	0.588	600	253	2
52-442-1415	15	14	41/30	0.723	600	392	2
52-442-1202	2	12	65/30	0.402	600	106	Black/Red

Note: All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without prior notice.

*See page 32 for corresponding Colour Code Chart