

## General Purpose Paired Cont'd

### Overall Foil Shielded Stranded

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (LB/MFT)	Colour Code Chart
	No.	AWG Size	Stranding				
52-644-1802	2	18	16/30	0.287	600	50	3
52-644-1803	3	18	16/30	0.335	600	65	3
52-644-1804	4	18	16/30	0.357	600	82	3
52-644-1806	6	18	16/30	0.406	600	118	3
52-644-1809	9	18	16/30	0.482	600	165	3
52-644-1812	12	18	16/30	0.570	600	210	3
52-644-1815	15	18	16/30	0.620	600	283	3
52-644-1819	19	18	16/30	0.772	600	335	3
52-644-1825	25	18	16/30	0.785	600	437	3
52-644-1601	1	16	26/30	0.236	600	45	3
52-644-1602	2	16	26/30	0.374	600	71	3
52-644-1603	3	16	26/30	0.399	600	95	3
52-644-1604	4	16	26/30	0.434	600	128	3
52-644-1606	6	16	26/30	0.495	600	175	3

Note: All dimensions are nominal and are subject to normal manufacturing tolerance.  
 Specifications are subject to change without prior notice

\*See page 32 for corresponding Colour Code Chart