

General Purpose Paired
Individual Foil Shielded



SPECIFICATIONS



APPLICATIONS

- Audio
- Control
- Instrumentation requiring superior circuit isolation

CONSTRUCTION

Conductor: Stranded tinned copper conductors
 Insulation: Polypropylene or polyolefin
 Individual Shield: Aluminum foil shield with stranded tinned copper drain wire over each pair
 Outer Jacket: PVC, grey
 Temperature: -20°C to 80°C
 Options: Stranded bare copper conductors
 Other coloured outer jacket and constructions available upon request

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (LB/MFT)	Colour Code Chart
	No.	AWG Size	Stranding				
52-602-2202	2	22	7/30	0.194	600	22	3
52-602-2203	3	22	7/30	0.258	600	41	3
52-602-2204	4	22	7/30	0.260	600	49	3
52-602-2206	6	22	7/30	0.329	600	70	3
52-602-2209	9	22	7/30	0.369	600	101	3
52-602-2212	12	22	7/30	0.412	600	130	3
52-602-2215	15	22	7/30	0.451	600	161	3
52-602-2219	19	22	7/30	0.530	600	234	3
52-602-2227	27	22	7/30	0.654	600	295	3
52-602-2002	2	20	7/28	0.243	600	39	3
52-602-2003	3	20	7/28	0.260	600	51	3
52-602-2004	4	20	7/28	0.288	600	65	3
52-602-2006	6	20	7/28	0.354	600	95	3
52-602-2009	9	20	7/28	0.411	600	134	3
52-602-2012	12	20	7/28	0.457	600	175	3
52-602-2015	15	20	7/28	0.524	600	215	3
52-602-1802	2	18	16/30	0.326	600	59	3
52-602-1803	3	18	16/30	0.348	600	79	3
52-602-1804	4	18	16/30	0.386	600	100	3
52-602-1806	6	18	16/30	0.447	600	140	3
52-602-1809	9	18	16/30	0.533	600	194	3
52-602-1812	12	18	16/30	0.623	600	300	3
52-602-1815	15	18	16/30	0.750	600	351	3
52-602-1602	2	16	26/30	0.368	600	81	3
52-602-1603	3	16	26/30	0.394	600	110	3
52-602-1604	4	16	26/30	0.440	600	142	3

Note: All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without prior notice

*See page 32 for corresponding Colour Code Chart