

General Purpose Paired Stranded



SPECIFICATIONS



APPLICATIONS

- Audio
- Control
- Instrumentation

CONSTRUCTION

- Conductor: Stranded tinned copper conductors
- Insulation: Semi-rigid (SR)-PVC
- Outer Jacket: PVC, grey
- Temperature: -20°C to 105°C
- Options: Stranded bare copper conductors
- Other coloured outer jacket and constructions available upon request

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (LB/MFT)	Colour Code Chart
	No.	AWG Size	Stranding				
52-324-2204	4	22	7/30	0.240	600	38	3
52-324-2206	6	22	7/30	0.294	600	52	3
52-324-2209	9	22	7/30	0.345	600	73	3
52-324-2212	12	22	7/30	0.384	600	93	3
52-324-2215	15	22	7/30	0.418	600	113	3
52-324-2002	2	20	7/28	0.239	600	33	3
52-324-2003	3	20	7/28	0.250	600	44	3
52-324-2004	4	20	7/28	0.280	600	53	3
52-324-2009	9	20	7/28	0.391	600	105	3
52-324-1804	4	18	16/30	0.354	600	77	3
52-324-1806	6	18	16/30	0.404	600	109	3
52-324-1819	19	18	16/30	0.680	600	334	3
52-324-1603	3	16	26/30	0.388	600	96	3

Note: All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without prior notice.

*See page 32 for corresponding Colour Code Chart