


NMWU Cable 300V

PVC/PVC



SPECIFICATIONS

- CSA FT1
- CSA C22.2 No. 48

*Refer to CE Code for details



CONSTRUCTION

Conductor: Annealed, soft, copper with compressed or compact stranding

Insulation: Polyvinyl Chloride (PVC)

Ground (Bonding) Conductor: Bare solid or stranded copper bonding wire

Outer Jacket: Moisture & sunlight resistant Polyvinyl Chloride (PVC), black, 60°C

Options: Long lengths available upon request

2 CONDUCTOR

Part Number	No. of Conductors	AWG Size		Insulation Thickness		Jacket Thickness		Approximate Diameter		Net Weight	
		Cond.	Bond Wire	in.	mm.	in.	mm.	in.	mm.	LB/MFT	KG/KM
11017-01-000	2	14 (1)	14 (1)	0.060	1.520	0.030	0.760	0.25x0.50	6.3x12.7	95	142
11017-03-000	2	12 (1)	14 (1)	0.060	1.520	0.030	0.760	0.27x0.53	6.8x13.6	117	173
11017-05-000	2	10 (1)	12 (1)	0.060	1.520	0.030	0.760	0.29x0.59	7.3x15.1	157	234
11017-07-000	2	8 (7)	10 (1)	0.075	1.910	0.045	1.140	0.39x0.79	9.9x20.0	270	402
11017-09-000	2	6 (7)	10 (1)	0.090	2.290	0.045	1.140	0.46x0.92	11.6x23.5	379	565

3 CONDUCTOR

Part Number	No. of Conductors	AWG Size		Insulation Thickness		Jacket Thickness		Approximate Diameter		Net Weight	
		Cond.	Bond Wire	in.	mm.	in.	mm.	in.	mm.	LB/MFT	KG/KM
11017-02-000	3	14 (1)	14 (1)	0.060	1.520	0.030	0.760	0.470	11.900	122	181
11017-04-000	3	12 (1)	14 (1)	0.060	1.520	0.030	0.760	0.500	12.800	152	227
11017-06-000	3	10 (1)	12 (1)	0.060	1.520	0.030	0.760	0.550	13.900	205	306
11017-08-000	3	8 (7)	10 (1)	0.075	1.910	0.045	1.140	0.730	18.600	351	523
11017-10-000	3	6 (7)	10 (1)	0.090	2.290	0.045	1.140	0.880	22.300	505	752
11017-16-000	3	2 (7)	8 (7)	0.090	2.290	0.080	2.030	1.170	29.800	1069	1591

Note: All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without prior notice.

Refer to CEC for Ampacity