

Battery Cable SGT



SPECIFICATION

Meets S.A.E. J1127

CONSTRUCTION

Conductor: Stranded bare copper conductors

Insulation: Polyvinyl Chloride (PVC)

Temperature: -40°C to 105°C

Voltage: 600V

Features: Flexible and resistant to oil

Option: Standard colours are red and black; other solid coloured outer jacket available upon request

Part Number	Conductor		Approx. Insulation Thickness (in.)	Approx. Diameter (in.)	Approx Weight (LB/MFT)
	AWG Size	Stranding			
06015-12-010	4	133/23	0.065	0.356	162
06015-13-010	2	259/25	0.065	0.420	236
06015-07-010	1/0	1007/30	0.065	0.515	367
06015-06-010	2/0	1292/30	0.065	0.570	473
06015-04-010	4/0	2090/30	0.078	0.706	758

Battery Cable SGR



SPECIFICATION

Meets S.A.E. J1127

CONSTRUCTION

Conductor: Stranded tinned copper conductors

Insulation: Polyvinyl Chloride (PVC)

Temperature: -40°C to 85°C

Voltage: 50V

Features: Flexible and resistant to oil

Option: Standard colours is black; other solid coloured outer jacket available upon request

Part Number	Conductor		Approx. Insulation Thickness (in.)	Approx. Diameter (in.)	Approx Weight (LB/MFT)
	AWG Size	Stranding			
18T-769265	4	7x27x0.142	0.065	0.350	162
18T-769261	1/0	19x26x0.142	0.065	0.510	367

*Note: All dimensions are nominal and are subject to normal manufacturing tolerance.
Specifications are subject to change without prior notice*