


## USEB-90 Utility Distribution Cable (Reduced)



### SPECIFICATIONS

- CSA C22.2 No 52
- FT1



### CONSTRUCTION

- Conductor:** Aluminum stranded, Class B compact or compact soft drawn copper
- Insulation:** Cross-linked Polyethylene (XLPE)
- Outer Jacket:** Polyvinyl Chloride (PVC)
- Voltage:** 600V
- Bare Neutral:** Annealed, plain copper wires
- Options:** Full Neutral available upon request  
USEB Reduced Neutral splice kits available upon request

Part Number	Conductor Type	Conductor AWG Size	Reduced Neutral Conductor No. Wires x Size (AWG)	Effective Diameter Thickness x Width		Net Weight	
				(in)	(mm)	(LBS/MFT)	(KG/KM)
09054-03-011	Copper	4	11 x 16	0.551 x 0.866	14 x 22	691	1029
09054-05-011	Copper	2	17 x 16	0.987 x 0.629	25 x 16	897	1336
09054-07-011	Copper	1/0	26 x 16	1.141 x 0.745	29 x 19	1237	1841
09055-03-011	Aluminum	4	9 x 16	0.590 x 0.905	15 x 23	282	420
09055-05-011	Aluminum	2	11 x 16	0.629 x 1.023	16 x 26	369	550
09055-07-011	Aluminum	1/0	17 x 16	0.748 x 1.181	19 x 30	538	800
09055-08-011	Aluminum	2/0	21 x 16	0.787 x 1.299	20 x 33	638	950
09055-10-011	Aluminum	4/0	33 x 16	0.866 x 1.496	22 x 38	940	1400
09055-14-011	Aluminum	300	21 x 10	1.102 x 1.811	28 x 46	1344	2000

*Note: All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without prior notice.*