EXTRA-HEAVY DUTY ALUMINUM STRAIGHT LADDER

Meets or exceeds CSA Grade 1A, ANSI Type 1A

- Rigid "Box Section" side rails, unequalled for strength and durability
- Yellow ABS, high impact non-marring end caps
- Slip-resistant round serrated aluminum rungs
- Non-slip heavy duty ribbed swivel feet with ice picks

MODEL	SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT lbs
4108	8'	14 5/8"	12 7/8"	13
4110	10'	14 5/8"	12 7/8"	15
4112	12'	14 5/8"	12 7/8"	19
4114	14'	14 5/8"	12 7/8"	22
4116	16'	14 5/8"	12 7/8"	25
4118	18'	14 5/8"	12 7/8"	28
4120	20'	14 5/8"	12 7/8"	31
4122	22'	15 3/4"	13 3/4"	41
4124	24'	15 3/4"	13 3/4"	44

EXTRA-HEAVY DUTY ALUMINUM STRAIGHT LADDER

Meets or exceeds CSA Grade 1A, ANSI Type 1A

- Heavy duty "I" beam construction, 3 1/16" x 1 1/4" rails provide stability, torque resistance and high strength to weight ratio
- Heavy duty serrated "D" rungs prevent slipping for safe and sure climbing
- Yellow ABS, high impact non-marring end caps
- Non-slip heavy duty ribbed swivel feet with ice picks

MODEL	SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT lbs
3108D	8'	17 3/4"	15 1/4"	12
3110D	10'	17 3/4"	15 1/4"	14
3112D	12'	17 3/4"	15 1/4"	18
3114D	14'	17 3/4"	15 1/4"	21
3116D	16'	17 3/4"	15 1/4"	24
3118D	18'	17 3/4"	15 1/4"	27
3120D	20'	17 3/4"	15 1/4"	30

LIGHT DUTY ALUMINUM EXTENSION

Meets or exceeds CSA Grade 3, ANSI Type 3

- Strong extruded "C" channel construction
- Slip-resistant serrated "D" rungs for safe climbing and comfort
- Blue, high impact, non-marring end caps
- Non-slip swivel feet

			BASE SECTION		FLY SECTION		
MODEL	SIZE	MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT lbs.
1216	16'	13'	15 7/8"	14 1/8"	15 1/8"	13 1/4"	19
1220	20'	17'	15 7/8"	14 1/8"	15 1/8"	13 1/4"	24
1224	24'	21'	15 7/8"	14 1/8"	15 1/8"	13 1/4"	30