SUPER-HEAVY DUTY FIBERGLASS EXTENSION

CSA Approved Grade 1, ANSI Type 1AA

OUR STRONGEST AND MOST RUGGED FIBERGLASS EXTENSION LADDER, DESIGNED AND BUILT TO WITHSTAND A LIFETIME OF DEMANDING INDUSTRIAL USE.

- Durable non-conductive fiberglass side rails in high visibility safety yellow
- Riveted rung to rail design maintains continuous strength of fibers and allows for easy repair
- Slip-resistant serrated "D" rungs for safe climbing and comfort
- Traditional raise from the rear pulley design
- Premium heavy-duty rung locks for durability
- Large heavy-duty pivot feet with slip-resistant rubber pads and ice pick

			BASE SECTION		FLY SECTION		
MODEL	SIZE	MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT lbs
9216-AA	16′	13′	17 3/8″	15″	16 5/8″	14 1/4″	40
9220-AA	20′	17′	17 3/8″	15″	16 5/8″	14 1/4″	47
9224-AA	24′	21′	17 3/8″	15″	16 5/8″	14 1/4″	56
9228-AA	28′	25′	17 3/8″	15″	16 5/8″	14 1/4″	64
9232-AA	32′	28′	17 3/8″	15″	16 5/8″	14 1/4″	72

EXTRA-HEAVY DUTY FIBERGLASS EXTENSION

CSA Approved Grade 1, ANSI Type 1A

THE #1 CHOICE OF CONTRACTORS ACROSS THE COUNTRY

- Durable non-conductive fiberglass side rails in high visibility safety yellow
- Riveted rung to rail design maintains continuous strength of fibers and allows for easy repair
- Slip-resistant serrated rungs for safe climbing (available in round or "D" profile)
- Top cross over bar allows for ladder to be raised or lowered from front and provides torsional stiffness
- Premium heavy-duty rung locks for durability
- Exclusive "1-Piece" foot assembly with spur wheel provides unequalled strength, durability and torsion resistance.

				BASE SECTION		FLY SECTION		
	MODEL	SIZE	MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT lbs
ROUND RUNG	6216	16′	13′	17 3/8″	15″	16 5/8″	14 1/4″	38
	6220	20′	17′	17 3/8″	15″	16 5/8″	14 1/4″	44
	6222	22′	19′	17 3/8″	15″	16 5/8″	14 1/4″	48
	6224	24′	21′	17 3/8″	15″	16 5/8″	14 1/4″	52
	6228	28′	25′	17 3/8″	15″	16 5/8″	14 1/4″	59
	6232	32′	28′	17 3/8″	15″	16 5/8″	14 1/4″	66
"D" RUNG	6216D	16′	13′	17 3/8″	15″	16 5/8″	14 1/4″	39
	6220D	20′	17′	17 3/8″	15″	16 5/8″	14 1/4″	46
	6222D	22′	19′	17 3/8″	15″	16 5/8″	14 1/4″	50
	6224D	24′	21′	17 3/8″	15″	16 5/8″	14 1/4″	55
	6228D	28′	25′	17 3/8″	15″	16 5/8″	14 1/4″	63
	6232D	32′	28′	17 3/8″	15″	16 5/8″	14 1/4″	70
	*6236D	36'	32'	19″	15 1/2″	17 3/4″	14 1/4″	96
	*6240D	40'	35'	19″	15 1/2″	17 3/4″	14 1/4″	106

* Traditional raise from the rear pulley system

9200/6200/5700/5400 OPTIONS

Non-slip Strip
Part #99322

Levelok Leg Leveler
Part # 21145