

RESIDENTIAL PRODUCTS

NONMETALLIC CABLE FITTINGS



650-DC2 thru
676-DC2

Zinc Die Cast - Oval Cable

Catalog Number	K.O. Size	Oval Service Cable Size		Unit Qty.	Std. Pkg.
		Height	Width		
650-DC2	1/2"	.250"	.500"	100	1000
650-HD2	1/2"	.250"	.500"	100	1000
670-DC2	3/4"	.437"	.625"	25	250
672-DC2	1"	.500"	.750"	10	100
674-DC2	1 1/4"	.625"	1.062"	10	100
675-DC2	1 1/2"	.750"	1.250"	---	25
676-DC2	2"	1.062"	1.625"	---	25



Whipper-Snap® Two Screw, Strap Type Connector

For connecting nonmetallic cable to box or enclosure. For use with one 14/2 to 10/3 or two 14/2 to 12/2 NM-B cables. Simply snap connector into electrical box. External spring-steel locking tabs secure connector to electrical box. Patented Whipper-Snap design.

UL File No. E11698

Zinc Die Cast

Catalog Number	Trade Size	K.O. Size	Unit Qty.	Std. Pkg.
841SP	3/8"	1/2"	100	1000



Knockout Insulating Bushings

Converts metallic box rough-edged holes to smooth insulated holes for protection of electrical, voice, data and video cables.

CSA File No. LR24719

UL File No. E240912

Plastic Rated 105°C

Catalog Number	K.O.	K.O. Dia.	Unit Qty.	Std. Pkg.
9791	1/2"	.875"	100	1000
9792	3/4"	1.109"	100	1000
9793	1"	1.375"	50	500
9794	1 1/4"	1.734"	50	500
9795	1 1/2"	1.984"	25	250
9796	2"	2.469"	20	100



Stud Bushings

Protects wire insulation from abrasion in metal studs. Bushing allows smooth wire pulling. Used for all pre-punched shaped holes.

UL File No. E11259



Polypropylene

Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
9882	---	50	500



NMCB-1



NMCB-2

Cable Supports

NMCB-1 positions maximum of (6) 14/2 to 10/3 NM-B cables or (4) 14/2 to 12/2 AC or MC cables. Also suitable for use with low-voltage cabling to 3/8" diameter. Furnished with (2) #8 screws for use on wood or steel stud. Complies with NEC Articles 300.4(D) and 320.23(B). Patented.

NMCB-2 is provided with a nail for use on wood studs or 3/4" thick furring strips to position nonmetallic sheath cable. Capable of positioning a single 14/2 to 10/3 NM cable or two 14/2 NM cables in each of three rectangular slots. May also be used with low-voltage cable. Low-profile design and unique self-locking fingers prevent accidental removal of cables. Grooved nail for extra gripping with stud. Patented.

cJLus File No. E161206

Polypropylene


Catalog Number	Trade Size	Unit Qty.	Std. Pkg.
NMCB-1	---	25	100
NMCB-2	---	25	100




Cable Stacker

For use on steel or wood studs to support nonmetallic sheath, communication, and data cables. Furnished with nail for wood stud. Use #8 x 1/2" self-tapping sheet metal screw for steel stud. Complies with NEC Articles 300-4(D) and 320.23(B). Patented.

cJLus File No. E161206



Metal Stud



Wood Stud

Polypropylene

Catalog Number	Size	Unit Qty.	Std. Pkg.
NMWH-43	---	25	100

CABLE RANGES:

Data / Communication Cable

Oval Openings:	1 or 2	.06" to .20" diameter
	1	.20" to .32" diameter
Round Openings:	1	.16" to .50" diameter

Nonmetallic Sheath Cable

Oval Openings:	1 or 2	14/2 AWG
	1 or 2	12/2 AWG
	1	10/2 AWG
Round Openings:	1	14/3 AWG
	1	12/3 AWG
	1	10/3 AWG