

## Primary Wire

B



### GPT Wire

Techspan GPT (General Purpose Thermoplastic) primary single conductor wire is manufactured using 100% pure copper conductors with a PVC compound that resists chemical, abrasion and heat, up to 85°C (185°F). Jacket surface is smooth enough for easy, clean wire stripping. Ideal for automotive, truck, trailers, tractor, boats, and other point-to-point, low voltage applications (up to 60 Volts). Type GPT to SAE specification J1128 meets the standard for OEM or replacement applications for general purpose requirements.

#### Mini Spools

GA	Length	O.D.	Stranding	Black	Blue	Brown	Green	Red	White	Yellow
18	50' (15.2m)	.091"	16 x 30 x .010"	668051	668052	668053	668054	668056	668057	668059
16	35' (10.7m)	.104"	19 x 29 x .011"	668061	668062	668063	668064	668065	668066	668067
14	25' (7.6m)	.119"	19 x 27 x .014"	668068	668069	668070	668071	668072	668073	668074
12	15' (4.6m)	.145"	19 x 25 x .018"	668075	668076	668983	668922	668077	668078	668928
10	10' (3m)	.175"	19 x 23 x .024"	668080	668906	668081	668980	668082	668981	668979

O.D. = Outside Diameter

#### 100' (30.5m) Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Red	White	Yellow	Grey	Orange	Pink	Purple	Tan
20	.084"	7 x 30 x .012"	767987	767988	767989	767990	767991	767992	767993	*767996	*767995		*767997	
18	.091"	16 x 30 x .010"	768000	768001	768002	768003	768005	768006	768007	768009	768004	*767994	768008	*767999
16	.104"	19 x 29 x .011"	768010	768011	768012	768013	768015	768016	768017	768019	768014	*767984	768018	
14	.119"	19 x 27 x .014"	768020	768021	768022	768023	768025	768026	768027	768029	768024		768028	
12	.145"	19 x 25 x .018"	768030	768031	768032	768033	768035	768036	768037		768034			
10**	.175"	19 x 23 x .024"	768102	768103	768104	768105	768106	768107	768108					
8	.216"	19 x 21 x .028"	768050				768155	768056						
6	.285"	7 x 19 x .014"	768060				768165							
4	.354"	7 x 27 x .014"					768175							

O.D. = Outside Diameter

Note: 8GA to 4GA supplied on metal spools

\*\* 50' (15.2m) spools

#### 1000' (305m) Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Red	White	Yellow	Grey	Orange	Purple
20	.084"	7 x 30 x .012"	*767987M	*767988M	*767989M	*767990M	*767991M	*767992M	*767993M			
18	.091"	16 x 30 x .010"	768200	768201	768202	768203	768205	768206	768207	768209	768204	768208
16	.104"	19 x 29 x .011"	768210	768211	768212	768213	768215	768216	768217	768219	768214	768218
14	.119"	19 x 27 x .014"	768220	768221	768222	768223	768225	768226	768227	768229	768224	768228
12	.145"	19 x 25 x .018"	768230	768231	768232	768233	768235	768236	768237		768234	
10	.175"	19 x 23 x .024"	768240	768241	768242	768243	768245	768246	768247			
8	.216"	19 x 21 x .028"	*768250				*768255	*768256				

O.D. = Outside Diameter

Note: 1000' spools supplied on metal spools.



#### LOOKING FOR STRIPED WIRE?

Contact Techspan for availability. Minimum Order Quantities will apply.

