

# QUICK DISCONNECTS

B

FEMALE				
Wire Range	Tab Size	Non-insulated	P.V.C.	Nylon
22-18	.110X.020	<b>FR1A 110</b>	<b>FR4A 110</b>	<b>FR6A 110</b>
	.187X.020	<b>FR1A 187</b>	<b>FR4A 187</b>	<b>FR6A 187</b>
	.250X.032	<b>FR1A 250</b>	<b>FR4A 250</b>	<b>FR6A 250</b>
16-14	.110X.020	<b>FR1B 110</b>	<b>FR4B 110</b>	<b>FR6B 110</b>
	.187X.020	<b>FR1B 187</b>	<b>FR4B 187</b>	<b>FR6B 187</b>
	.250X.032	<b>FR1B 250</b>	<b>FR4B 250</b>	<b>FR6B 250</b>
12-10	.250X.032	<b>FR1C 250</b>	<b>FR4C 250</b>	<b>FR6C 250</b>

FEATURES: The tin plated brass connector features the rolled edge design for maximum spring-like insertion/withdrawal force. Protruding lip and beveled floor with detent aid in insertion and retention of tab and a wire stop prevents over-insertion of stripped wire. Other sizes and styles available. Check with factory for .187 x .032 size parts.

MALE				
Wire Range	Tab Size	Non-insulated	P.V.C.	Nylon
22-18	.187X.020	<b>MT1A 187</b>	<b>MT4A 187</b>	<b>MT6A 187</b>
	.250X.032	<b>MT1A 250</b>	<b>MT4A 250</b>	<b>MT6A 250</b>
16-14	.187X.020	<b>MT1B 187</b>	<b>MT4B 187</b>	<b>MT6B 187</b>
	.250X.032	<b>MT1B 250</b>	<b>MT4B 250</b>	<b>MT6B 250</b>
12-10	.250X.032	<b>MT1C 250</b>	<b>MT4C 250</b>	<b>MT6C 250</b>

FEATURES: Pure copper tab plated with zinc chromate for maximum insertion/withdrawal values affording greater corrosion resistance. Lip for easier insertion. NOTE: Consult factory for .187 x .032 size parts.

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

P.V.C. & Nylon disconnects rated -55°C to 105°C

Approved installation tool: RHT-1992/192850004,

RHT-1990/192840010/11/13 (insulated)

Economy installation tools: 453, HTS1000, RAT-NINS, RAT-DISC (insulated)

## DUAL ADAPTERS



Part Number **MMFA** Converts one .250 x .032" male tab to two male tabs. Dual Male-Female Adapter. Also Available in .187 x .020 Part Number **MMFA187**



**Copper Stranded Wire Only**  
 (All items listed on this page)

## FLAG DISCONNECTS

Wire Range	Tab Size	Non-insulated
22-18	.187X.020	<b>FLFR1A 187<sup>†</sup></b>
	.250X.032	<b>FLFR1A 250<sup>†</sup></b>
16-14	.187X.020	<b>FLFR1B 187<sup>†</sup></b>
	.250X.032	<b>FLFR1B 250<sup>†</sup></b>
12-10	.250X.032	<b>FLFR1C 250<sup>††</sup></b>

Add suffix "M" for 1000 pack  
 Add suffix "P" for Pro Pack  
 (Quantities vary by Part #)


<sup>†</sup>Approved installation tool: RHT-NIFG/192840031

<sup>††</sup>Economy installation tool: HTS2000

\* Not CSA or UL Listed

## RECEPTACLES

INSULATED TAB RECEPTACLE



Part No. **MDT250** For connecting two .250 x .032 Female Quick Disconnects

