




FULLY INSULATED FEMALE DISCONNECTS NYLON SINGLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C

600V

Part #	AWG	COLOUR	TAB SIZE
CFR4NA250F	22-18	RED	.250"
CFR4NA187F	22-18	RED	.187"
CFR4NB250F	16-14	BLUE	.250"
CFR4NB187F	16-14	BLUE	.187"
CFR4NC250F	12-10	YELLOW	.250"



Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: RHT-1991/192850004

Economy installation tools: RAT-FIDISC, 453, HTS1000



FULLY INSULATED MALE DISCONNECTS NYLON SINGLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C

600V

Part #	AWG	COLOUR	TAB SIZE
CM4TNA250F	22-18	RED	.250"
CM4TNA187F	22-18	RED	.187"
CM4TNB250F	16-14	BLUE	.250"
CM4TNB187F	16-14	BLUE	.187"
CM4TNC250F	12-10	YELLOW	.250"



Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: RHT-1991/192850004

Economy installation tools: RAT-FIDISC, 453, HTS1000


FULLY INSULATED FEMALE FLAG DISCONNECTS - NYLON SINGLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C

600V

Part #	AWG	COLOUR	TAB SIZE
*FLFR6A250F	22-18	RED	.250"
*FLFR6B250F	16-14	BLUE	.250"
FLFR6C250F	12-10	YELLOW	.250"



Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: RHT-FIFG/192840014 (Red, Blue), 64001-2800 (Yellow)

Economy installation tools: RAT-FLAG (Red, Blue)


FULLY INSULATED FEMALE FLAG DISCONNECTS - NYLON DOUBLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C

600V

Part #	AWG	COLOUR	TAB SIZE
*FLFR6A250BF	22-18	RED	.250"
*FLFR6B250BF	16-14	BLUE	.250"
FLFR6C250BF	12-10	YELLOW	.250"



Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: RHT-AFIFG/192840014 (Red, Blue), 64001-2800 (Yellow)

Economy installation tools: -RAT-FLAG (Red, Blue)



Copper Stranded Wire Only