

# K-SPEC® ECONOMY TERMINALS



## Butt Connectors with Vinyl (PVC) Insulation – Economy

300V Rating, 75°C, Brass

Pkg	GA	Red	Blue	Yellow
		22-18 GA	16-14 GA	12-10 GA
100 pk		561231	561232	561233
500 pk		561231D	561232D	561233D



## Butt Connectors with Heat Shrink Tubing – Economy

600V Rating, 105°C, Copper

Pkg	GA	Red	Blue	Yellow
		22-18 GA	16-14 GA	12-10 GA
100 pk		561244	561245	561246
500 pk		561244D	561245D	561246D



**NEW** K-Spec Economy Terminals are packaged in re-sealable bags

## Ring Terminals with Vinyl (PVC) Insulation – Economy

600V Rating, 75°C, Copper


100 pcs/pk				500 pcs/pk					
Stud	GA	Red	Blue	Yellow	Stud	GA	Red	Blue	Yellow
		22-18 GA	16-14 GA	12-10 GA			22-18 GA	16-14 GA	12-10 GA
#6		561000	561016	561032	#6		561000D	561016D	561032D
#8		561002	561018	561033	#8		561002D	561018D	561033D
#10		561003	561019	561034	#10		561003D	561019D	561034D
1/4"		561004	561020	561035	1/4"		561004D	561020D	561035D
5/16"		561005	561021	561036	5/16"		561005D	561021D	561036D
3/8"		561006	561022	561037	3/8"		561006D	561022D	561037D
1/2"				561038	1/2"				561038D



## Spade Terminals with Vinyl (PVC) Insulation – Economy

600V Rating, 75°C, Copper

100 pcs/pk				500 pcs/pk					
Stud	GA	Red	Blue	Yellow	Stud	GA	Red	Blue	Yellow
		22-18 GA	16-14 GA	12-10 GA			22-18 GA	16-14 GA	12-10 GA
#6		561048	561061	561074	#6		561048D	561061D	561074D
#8		561049	561062	561075	#8		561049D	561062D	561075D
#10		561050	561063	561076	#10		561050D	561063D	561076D
1/4"			561064	561077	1/4"			561064D	561077D



## Male Slide Connectors with Vinyl (PVC) Insulation – Economy

300V Rating, 75°C, Brass

100 pcs/pk				500 pcs/pk					
Male Tab	GA	Red	Blue	Yellow	Male Tab	GA	Red	Blue	Yellow
		22-18 GA	16-14 GA	12-10 GA			22-18 GA	16-14 GA	12-10 GA
.110" x .020"		561378	561391		.110" x .020"		561378D	561391D	
.110" x .032"		561380			.110" x .032"		561380D		
.187" x .020"		561382	561388		.187" x .020"		561382D	561388D	
.187" x .032"		561384	561390		.187" x .032"		561384D	561390D	
.250" x .032"		561351	561356	562115	.250" x .032"		561351D	561356D	562115D



## Female Flag Disconnects with Nylon Insulation – Economy

300V Rating, 105°C, Copper

Pkg	GA	Red	Blue
		22-18 GA	16-14 GA
100 pk		562407	562408
500 pk		562407D	562408D



For Copper Solid and Stranded Wire only – 22-18 and 16-14 AWG ring, fork and butt splices.  
 For Copper Stranded Wire only – 12-10 AWG ring, fork and butt splices and all Male/Female Disconnects.