

A

Terminals & Connectors (K-Spec® Series)

Crimp 'N' Shrink Butt Connectors (K-Spec® Series)

600V Rating, 105°C, Copper



22-18GA



Approximate length of tubing: 1.250"

691244	5 pk
561244	100 pk
*NEW 561244J	300 pcs/Jar
561244D	500 pk


16-14GA



Approximate length of tubing: 1.250"

691245	5 pk
561245	100 pk
*NEW 561245J	300 pcs/Jar
561245D	500 pk

12-10GA



Approximate length of tubing: 1.500"

691246	5 pk
561246	100 pk
*NEW 561246J	200 pcs/Jar
561246D	500 pk



PVC Insulated Butt Connectors (K-Spec® Series)

300V Rating, 75°C, Brass



22-18GA



691231	11 pk
561231	100 pk
561231D	500 pk

16-14GA



691232	10 pk
561232	100 pk
561232D	500 pk

12-10GA



691233	7 pk
561233	100 pk
561233D	500 pk

PVC Insulated Ring Terminals (K-Spec® Series)

600V Rating, 75°C, Copper



22-18GA



Stud Size #6	Stud Size #8	Stud Size #10	Stud Size 1/4"	Stud Size 5/16"	Stud Size 3/8"
691000	691002	691003	691004	691005	691006
11 pk	100 pk	11 pk	100 pk	100 pk	100 pk
561000	561002	561003	561004	561005	561006
100 pk	100 pk	100 pk	100 pk	100 pk	100 pk
561000D	561002D	561003D	561004D	561005D	561006D
500 pk	500 pk	500 pk	500 pk	500 pk	500 pk

16-14GA



Stud Size #6	Stud Size #8	Stud Size #10	Stud Size 1/4"	Stud Size 5/16"	Stud Size 3/8"
691016	691018	691019	691020	691021	691022
11 pk	11 pk	10 pk	9 pk	100 pk	7 pk
561016	561018	561019	561020	561021	561022
100 pk	100 pk	100 pk	100 pk	100 pk	100 pk
561016D	561018D	561019D	561020D	561021D	561022D
500 pk	500 pk	500 pk	500 pk	500 pk	500 pk

12-10GA



Stud Size #6	Stud Size #8	Stud Size #10	Stud Size 1/4"	Stud Size 5/16"
691032	691033	691034	691035	691036
7 pk	100 pk	7 pk	6 pk	100 pk
561032	561033	561034	561035	561036
100 pk	100 pk	100 pk	100 pk	100 pk
561032D	561033D	561034D	561035D	561036D
500 pk	500 pk	500 pk	500 pk	500 pk



Stud Size 3/8"	Stud Size 1/2"
691037	691038
6 pk	6 pk
561037	561038
100 pk	100 pk
561037D	561038D
500 pk	500 pk

Crimp Tools can be found on pages 42-45

Terminals & Connectors (K-Spec® Series)

PVC Insulated Spade/Fork Terminals (K-Spec® Series)



600V Rating, 75°C, Copper

22-18GA



Stud Size #6
561048 100 pk
561048D 500 pk




Stud Size #8
561049 100 pk
561049D 500 pk



Stud Size #10
561050 100 pk
561050D 500 pk


16-14GA



Stud Size #6
561061 100 pk
561061D 500 pk



Stud Size #8
561062 100 pk
561062D 500 pk



Stud Size #10
691063 9 pk
561063 100 pk
561063D 500 pk



Stud Size 1/4"
561064 100 pk
561064D 500 pk

12-10GA



Stud Size #6
561074 100 pk
561074D 500 pk



Stud Size #8
561075 100 pk
561075D 500 pk



Stud Size #10
691076 7 pk
561076 100 pk
561076D 500 pk



Stud Size 1/4"
561077 100 pk
561077D 500 pk

Fully Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)



300V Rating, Brass, Nylon (105°C), PVC (75°C)

22-18GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561354 100 pk
561354D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561353 100 pk
561353D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561345 100 pk
561345D 500 pk

16-14GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561357 100 pk
561357D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561358 100 pk
561358D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561346 100 pk
561346D 500 pk

12-10GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561623 100 pk
561623D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561621 100 pk
561621D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561347 100 pk
561347D 500 pk

A





Terminals & Connectors (K-Spec® Series)





PVC Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)






300V Rating, 75°C, Brass




22-18GA





			
Female quick disconnect Tab Size .110" x .020"	Male quick disconnect Tab Size .110" x .020"	Female quick disconnect Tab Size .110" x .032"	Male quick disconnect Tab Size .110" x .032"
561377 100 pk	561378 100 pk	561379 100 pk	561380 100 pk
561377D 500 pk	561378D 500 pk	561379D 500 pk	561380D 500 pk




			
Female quick disconnect Tab Size .187" x .020"	Male quick disconnect Tab Size .187" x .020"	Female quick disconnect Tab Size .187" x .032"	Male quick disconnect Tab Size .187" x .032"
561381 100 pk	561382 100 pk	561383 100 pk	561384 100 pk
561381D 500 pk	561382D 500 pk	561383D 500 pk	561384D 500 pk



		
Female quick disconnect Tab Size .205" x .020"	Female quick disconnect Tab Size .250" x .032"	Male quick disconnect Tab Size .250" x .032"
561395 100 pk	561352 100 pk	561351 100 pk
561395D 500 pk	561352D 500 pk	561351D 500 pk

16-14GA




		
Female quick disconnect Tab Size .110" x .020"	Male quick disconnect Tab Size .110" x .020"	Female quick disconnect Tab Size .110" x .032"
561396 100 pk	561391 100 pk	561397 100 pk
561396D 500 pk	561391D 500 pk	561397D 500 pk

			
Female quick disconnect Tab Size .187" x .020"	Male quick disconnect Tab Size .187" x .020"	Female quick disconnect Tab Size .187" x .032"	Male quick disconnect Tab Size .187" x .032"
561387 100 pk	561388 100 pk	561389 100 pk	561390 100 pk
561387D 500 pk	561388D 500 pk	561389D 500 pk	561390D 500 pk

		
Female quick disconnect Tab Size .205" x .020"	Female quick disconnect Tab Size .250" x .032"	Male quick disconnect Tab Size .250" x .032"
561398 100 pk	691355 11 pk	691356 10 pk
561398D 500 pk	561355 100 pk	561356 100 pk
	561355D 500 pk	561356D 500 pk

	
Female quick disconnect Tab Size .312" x .032"	Female quick disconnect Tab Size .375" x .047"
561399 100 pk	561400 100 pk
561399D 500 pk	561400D 500 pk

12-10GA

		
Female quick disconnect Tab Size .250" x .032"	Male quick disconnect Tab Size .250" x .032"	Female quick disconnect Tab Size .375" x .047"
692093 6 pk	692115 7 pk	561401 100 pk
562093 100 pk	562115 100 pk	561401D 500 pk
562093D 500 pk	562115D 500 pk	

Crimp Tools can be found on pages 42-45

Terminals & Connectors (K-Spec® Series)

PVC Insulated Bullet Connectors (K-Spec® Series)



300V Rating, 75°C, Brass

22-18GA



.156" Female Receptacle

561248	100 pk
561248D	500 pk



.156" Male Snap Plug

561247	100 pk
561247D	500 pk

16-14GA – 2 Way (Clear)



Mates with two .156" Males

691261	5 pk
561261	100 pk
561261D	500 pk

16-14GA



.156" Female Receptacle

691289	8 pk
561289	100 pk
561289D	500 pk



.156" Male Snap Plug

691251	8 pk
561251	100 pk
561251D	500 pk



.197" Female Receptacle

561258	100 pk
561258D	500 pk



.197" Male Snap Plug

561257	100 pk
561257D	500 pk

12-10GA



.197" Female Receptacle

561260	100 pk
561260D	500 pk



.197" Male Snap Plug

561259	100 pk
561259D	500 pk

PVC Insulated Piggy Back Connectors (K-Spec® Series)



300V Rating, 75°C, Brass

22-18GA



562415	100 pk
562415D	500 pk

16-14GA



562416	100 pk
562416D	500 pk

12-10GA



562399	100 pk
562399D	500 pk

PVC Insulated Instant Connectors (K-Spec® Series)



600V Rating, 75°C, Copper

22-18GA



Tap Splice-Red

561370	100 pk
561370D	500 pk

16-14GA



Tap Splice-Blue

691371	3 pk
561371	100 pk
561371D	500 pk

12-10GA



Tap Splice-Yellow

691372	2 pk
561372	100 pk
561372D	500 pk

PVC Insulated Pin Terminals (K-Spec® Series)



600V Rating, 75°C, Copper

22-18GA



562418	100 pk
562418D	500 pk

16-14GA



562419	100 pk
562419D	500 pk

12-10GA



562417	100 pk
562417D	500 pk

A

Terminals & Connectors (K-Spec® Series)

Nylon Insulated Closed End Connectors (K-Spec® Series)

300V Rating, 105°C, Copper



22-18GA



561293 100 pk
561293D 500 pk

16-14GA



561294 100 pk
561294D 500 pk

12-10GA



561295 100 pk
561295D 500 pk

Nylon Insulated Female Flag Connectors (K-Spec® Series)

300V Rating, 105°C, Copper



22-18GA



.187" x .032"

***NEW** 562398 100 pk
***NEW** 562398D 500 pk



.250" x .032"

562407 100 pk
562407D 500 pk

16-14GA



.250" x .032"

562408 100 pk
562408D 500 pk

Non-Insulated Butt Connectors (K-Spec® Series)



600V Rating, 75°C, Copper. Butted Seam

22-18GA



*562404 100 pk
*562404D 500 pk

16-14GA



*562405 100 pk
*562405D 500 pk

12-10GA



*562406 100 pk
*562406D 500 pk

The following part numbers have been discontinued, and replaced with the corresponding part numbers.

Old Part#	⇒	New Part#
762401(M)	⇒	562404(D)
762402(M)	⇒	562405(D)
762403(M)	⇒	562406(D)

Non-Insulated Ring Terminals (K-Spec® Series)



600V Rating, 75°C, Copper. Butted Seam

22-18GA



Stud Size #6
*562000 100 pk
*562000D 500 pk



Stud Size #8
*562001 100 pk
*562001D 500 pk



Stud Size #10
*562002 100 pk
*562002D 500 pk



Stud Size 1/4"
*562003 100 pk
*562003D 500 pk

16-14GA



Stud Size #6
*562004 100 pk
*562004D 500 pk



Stud Size #8
*562005 100 pk
*562005D 500 pk



Stud Size #10
*562006 100 pk
*562006D 500 pk



Stud Size 1/4"
*562007 100 pk
*562007D 500 pk

12-10GA



Stud Size #8
*562008 100 pk
*562008D 500 pk



Stud Size #10
*562009 100 pk
*562009D 500 pk



Stud Size 1/4"
*562010 100 pk
*562010D 500 pk



Stud Size 5/16"
*562011 100 pk
*562011D 500 pk



Stud Size 3/8"
*562012 100 pk
*562012D 500 pk

Crimp Tools can be found on pages 42-45

Terminal Assortment Kits (K-Spec® Series)

A

Solderless Terminal Assortment Kit (K-Spec® Series)

560500 Green metal storage tray with carrying handle comes complete with 500 pieces of 20 widely used K-Spec® Series Solderless Terminals. Tray has space for a Crimp Tool. Each part number is indexed on an affixed reference chart for easy identification and quick reorder. Dimensions: 13-1/2"W x 10"L x 1-5/8"H

Kit Contents:

Part#	Qty	Part#	Qty	Part#	Qty
561003	25 pcs	561250	25 pcs	561352	25 pcs
561016	25 pcs	561251	25 pcs	561353	25 pcs
561019	25 pcs	561261	25 pcs	561355	25 pcs
561231	25 pcs	561289	25 pcs	561356	25 pcs
561232	25 pcs	561345	25 pcs	561358	25 pcs
561233	25 pcs	561346	25 pcs	562093	25 pcs
561247	25 pcs	561351	25 pcs		



560500 Solderless Terminal Assortment Kit in a Metal Storage Tray (K-Spec® Series)

Solderless Terminal Assortment Kit (K-Spec® Series)

These handy assortment kits come complete with 175 pieces of 18 widely used K-Spec® Series PVC Insulated Solderless Terminals in plastic storage trays. Each part number is indexed on an affixed reference chart for easy identification and quick reorder. Dimensions: 8-1/4"W x 4-1/8"L x 1-1/8"H. These kits are available with or without a crimp tool under the following part numbers:

560175 (with tool)

560175NT (without tool)

Both Kits' Contents:

Part#	Qty	Part#	Qty	Part#	Qty
561003	10 pcs	561247	10 pcs	561346	10 pcs
561016	10 pcs	561250	10 pcs	561351	10 pcs
561019	10 pcs	561251	10 pcs	561352	10 pcs
561231	10 pcs	561261	10 pcs	561355	10 pcs
561232	10 pcs	561289	10 pcs	561356	10 pcs
561233	10 pcs	561345	10 pcs	562093	10 pcs

Available with or without a crimp tool... your choice!



560175 Solderless Terminal Assortment Kit in a Plastic Storage Tray (K-Spec® Series) with Tool



560175NT Solderless Terminal Assortment Kit in a Plastic Storage Tray (K-Spec® Series)

A

Non-Insulated Terminals



Non-Insulated Terminals & Connectors are made of 100% pure copper for maximum conductivity with the addition of tin plating for marine applications. Where applicable, serrated barrel offers increased pullout strength of hard-to-crimp solid or stranded wire. Can be crimped or soldered. 600V rating.

Comparing Butted Seam & Brazed Seam Terminals & Connectors (Non-Insulated)

BUTTED SEAMS are formed when the metal is stamped, rolled, and butted to create the connector barrel. Should only be used with stranded wire and must be crimped in the proper place to avoid opening the seam.

BRAZED SEAMS are formed much like a butted seam, except the seam is brazed together with a solder alloy. This provides a better crimp, as the barrel will not open under stress or pull. May be used with solid or stranded wire and can be crimped on any side of the barrel without opening the seam.



Butted Seam



Brazed Seam

Comparing Butted Seam & Seamless Butt Connectors & Splices (Non-Insulated)

BUTTED SEAMS are formed when the metal is stamped, rolled, and butted to create the connector barrel. Should only be used with stranded wire and must be crimped in the proper place to avoid opening the seam.

Generally, the **SEAMLESS** feature is only available for butt connectors or butt splices. The barrel is created to form one seamless point of metal. This eliminates the problem of the barrel opening. May be used with solid or stranded wire.



Butted Seam



Seamless



NOTE: SEAMLESS CONNECTORS ARE LONGER THAN BUTTED SEAM CONNECTORS



Non-Insulated Terminals:
Packaging Variations

Non-Insulated Terminals & Connectors

Non-Insulated Butt Connectors (Seamless)

22-18GA

	
762404	100 pk
762404M	1000 pk

16-14GA


	
762405	100 pk
762405M	1000 pk

12-10GA

	
762406	100 pk
762406M	1000 pk




8GA

	
762429	25 pk
762429B	500 pk

6GA

	
762456	25 pk

4GA

	
762457	25 pk
762457B	500 pk

The following part numbers have been discontinued, and replaced with the corresponding part numbers. You can now find these on pages 34 & 40.

Old Part#	⇒	New Part#
762401(M)	⇒	562404(D)
762402(M)	⇒	562405(D)
762403(M)	⇒	562406(D)

Non-Insulated 'Step-Down' Butt Connectors (Seamless)

20-18GA ⇒ 16-14GA

	
*762481	100 pk
*762481M	1000 pk

16-14GA ⇒ 12-10GA

	
*762482	100 pk
*762482M	1000 pk

12-10GA ⇒ 8GA

	
*762483	100 pk
*762483M	1000 pk



Non-Insulated Quick Disconnects/Slide Connectors


Butted Seam





22-18GA

			
Female quick disconnect Tab Size: .110"	Female quick disconnect Tab Size: .187"	Female quick disconnect Tab Size: .25"	Male quick disconnect Tab Size: .25"
762026 100 pk	762028 100 pk	762412 100 pk 762412M 1000 pk	762420 100 pk 762420M 1000 pk

16-14GA

				
Female quick disconnect Tab Size: .110"	Female quick disconnect Tab Size: .187"	Male quick disconnect Tab Size: .187"	Female quick disconnect Tab Size: .25"	Male quick disconnect Tab Size: .25"
762032 100 pk 762032M 1000 pk	762034 100 pk 762034M 1000 pk	762033 100 pk	762413 100 pk 762413M 1000 pk	762421 100 pk

	
Female quick disconnect Tab Size: .25"	Male quick disconnect Tab Size: .25"
762414 100 pk 762414M 1000 pk	762422 100 pk 762420M 1000 pk

Non-Insulated Female Flag Connectors

Butted Seam



22-18GA

	
Tab Size .25"	
762410	100 pk

16-14GA



	
Tab Size .25"	
762411	100 pk
762411M	1000 pk

12-10GA

	
Tab Size .25"	
762423	100 pk
762423M	1000 pk

Non-Insulated Adapters



	
Non-insulated male/female/ male quick disconnect adapter, converts one .25" tab connection to two connections	Non-insulated female/ male/male adapter, converts one male tab to two male tabs.
762098 25 pk 762098M 1000 pk	762373 25 pk 762373M 1000 pk