STELPRO

WALL FAN HEATER ALUMINUM - WFA SERIES

WHEN DURABILITY AND PERFORMANCE MEET DESIGN

In need of a solid, stylish heater to warm your clients in the lobby or entrance of your business? The ALUX™ series wall fan heater (WFA) with its remarkable rush of warm air is the solution. It has an aluminum extrusion grille that is striking, modern and unbelievably resistant. Imagine, no more dents or rust! The WFA can be installed recessed or surface mounted on the wall and is available in a large array of wattages to meet all your needs.









EXTRUDED ALUMINUM PROFILE WITH A UNIQUE AND LUXURIOUS DESIGN

EXTREMELY RUGGED, IMPACT AND RUST RESISTANT

WIDE RANGE OF MODELS AND HEATING CAPACITIES

INCLUDING A SINGLE UNIT OF 4800 W

SIGNATURE NICHROME ELEMENT

OFFERING SUPERIOR PERFORMANCE AND IMMEDIATE HEAT!

	<u>ACCESSORIES</u>	
<u>PRODUCT</u>	<u>DESCRIPTION</u>	
WFAT1	built-in single pole thermostat [120 V-347 V]	
WFAT2	built-in double pole thermostat [120 V-347 V]	
WFASA1*	surface adapter (single unit)	
WFASA2*	surface adapter (double unit)	
WFASA3*	surface adapter (triple unit)	
WFADIS-30*	disconnect switch kit 600 V/30 A, 2 poles	
WFADIS-40*	disconnect switch kit 600 V/40 A, 2 poles/3 poles	
WFADIS-60*	disconnect switch kit 600 V/60 A, 2 poles/3 poles	

^{*} Add W for white, SW for silica white, A for almond, S for silver, BK for black, CHAR for textured charcoal, NIC for nickel, CHA for champagne, LB for light bronze, BR for dark brown or CAP for clear anodized (paint)

RECOMMENDED LOCATIONS

LOBBY, ENTRANCE, CORRIDOR, FACTORY, WAREHOUSE, STAIRWELL

COLOURS

white, silica white, almond, silver, black, textured charcoal, nickel, champagne, light bronze, dark brown, clear anodized (paint)

FINISH

epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet
- aluminum extrusion grille
- top air intake with bottom air discharge
- quiet helicoidal fan: single unit 1 x 160 CFM - double unit 2 x 160 CFM triple unit 3 x 160 CFM
- thermal protection with automatic reset
- totally enclosed, permanently lubricated motor

ELEMENT

high quality nichrome element producing instant heat

INSTALLATION

- wall mounted
- recessed or surface mounted with surface adapter (optional)





^{*} Factory installation