


Flexible Cord

Steel Fittings




- Made of corrosion resistant, zinc plated machined steel
- Raintight and strainrelief
- Has a neoprene rubber bushing that ensures a permanent raintight seal around the cord outer jacket and a galvanized steel pressure ring that prevents distortion of the bushing when subjected to the tightening of the gland nut

CICG50A250 / CICG150D1375



CICG9050-A250 / CICG9075-B850



Cat. No.	Trade Size (in.)	KO Size (in.)	Cable Dimensions (in.)		Throat (in.)	Dimensions (in.)		
			Min.	Max.		A	B	C
Cord Grip Fittings (Machined Steel / Zinc Plated)								
CICG50A250	1/2	1/2	0.150	0.250	0.640	1-1/32	13/16	1-5/16
CICG50A350			0.250	0.350				
CICG50A450			0.350	0.460				
CICG50A560			0.450	0.560				
CICG50A650			0.560	0.650				
CICG75A250	3/4	3/4	0.150	0.250	0.687	1-1/32	13/16	1-5/16
CICG75A350			0.250	0.350				
CICG75A450			0.350	0.460				
CICG75A560			0.450	0.560				
CICG75A650			0.550	0.650				
CICG75B750	1	1	0.650	0.750	0.845	1-1/4	1-1/32	1-9/16
CICG75B850			0.750	0.850				
CICG100B560	1	1	0.450	0.560	0.937	1-1/4	1-1/8	1-3/4
CICG100B650			0.560	0.650				
CICG100B750			0.650	0.750				
CICG100B850			0.750	0.850				
CICG100C950			0.850	0.950				
CICG100C1050	0.950	1.050						
CICG125C850	1-1/4	1-1/4	0.750	0.850	1.187	1-1/2	1-1/4	1-5/16
CICG125C950			0.850	0.950				
CICG125D1050			0.950	1.050				
CICG125D1150			1.050	1.150				
CICG125D1250			1.150	1.250				
CICG125D1375	1.250	1.375						
CICG150D1050	1-1/2	1-1/2	0.950	1.050	1.375	2	1-5/16	2
CICG150D1150			1.050	1.150				
CICG150D1250			1.150	1.250				
CICG150D1375			1.250	1.375				
CICG150D1375			1.250	1.375				
90° Cord Grip Fittings (Malleable Iron)								
CICG9050-A250	1/2	1/2	0.150	0.250	0.609	1-1/8	9/16	1-21/32
CICG9050-A350			0.250	0.350				
CICG9050-A450			0.350	0.450				
CICG9050-A560			0.450	0.560				
CICG9050-A650			0.550	0.650				
CICG9075-A250	3/4	3/4	0.150	0.250	0.813	1-3/8	19/32	1-25/32
CICG9075-A350			0.250	0.350				
CICG9075-A450			0.350	0.450				
CICG9075-A560			0.450	0.560				
CICG9075-A650			0.550	0.650				
CICG9075-B750			0.650	0.750				
CICG9075-B850	0.750	0.850						