

DUPONT™ TYVEK® DUAL GARMENTS

PROVIDING PROTECTION WHERE YOU NEED IT MOST— WITH ENHANCED COMFORT OVERALL

DuPont™ Tyvek® Dual garments combine the value of two DuPont fabrics.

When it comes to protective apparel, both protection and comfort are crucial to help you perform at your best. With this in mind, DuPont engineers designed DuPont™ Tyvek® Dual garments—which offer the protection, durability and comfort of DuPont™ Tyvek® fabric **on the front** with the increased breathability of DuPont™ ProShield® fabric **on the back**.

The concept behind DuPont™ Tyvek® Dual garments takes advantage of the performance of two DuPont fabrics that are well known for their use in protective apparel and, through a unique design, enables each fabric to provide you with the best of its performance where you need it most. The result is a garment that provides excellent durability, an inherent barrier to fine particles **on the front** and increased breathability for reduced heat stress and enhanced comfort **on the back**.

DuPont™ Tyvek® fabric on the front

Tyvek® fabric is composed of flashspun high-density polyethylene, which creates a unique nonwoven material available only from DuPont.

Tyvek® fabric provides an ideal balance of protection, durability and comfort compared to any limited-use fabric technology.

Tyvek® fabric's durability delivers consistently better barrier, even after wear and abrasion.

DuPont™ ProShield® fabric on the back

ProShield® fabric has been optimized for comfort, softness and breathability.

ProShield® fabric is designed for nonhazardous dry particle and light liquid splash applications.

ProShield® is made from a polypropylene SMS (spunbond, meltblown, spunbond) fabric.



Typical applications

DuPont™ Tyvek® Dual garments have been designed for very specific applications where demanding comfort requirements are combined with limited protective requirements for frontal exposures. They are well suited for workers who are involved in a variety of strenuous activities that can lead to heat stress in applications that include:

- Wind turbines
- Composites manufacturing
- Boat manufacturing
- Remediation
- Utilities
- Maintenance
- Glass manufacturing

For challenges ranging from tacky resin molds that can stick to (or delaminate) garments to sanding and grinding operations that release fine airborne particulates, DuPont™ Tyvek® Dual garments provide an ideal balance of comfort, durability and protection for workers.

DUPONT™ TYVEK® DUAL GARMENTS

DuPont™ Tyvek® fabric is used only on the front of the garment to provide inherent barrier to fine particles and avoid liquid splash while not sticking to tacky resins.

FRONT



TD125S

Respirator-fit hood with elastic around face opening is designed to fit tightly around respirator.

Longer zipper extends to chin for complete coverage of neck area.

Storm flap.

Elastic wrists and ankles.



TD127S



DuPont™ ProShield® fabric is used on the back of the garment to increase breathability and reduce heat stress. ProShield® fabric is denim blue color.

BACK



TD125S

Comfort fit design helps enable a greater range of movement while stretching and bending; provides a more tailored fit; and utilizes a longer zipper to make coveralls easier to get on and take off.

Thumb loop keeps garment sleeve in place while donning gloves and while reaching.

Elastic to properly position garment at the waist.



TD127S

FASTENAL™

Model Number	Fastenal Sku Assigned
TD125SWBMD0025CM	1047372
TD125SWBLG0025CM	1047373
TD125SWBXL0025CM	1047374
TD125SWB2X0025CM	1047375
TD125SWB3X0025CM	1047376
TD125SWB4X0025CM	1047377
TD127SWBMD0025CM	1047379
TD127SWBLG0025CM	1047380
TD127SWBXL0025CM	1048634
TD127SWB2X0025CM	1048635
TD127SWB3X0025CM	1048636
TD127SWB4X0025CM	1048637

Customer Service:
United States 1.800.931.3456
Canada 1.800.387.9326

5401 Jefferson Davis Highway
Richmond, VA 23234

www.PersonalProtection.DuPont.com



DuPont™ SafeSPEC™ 2.0

www.SafeSPEC.DuPont.com

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the nature and level of hazards and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher penetration rates than the fabric. Please contact DuPont for specific data. These garments are intended for limited use and should be disposed of after single use. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc. are damaged, end user should discontinue use of garment to avoid potential exposure.