


PRODUCT CODE: DLSR6-1213D-WH-FF
6 INCH LED ULTRA SLIM PROFILE DOWNLIGHT


PRODUCT DESCRIPTION

Etlin-Daniels new generation of Ultraslim products features significantly higher efficacy along with superior Fire Code rated cabling. The new DLSR6-1213D-WH-FF LED UltraSlim Profile Downlight is a modern and sleek looking energy efficient solution for both new construction and retrofit / remodeling projects. It installs in minutes where there is limited space due to ductwork, joists and beams. With our new lumen levels, we are now able to provide lighting options for higher ceiling heights than with previous generation products.

Why waste time installing older space restrictive recessed options when the new DLSR6 series provides a quick install solution and elegant, superior lighting for both residential and commercial applications.


FEATURES

- LED Indoor Light Source
- 6" LED downlight
- Durable air tight aluminum body
- Elegant white paint finish
- Etched white Polycarbonate diffuser lens
- Includes two spring loaded clips for mounting to any ceiling material
- Driver box using terminal connectors
- 50,000hrs L70 life
- Triac dimmable
- IC Air-tight rated
- FT6 Cable rating
- Damp location rated
- 5 year limited warranty
- Energy Star

PRODUCT SPECIFICATIONS (OPTICAL DATA)

LED TYPE	LED QTY	SYSTEM EFFICACY	LUMENS	COLOR TEMPERATURE	BEAM ANGLE	CRI	SYSTEM EFFICIENCY	VOLTAGE	POWER FREQ.	POWER EFFICIENCY	POWER FACTOR	HARMONIC DISTORTION
SMD 2835	44 CHIPS	83.3LM/W	1100LM	3000K	120°	>80CRI	>0.96%	AC120V	50-60HZ	>80%	>0.96	<2%

PRODUCT SPECIFICATIONS

WATTAGE	FIXTURE MATERIAL	LIFE SPAN	STORAGE TEMP	OPERATING TEMP	PRODUCT DIMENSIONS	CARTON SIZE	
12W	ALUMINUM/ POLYCARBONATE LENS	>50,000 HOURS	-40°C~+80°C -40°F~+176°F	-40°C~+60°C -4°F~+140°F	Ø6.85 X 1 INCHES (174 X 24 MM)	7.48 X 7.48 X 2.46 INCHES (190 X 190 X 60MM)	

ADDITIONAL INFORMATION

INSTALLATION METHOD

RECESSED CEILING MOUNT


FIXTURE COLOR


WHITE WITH WHITE
ETCHED DIFFUSER

CONTROL TYPE

TRIAC DIMMABLE DRIVER INCLUDED

PRODUCT CODE: DLSR6-1213D-WH-FF
6 INCH LED ULTRA SLIM PROFILE DOWNLIGHT
LUMINAIRE PHOTOMETRIC (TEST REPORT)
ILLUMINANCE (AT A DISTANCE) FLUX OUT: 1100LM

3.281FT 1M	8.277, 28.96FC 89.09, 311.8LX		9.37FT 285.60CM
6.562FT 2M	2.069, 7.241FC 22.27, 77.94LX		18.41FT 561.20CM
9.843FT 3M	0.9196, 3.218FC 9.899, 34.64LX		28.11FT 856.81CM
13.12FT 4M	0.5173, 1.810FC 5.568, 19.49LX		37.49FT 1142.60CM
16.4FT 5M	0.3311, 1.159FC 3.564, 12.47LX		46.86FT 1428.20CM
HT	EAVG/EMAX	ANGLE: 110.6DEG	DIA

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

CERTIFICATIONS

DRIVER / LED CHIP

120V APPROVED DIMMERS

LUTRON:
CTCL-153P · SCL-153P · DV-630P
MACI-153M · DVCL-153P · TGCL-153P
LEVITON: 6672 · 6674
FEIT: 72309

ACCESSORIES


PRE-MOUNTING PLATE FOR NEW CONSTRUCTION APPLICATIONS AVAILABLE. PLEASE CONTACT ET LIN-DANIELS.



PART NO#: DLS6-MP

ORDERING INFORMATION - DLSR SERIES

SERIES	SHAPE	SIZE	WATTAGE	VOLTAGE	COLOR TEMPERATURE	DIMMABLE	COLOR	LENS	TRIM
E.G. DLS	R	6	12	1	3	D	WH	F	F
DLS - DOWNLIGHT SLIM	R - ROUND	6 - 6"	12 - 12W	1 - 120V	3 - 3000K	D - TRIAC	WH - WHITE	F - FROSTED	F - FIXED

IF PRE-MOUNTING PLATE IS REQUIRED FOR NEW CONSTRUCTION PROJECTS, PLEASE QUOTE: PART NO#: DLS6-MP WHEN ORDERING.

Head Office - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · Tel: 416.741.7336 · Fax: 416.741.9104

Toll Free: in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

www.etlin-daniels.com · For sales/service questions · sales@etlin.com