



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches.  
 Type: ENCLOSED, SAFETY SWITCH Std: CSA V. Rating: 240V A.  
 Rating: 200A Wattage: 3W No. Of Poles: 2P F. Rating: 60Hz Action:  
 SINGLE THROW Material: 304SS Enclosure: TYPE 3R. 2-3 point  
 mounting holes. O. Cycles: 8000 O. Temperature: (-20F-120F)  
 AMBIENT TEMPERATURE Environmental Conditions: OUTDOOR

Installation location	OUTDOOR
Manner of function of the actuating element	SINGLE THROW
Mechanical service life (switching cycles) typical	8000
Mounting type	2 OR 3 POINT MOUNTING HOLES
Number of poles	2
<b>Electricity</b>	
Ampacity	200 A
Supply voltage frequency rated value 50/60 Hz	Yes
Voltage between phase and Ground (GND) rated value	240 V
<b>Switching capacity</b>	
Switching capacity active power	3 W
<b>Environmental conditions</b>	
Ambient temperature during operation maximum	120 °C
Ambient temperature during operation minimum	-20 °C
<b>Model</b>	
Product brand name	SIEMENS
Product type designation	ENCLOSED/SAFETY SWITCH

## Mechanical Design

Design of the housing TYPE 3R

Material 304SS

## General product approval

Certificate of suitability CSA

**last modified:** 05/28/2019