



THE MUST FOR RUST®

RUST REMOVER & INHIBITOR

HOW THE MUST FOR RUST® WORKS

The proprietary formulation penetrates into every void of a metal surface and dissolves rust/oxidation through chemical action. Then tiny, rust-inhibiting crystals are formed and become integral with the surface molecules of the metal to resist further rusting. The corrosive agents attack these crystals instead of the metal. Once completely dry, the surface is ready for the next step, whether it be painting, welding, plating, lubricating, etc. Or simply leave the surface bare, and the crystals will inhibit future rust formation.

IDEAL FOR PAINTING!

- When dry, THE MUST FOR RUST® accepts any primer, paint, coating, etc., and provides a clean surface free of contaminants, which allow a secure bond for coating.
- When chips or breaks appear in the coating, the surface underneath will limit the rust to the break. That means that rust won't spread under the coating and maintenance touch-ups will be quicker and easier.



Part Number	Unit Size	UPC Code	Case/Display	Carton Code
287799	236 mL	0-20066-29605-6	6 Unit Case	100-20066-30059-0
287810	946 mL	0-20066-29606-3	6 Unit Case	100-20066-30060-6
287798	3.78 L	0-20066-29603-2	6 Unit Case	100-20066-30058-3



Krud Kutter® The Must For Rust®

2015

Technical Data

Physical Data:

Contains: Phosphoric Acid and other proprietary ingredients in a water based solution.

Physical State: Liquid

Colour: Light Green

Odour: Slight Phosphoric Acid Odour

pH: <1.5

Flash Point: Non-Flammable

VOC: 1% (10.78g/L)

Coverage:

236 mL: 1.2 m² - 1.7 m² (12.5 ft² - 18.75 ft²)

946 mL: 4.5 m²-7 m² (50 ft²- 75 ft²)

3.78 L: 18.5 m² - 28 m² (200 ft² - 300 ft²)



DIRECTIONS: Remove oil and grease from the metal to be treated. Rinse the metal to break the surface tension and wash away loose dirt. Apply the remover by brush, spray or by dipping. Use plastic, glass or stainless steel containers. Disassemble units composed of moveable parts before cleaning. Clean parts and allow to dry before reassembling.

DISSOLVING RUST FROM IRON OR STEEL:

Apply the remover as required to penetrate the rust. Chemical action begins at once. Cleaning time will vary according to the rust. Medium to light rust will be dissolved in 30 minutes or less, while heavier deposits may require a second application.

ALUMINUM/CHROME: Apply the remover to wet surface. Allow time to clean, then rinse away with clean water, and buff dry with a cloth.

GALVANIZING: Where surface is unbroken, treat as suggested for aluminum. Where rust is showing at the surface, treat as for iron or steel. New galvanizing is properly prepared for painting by applying the remover, allowing 3-5 minutes to work, and then wiping the surface clean.

BATHROOM/SHOWER/TOILET CLEANER: Dissolves most calcium, lime and other hard water stains on porcelain, tile, fiberglass, and glass. Spray remover directly onto surface. Let sit for 5 minutes. Agitation with brush will speed penetration. Rinse away with water when stain is removed. **AUTO COOLING SYSTEMS:** Removes oxides and rust when circulated in the system. When cleaning action is complete, flush system with fresh water and refill with coolant.

STOPS RUST & PROTECTS METAL!

The proprietary (water based) formulation penetrates into every void of a metal surface and dissolves rust/oxidation through chemical action.

Then tiny, rust-inhibiting crystals are formed and become integral with the surface molecules of the metal to resist future rusting.

IMPORTANT: Always test on an inconspicuous area first. For best results apply in ambient temperature of 21°C (70°F) or above. On metal, maintain wet solution on surface to remove rust. Once the rust is dissolved, rinse or wipe the surface, and wait one hour or more before painting. Do not allow remover to dry on painted surfaces. For improved paint adhesion on clean metal surfaces, dilute remover 50/50 with water, apply solution, and rinse or wipe the surface. To use as a rust inhibitor on unpainted metal, allow the remover to dry on the surface after the rust is dissolved. The remover will then protect bare metal against rust for up to 12 months. Do not use on marble.

CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. Do not mix with bleach or ammonia. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Handle with care. Keep out of reach of children. Wear rubber gloves and safety glasses. Use only in a well-ventilated area. **FIRST AID TREATMENT:** Contains phosphoric acid. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse well with water. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

RUST-OLEUM
CONSUMER BRANDS CANADA

Concord, Ontario L4K 4T8

© 2015 Rust-Oleum Corporation www.rustoleum.ca

1-800-387-3625