



MR16

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life <sup>1</sup> (hrs)	Initial lumens <sup>2</sup> (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable <sup>3</sup> (Yes/No)	Case qty
<b>MR16<sup>♦</sup></b>													
MOL : 1 7/8 in. (48 mm)    Dia. : 1 3/32 in. (50 mm)													
62462	LED/MR16/6W/NFL/27K/12V/25/D/STD	6	GU5.3	12	2 700	82	40 000	360	25	1 863	35	Y	24
62465	LED/MR16/6W/FL/27K/12V/38/D/STD	6	GU5.3	12	2 700	82	40 000	360	38	974	35	Y	24
62463	LED/MR16/6W/NFL/30K/12V/25/D/STD	6	GU5.3	12	3 000	82	40 000	380	25	1 689	35	Y	24
62466	LED/MR16/6W/FL/30K/12V/38/D/STD	6	GU5.3	12	3 000	82	40 000	380	38	1 001	35	Y	24
62464	LED/MR16/6W/NFL/40K/12V/25/D/STD	6	GU5.3	12	4 000	82	40 000	410	25	1 998	35	Y	24
62467	LED/MR16/6W/FL/40K/12V/38/D/STD	6	GU5.3	12	4 000	82	40 000	410	38	1 018	35	Y	24
63092	LED/MR16/7W/27K/25/STD	7	GU5.3	12	2 700	80	40 000	500	25	-	50	Y	24
63093	LED/MR16/7W/27K/38/STD	7	GU5.3	12	2 700	80	40 000	500	38	-	50	Y	24
63094	LED/MR16/7W/30K/25/STD	7	GU5.3	12	3 000	80	40 000	500	25	-	50	Y	24
63095	LED/MR16/7W/30K/38/STD	7	GU5.3	12	3 000	80	40 000	500	38	-	50	Y	24
63096	LED/MR16/7W/40K/25/STD	7	GU5.3	12	4 000	80	40 000	520	25	-	50	Y	24
63097	LED/MR16/7W/40K/38/STD	7	GU5.3	12	4 000	80	40 000	520	38	-	50	Y	24
<b>MR16<sup>♦</sup></b>													
MOL : 2 1/8 in. (54 mm)    Dia. : 1 3/32 in. (50 mm)													
62433	LED/MR16E26/6W/NFL/30K/25/D/STD	6	E26	120	3 000	82	25 000	340	25	1 100	50	Y	48

# Reflectors



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life <sup>1</sup> (hrs)	Initial lumens <sup>2</sup> (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable <sup>3</sup> (Yes/No)	Case qty
<b>ES16<sup>♦</sup></b>													
MOL : 2 3/32 in. (53 mm)      Dia. : 1 3/32 in. (50 mm)													
62468	LED/GU10/6W/NFL/27K/25/D/STD	6	GU10	120	2 700	82	40 000	360	25	1 749	50	Y	24
62471	LED/GU10/6W/FL/27K/38/D/STD	6	GU10	120	2 700	82	40 000	340	38	929	50	Y	24
62469	LED/GU10/6W/NFL/30K/25/D/STD	6	GU10	120	3 000	82	40 000	380	25	1 918	50	Y	24
62472	LED/GU10/6W/FL/30K/38/D/STD	6	GU10	120	3 000	82	40 000	380	38	1 045	50	Y	24
62775	LED/GU10/6W/FL/30K/38/D/STD/GRY	6	GU10	120	3 000	82	40 000	380	38	1 045	50	Y	24
62470	LED/GU10/6W/NFL/40K/25/D/STD	6	GU10	120	4 000	82	40 000	410	25	1 793	50	Y	24
62473	LED/GU10/6W/FL/40K/38/D/STD	6	GU10	120	4 000	82	40 000	410	38	1 035	50	Y	24
63085	LED/GU10/7W/27K/25/STD	7	GU10	120	2 700	80	40 000	500	25	-	50	Y	24
63086	LED/GU10/7W/27K/38/STD	7	GU10	120	2 700	80	40 000	500	38	-	50	Y	24
63087	LED/GU10/7W/30K/25/STD	7	GU10	120	3 000	80	40 000	500	25	-	50	Y	24
63088	LED/GU10/7W/30K/38/STD/GRY	7	GU10	120	3 000	80	40 000	500	38	-	50	Y	24
63089	LED/GU10/7W/30K/38/STD	7	GU10	120	3 000	80	40 000	500	38	-	50	Y	24
63090	LED/GU10/7W/40K/25/STD	7	GU10	120	4 000	80	40 000	520	25	-	50	Y	24
63091	LED/GU10/7W/40K/38/STD	7	GU10	120	4 000	80	40 000	520	38	-	50	Y	24
<b>PAR16<sup>♦</sup></b>													
MOL : 3 3/32 in. (88 mm)      Dia. : 1 3/32 in. (50 mm)													
62786	LED/PAR16/6W/FL/30K/38/D/STD	6	E26	120	3 000	80	40 000	380	38	630	35	Y	24
<b>PAR20<sup>♦♦</sup></b>													
MOL : 3 3/8 in. (86 mm)      Dia. : 2 3/32 in. (63 mm)													
62474	LED/PAR20/8W/NFL/27K/25/D/STD	8	E26	120	2 700	82	40 000	490	25	1 668	50	Y	12
62477	LED/PAR20/8W/FL/27K/40/D/STD	8	E26	120	2 700	82	40 000	490	40	759	50	Y	12
62475	LED/PAR20/8W/NFL/30K/25/D/STD	8	E26	120	3 000	82	40 000	500	25	1 710	50	Y	12
62580	LED/PAR20/8W/NFL/30K/25/D/STD/BLK	8	E26	120	3 000	82	40 000	500	25	1 710	50	Y	12
62773	LED/PAR20/8W/NFL/30K/25/D/STD/GRY	8	E26	120	3 000	82	40 000	500	25	1 710	50	Y	12
62478	LED/PAR20/8W/FL/30K/40/D/STD	8	E26	120	3 000	82	40 000	500	40	824	50	Y	12
62476	LED/PAR20/8W/NFL/40K/25/D/STD	8	E26	120	4 000	81	40 000	550	25	1 921	50	Y	12
62479	LED/PAR20/8W/FL/40K/40/D/STD	8	E26	120	4 000	81	40 000	550	40	909	50	Y	12



<sup>1</sup> Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

<sup>2</sup> Typical lumens +/- 5 %

<sup>3</sup> For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)



PAR30SN



PAR30LN



PAR38

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life <sup>1</sup> (hrs)	Initial lumens <sup>2</sup> (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable <sup>3</sup> (Yes/No)	Case qty
<b>PAR30SN* ♦♦</b>													
MOL : 3 13/32 in. (85 mm)    Dia. : 3 3/4 in. (95 mm)													
62480	LED/PAR30SN/14.5W/NFL/27K/25/D/STD	14.5	E26	120	2 700	81	40 000	850	25	3 078	75	Y	6
62483	LED/PAR30SN/14.5W/FL/27K/40/D/STD	14.5	E26	120	2 700	81	40 000	850	40	1 403	75	Y	6
62481	LED/PAR30SN/14.5W/NFL/30K/25/D/STD	14.5	E26	120	3 000	82	40 000	880	25	3 225	75	Y	6
62774	LED/PAR30SN/14.5W/NFL/30K/25/D/STD/BLK	14.5	E26	120	3 000	82	40 000	880	25	3 225	75	Y	6
62484	LED/PAR30SN/14.5W/FL/30K/40/D/STD	14.5	E26	120	3 000	82	40 000	850	40	1 341	75	Y	6
62482	LED/PAR30SN/14.5W/NFL/40K/25/D/STD	14.5	E26	120	4 000	82	40 000	950	25	3 430	75	Y	6
62485	LED/PAR30SN/14.5W/FL/40K/40/D/STD	14.5	E26	120	4 000	82	40 000	950	40	1 388	75	Y	6
<b>PAR30LN** ♦♦</b>													
MOL : 4 19/32 in. (117 mm)    Dia. : 3 3/4 in. (95 mm)													
62498	LED/PAR30LN/14W/NFL/27K/25/D/STD	14	E26	120	2 700	81	40 000	800	25	3 732	75	Y	6
62501	LED/PAR30LN/14W/FL/27K/40/D/STD	14	E26	120	2 700	81	40 000	850	40	1 448	75	Y	6
62499	LED/PAR30LN/14W/NFL/30K/25/D/STD	14	E26	120	3 000	82	40 000	880	25	3 771	75	Y	6
62502	LED/PAR30LN/14W/FL/30K/40/D/STD	14	E26	120	3 000	82	40 000	880	40	1 418	75	Y	6
62500	LED/PAR30LN/14W/NFL/40K/25/D/STD	14	E26	120	4 000	82	40 000	950	25	3 081	75	Y	6
62503	LED/PAR30LN/14W/FL/40K/40/D/STD	14	E26	120	4 000	82	40 000	950	40	1 585	75	Y	6

# Reflectors



STANDARD's LED reflector lamps offer exceptional thermal management and professional grade optics to ensure uniform beam pattern, long life and luminous effect while reducing energy consumption.

Concise binning process ensures colour consistency from lamp to lamp. Ideal for goods and materials sensitive to heat and UV emission.



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life <sup>1</sup> (hrs)	Initial lumens <sup>2</sup> (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable <sup>3</sup> (Yes/No)	Case qty
<b>PAR38** ♦♦</b>													
MOL : 5 7/32 in. (129 mm) Dia. : 4 23/32 in. (120 mm)													
62504	LED/PAR38/16W/NFL/27K/25/D/STD	16	E26	120	2 700	81	40 000	980	25	4 727	90	Y	6
62507	LED/PAR38/16W/FL/27K/40/D/STD	16	E26	120	2 700	81	40 000	980	40	1 675	90	Y	6
62505	LED/PAR38/16W/NFL/30K/25/D/STD	16	E26	120	3 000	81	40 000	1 020	25	4 444	90	Y	6
62508	LED/PAR38/16W/FL/30K/40/D/STD	16	E26	120	3 000	81	40 000	1 020	40	1 683	90	Y	6
62506	LED/PAR38/16W/NFL/40K/25/D/STD	16	E26	120	4 000	81	40 000	1 150	25	4 766	90	Y	6
62509	LED/PAR38/16W/FL/40K/40/D/STD	16	E26	120	4 000	81	40 000	1 150	40	1 829	90	Y	6
<b>R20* ♦</b>													
MOL : 3 3/8 in. (86 mm) Dia. : 2 15/32 in. (63 mm)													
62784	LED/R20/7.5W/27K/D/STD	7.5	E26	120	2 700	82	40 000	500	40	759	50	Y	12
<b>R20* ♦</b>													
MOL : 3 29/32 in. (99 mm) Dia. : 2 23/32 in. (63 mm)													
62431	LED/R20/8W/27K/D/STD	8	E26	120	2 700	82	25 000	500	-	-	50	Y	48
<b>BR40* ♦♦</b>													
MOL : 6 1/4 in. (159 mm) Dia. : 4 29/32 in. (125 mm)													
63084	LED/BR40/17W/27K/STD	17	E26	120	2 700	80	40 000	1 100	100	401	85	Y	6
<b>BR30* ♦</b>													
MOL : 5 29/32 in. (150 mm) Dia. : 4 1/16 in. (103 mm)													
62783	LED/BR30/10W/27K/D/STD	10	E26	120	2 700	80	40 000	650	-	-	65	Y	6
<b>AR111* ♦</b>													
MOL : 2 9/32 in. (58 mm) Dia. : 4 1/8 in. (111 mm)													
62630	LED/AR111/13W/FL/30K/12V/40/STD	13	G53	12	3 000	80	25 000	750	40	-	-	N	12



<sup>1</sup> Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

<sup>2</sup> Typical lumens +/- 5 %

<sup>3</sup> For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)