

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour/Finish	Average life (hrs)	Initial lumens (lm)	MOL (in.)	(mm)	Case qty
T3 - High Voltage											
59261	H300QT3/119mm/CL/2M/220V/STD	N/A	300	R7s	220	Clear	2 000	33 000	4 11/16	119	50
51047	H1000T3/190mm/CL/2M/R7S/240V/STD	DYD	1 000	R7s	240	Clear	2 000	21 000	7 15/32	190	12
51085	H1000T3/256mm/CL/2M/R7S/240V/STD	N/A	1 000	R7s	240	Clear	2 000	21 000	10 3/32	256	50
59262	H1500QT3/256mm/CL/2M/R7S/208V/STD	N/A	1 500	R7s	208	Clear	2 000	33 000	10 3/32	256	50
51049	H1500T3/256mm/CL/2M/R7S/240V/STD	N/A	1 500	R7s	240	Clear	2 000	26 400	10 3/32	256	50
59260	H1500QT3/256mm/CL/2M/277V/STD	N/A	1 500	R7s	277	Clear	2 000	33 000	10 3/32	256	50
T3 - Low Voltage											
55088	H150T3/79mm/2M/R7S/12V/STD	N/A	150	R7s	12	Clear	2 000	2 900	3 1/8	79	10
10154	H150T3/119mm/CL/2M/R7S/12V/STD	N/A	150	R7s	12	Clear	2 000	2 250	4 11/16	119	10
10318	H300T3/119mm/CL/2M/R7S/24V/STD	N/A	300	R7s	24	Clear	2 000	5 400	4 11/16	119	10
10319	H300T3/119mm/CL/2M/R7S/32V/STD	EHM	300	R7s	32	Clear	2 000	5 400	4 11/16	119	10
T3 - Infrared											
55077	H375T3/221mm/CL/IR/5M/R7S/120V/STD	N/A	375	R7s	120	Clear	5 000	N/A	8 11/16	221	42
55070	H500T3/221MM/CL/IR/5M/R7S/120V/STD	N/A	500	R7s	120	Clear	5 000	N/A	8 11/16	221	42
55071	H500T3/224mm/CL/IR/5M/ML/120V/STD	N/A	500	Metal Leads	120	Clear	5 000	N/A	8 13/16	224	42
55073	H1000T3/303mm/CL/IR/5M/ML/240V/STD	N/A	1 000	Metal Leads	240	Clear	5 000	N/A	11 15/16	303	42
55072	H1000T3/351MM/CL/IR/5M/ML/240V/STD	N/A	1 000	Metal Leads	240	Clear	5 000	N/A	13 13/16	351	42
55074	H1600T3/503MM/CL/IR/5M/ML/240V/STD	N/A	1 600	Metal Leads	240	Clear	5 000	N/A	19 13/16	503	42
55075	H2500T3/732mm/CL/IR/5M/ML/480V/STD	N/A	2 500	Metal Leads	480	Clear	5 000	N/A	28 13/16	732	42
55076	H3800T3/1062MM/CL/IR/5M/ML/570V/STD	N/A	3 800	Metal Leads	570	Clear	5 000	N/A	41 13/16	1 062	36
T3 - Rough Service											
15491	500T3Q/CL/6 ROUGH SERVICE HAL	N/A	500	R7s	120	Clear	1 500	10 950	4 11/16	119	12

ALR LAMPS are halogen aluminium reflector lamps. They are a lightweight compact light source and are mainly used in display lighting, accent lighting, task lighting and elevator.



Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour temp. (K)	Colour/Finish	Beam angle (°)	Beam spread	CBCP (cd)	Average life (hrs)	Initial lumens (lm)	Case qty
ALR12 - Cover Glass													
MOL : 1 17/32 in. (39 mm) Dia. : 1 1/2 in. (38 mm)													
11068	20ALR12/NSP6-GBD	GBD	20	BA15d	12	3 000	Clear	6	Narrow Spot	7 000	2 000	250	50
55061	20ALR12/F/SP/BA15d/12V/GBE STD	GBE	20	BA15d	12	3 000	Frost	18	Spot	1 000	2 000	1 500	20
55062	20ALR12/F/FL/BA15d/12V/GBF STD	GBF	20	BA15d	12	3 000	Frost	32	Flood	400	2 000	750	20
ALR18 - Cover Glass													
MOL : 2 1/2 in. (57 mm) Dia. : 2 1/4 in. (57 mm)													
55010	H50ALR18/SP/CL/DC/12V/GBJ STD	GBJ	50	BA15d	12	3 000	Clear	10	Spot	13 900	2 000	N/A	25
55011	H50ALR18/NFL/F/DC/12V/GBK STD	GBK	50	BA15d	12	3 000	Frost	25	Narrow Flood	1 900	2 000	N/A	50



ALR Lamps