



JCD TYPE LAMPS are line voltage (120-130 volt) halogen capsules with pin bases.

All STANDARD JCD lamps are safe to use in open fixtures due to their patented integral safety fuses.

The filament is well supported through glass pinch technology which minimizes deformation as well. They are all made of UV stop quartz.



Order code	Description	Watts (W)	Base	Volts (V)	Colour/Finish	Average life (hrs)	Initial lumens (lm)	Case qty
JCD (GY6.35)								
MOL: 1 13/16 in. (46 mm) Dia.: 1/2 in. (13 mm)								
51045	H20JCD/CL/2M/GY6.35/120V/STD	20	GY6.35	120	Clear	2 000	180	120
50879	H35JCD/CL/2M/GY6.35/120V/STD	35	GY6.35	120	Clear	2 000	380	120
50878	H50JCD/CL/2M/GY6.35/120V/STD	50	GY6.35	120	Clear	2 000	600	120
10317	H75JCD/CL/2M/GY6.35/120V/STD	75	GY6.35	120	Clear	2 000	1 050	100
50877	H100JCD/CL/2M/GY6.35/120V/STD	100	GY6.35	120	Clear	2 000	1 500	100
JCD (G8)								
MOL: 1 13/16 in. (46 mm) Dia.: 1/2 in. (13 mm)								
55055	H20JCD/CL/2M/G8/120V/STD	20	G8	120	Clear	2 000	200	100
10253	H35JCD/CL/2M/G8/120V/STD	35	G8	120	Clear	2 000	380	120
10368	H50JCD/CL/2M/G8/120V/STD	50	G8	120	Clear	2 000	600	120
15710	JCD100W/130V/G8	100	G8	130	Clear	2 000	1 600	100
JCD (GY8)								
MOL: 1 7/8 in. (47.5 mm) Dia.: 1/2 in. (13 mm)								
11266	H25JCD/CL/2M/GY8/120V	25	GY8	120	Clear	2 000	420	50
11267	H75JCD/CL/2M/GY8/120V	75	GY8	120	Clear	2 000	1 300	50
11265	H100JCD/CL/2M/GY8/120V	100	GY8	120	Clear	2 000	1 900	50



JCD Lamps