











Order code	Description	Watts	Base	Volts	Finish/ Colour	Average life	Filament	Lumens	Case
code		(W)		(V)	Colour	(hrs)		(lm)	qty
<b>A19</b>									
MOL: 4 <sup>1</sup> / <sub>4</sub> in. (108 mm) LCL.: 3 <sup>1</sup> / <sub>6</sub> in. (79 mm)									
52223	15A19/F/1.5M/12V/STD	15	E26	12	Frost	1500	C-6	105	120
52022	25A19/F/1.5M/12V/STD	25	E26	12	Frost	1500	C-6	220	120
52024	25A19/F/1.5M/24V/STD	25	E26	24	Frost	1500	C-6	220	120
52222	25A19/F/1.5M/32V/STD	25	E26	32	Frost	1500	C-6	220	120
52010	50A19/F/1.5M/12V/STD	50	E26	12	Frost	1500	C-6	410	120
52011	50A19/F/1.5M/24V/STD	50	E26	24	Frost	1500	C-6	410	120
52012	50A19/F/1.5M/32V/STD	50	E26	32	Frost	1500	C-6	410	120
52224	50A19/F/1.5M/60V/STD	50	E26	60	Frost	1500	C-6	410	120
59846	50A19/F/RS/1M/75V/STD	50	E26	75	Frost	1000	C-9	500	120
52221	75A19/F/1.5M/12V/STD	75	E26	12	Frost	1500	C-6	865	120
52023	100A19/F/1.5M/12V/STD	100	E26	12	Frost	1500	C-6	1385	120
52025	100A19/F/1.5M/24V/STD	100	E26	24	Frost	1500	C-6	1385	120
52026	100A19/F/1.5M/32V/STD	100	E26	32	Frost	1500	C-6	1385	120
52225	100A19/F/1.5M/34V/STD	100	E26	34	Frost	1500	C-6	1 385	120

## Low Voltage Lamps