

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>F15</b>									
MOL : 4 1/2 in. (115 mm) LCL : 2 9/16 in. (65 mm)									
50751	25F15/CL/2M/130V/STD	25	E26	130	Clear	2 000	CC-6	160	120
50750	40F15/CL/2M/130V/STD	40	E26	130	Clear	2 000	CC-6	305	120
<sup>†</sup> 50752	60F15/CL/2M/130V/STD	60	E26	130	Clear	2 000	CC-6	275	120
<b>G8</b>									
MOL : 1 7/32 in. (47 mm) LCL : 1 1/16 in. (33 mm)									
52164	5G8/CL/1M/E12/130V/STD	5	E12	130	Clear	1 000	C-7A	40	500
<b>G9.5</b>									
MOL : 2 1/16 in. (52 mm) LCL : 1 1/2 in. (38 mm)									
52165	7.5G9.5/CL/1M/E12/130V/STD	7	E12	130	Clear	1 000	C-7A	40	500
<b>G11</b>									
MOL : 2 3/16 in. (59 mm) LCL : 1 1/2 in. (41 mm)									
50759	7.5G11/CL/1M/E12/130V/STD	7.5	E12	130	Clear	1 000	C-5	510	500
50761	7.5G11/CL/1M/130V/STD	7.5	E26	130	Clear	1 000	C-5	40	500
<b>G13</b>									
MOL : 2 3/8 in. (60.5 mm) LCL : 1 11/16 in. (43 mm)									
50681	10G13/CL/3M/E12/130V/STD	10	E12	130	Clear	3 000	C-7A	50	500
50682	25G13/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	135	120
50683	40G13/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	250	500
50684	60G13/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	C-7A	490	500
<b>G16.5</b>									
MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)									
10334	5G16.5/CL/3M/E12/130V/STD	5	E12	130	Clear	3 000	C-7A	20	500
10268	10G16.5/CL/3M/E12/130V/STD	10	E12	130	Clear	3 000	C-7A	50	500
50660	15G16.5/CL/3M/E12/130V/STD	15	E12	130	Clear	3 000	C-7A	70	120
50662	15G16.5/WH/3M/E12/130V/STD	15	E12	130	White	3 000	C-7A	60	120
50661	15G16.5/CL/3M/130V/STD	15	E26	130	Clear	3 000	C-7A	70	500
50648	25G16.5/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	135	120
50652	25G16.5/WH/3M/E12/130V/STD	25	E12	130	White	3 000	CC-2V	120	120
50777	25G16.5/CL/3M/E14/130V/STD	25	E14	130	Clear	3 000	CC-6	160	500
50649	25G16.5/CL/3M/130V/STD	25	E26	130	Clear	3 000	CC-2V	135	500
50653	25G16.5/WH/3M/130V/STD	25	E26	130	White	3 000	CC-2V	120	120
50650	40G16.5/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	250	120
50654	40G16.5/WH/3M/E12/130V/STD	40	E12	130	White	3 000	CC-2V	230	120
50651	40G16.5/CL/3M/130V/STD	40	E26	130	Clear	3 000	CC-2V	250	120
50655	40G16.5/WH/3M/130V/STD	40	E26	130	White	3 000	CC-2V	230	120
50656	60G16.5/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	CC-2V	440	120
50658	60G16.5/WH/3M/E12/130V/STD	60	E12	130	White	3 000	CC-2V	400	120
<sup>†</sup> 50657	60G16.5/CL/3M/130V/STD	60	E26	130	Clear	3 000	CC-2V	580	500
<sup>†</sup> 50659	60G16.5/WH/3M/130V/STD	60	E26	130	White	3 000	CC-2V	440	120
MOL : 2 7/8 in. (73 mm) LCL : 2 1/16 in. (52 mm)									
50779	25G16.5/WH/3M/E14/130V/STD	25	E14	130	White	3 000	CC-6	150	500
50778	40G16.5/CL/3M/E14/130V/STD	40	E14	130	Clear	3 000	CC-6	315	500
50780	40G16.5/WH/3M/E14/130V/STD	40	E14	130	White	3 000	CC-6	295	500
50782	60G16.5/WH/3M/E14/130V/STD	60	E14	130	White	3 000	CC-6	580	500
<b>G25</b>									
MOL : 2 1/2 in. (114 mm) LCL : 3 1/32 in. (77 mm)									
50199	25G25/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	135	60
50196	25G25/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	115	60
50222	40G25/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	255	60
50155	40G25/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	230	60
<sup>†</sup> 50154	60G25/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-9	460	60
<sup>†</sup> 50197	60G25/WH/3M/130V/STD	60	E26	130	White	3 000	C-9	425	60
<sup>†</sup> 50198	100G25/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	830	60

<sup>†</sup>This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps