

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Case qty
<b>A19 Transparent</b>								
MOL : 4 1/4 in. (108 mm) LCL : 2 2/32 in. (72 mm)								
52092	60A19/TG/5M/130V/STD	60	E26	130	Transparent green	5000	C-9	24
52041	60A19/TR/5M/130V/STD	60	E26	130	Transparent red	5000	C-9	24
52093	60A19/TY/5M/130V/STD	60	E26	130	Transparent yellow	5000	C-9	24
52098	100A19/TA/5M/130V/STD	100	E26	130	Transparent amber	5000	C-9	24
52099	100A19/TB/5M/130V/STD	100	E26	130	Transparent blue	5000	C-9	24
52100	100A19/TG/5M/130V/STD	100	E26	130	Transparent green	5000	C-9	24
52101	100A19/TR/5M/130V/STD	100	E26	130	Transparent red	5000	C-9	24
<b>B10</b>								
MOL : 3 1/2 in. (89 mm) LCL : 1 2/32 in. (47 mm)								
52152	40B10/WH/3M/130V/STD	40	E26	130	White	3000	C-7A	500
52151	60B10/WH/3M/E12/130V/STD	60	E12	130	White	3000	C-7A	500
<b>BR30</b>								
MOL : 5 29/32 in. (137 mm) LCL : 3 1/8 in. (86 mm)								
52027	75BR30/A/FL/5M/130V/STD	75	E26	130	Amber	5000	C-9	24
52028	75BR30/B/FL/5M/130V/STD	75	E26	130	Blue	5000	C-9	24
52029	75BR30/G/FL/5M/130V/STD	75	E26	130	Green	5000	C-9	24
52030	75BR30/P/FL/5M/130V/STD	75	E26	130	Pink	5000	C-9	24
52031	75BR30/R/FL/5M/130V/STD	75	E26	130	Red	5000	C-9	24
52032	75BR30/Y/FL/5M/130V/STD	75	E26	130	Yellow	5000	C-9	24
<b>BR30 Transparent</b>								
MOL : 5 29/32 in. (137 mm) LCL : 3 1/8 in. (86 mm)								
10083	75BR30/TA/5M/130V/STD	75	E26	130	Transparent amber	5000	C-9	24
10104	75BR30/TG/5M/130V/STD	75	E26	130	Transparent green	5000	C-9	24
10139	75BR30/TP/5M/130V/STD	75	E26	130	Transparent pink	5000	C-9	24
10082	75BR30/TR/5M/130V/STD	75	E26	130	Transparent red	5000	C-9	24
10080	75BR30/TY/5M/130V/STD	75	E26	130	Transparent yellow	5000	C-9	24
10081	75BR30/TB/5M/130V/STD	75	E26	130	Transparent blue	5000	C-9	24
<b>BR38</b>								
MOL : 5 29/32 in. (147 mm) LCL : 3 3/32 in. (83 mm)								
50093	100BR38/A/5M/130V/STD	100	E26	130	Amber	5000	C-9	12
50095	100BR38/G/5M/130V/STD	100	E26	130	Green	5000	C-9	12
50097	100BR38/R/5M/130V/STD	100	E26	130	Red	5000	C-9	12
50098	100BR38/Y/5M/130V/STD	100	E26	130	Yellow	5000	C-9	12
<b>BR40</b>								
MOL : 6 1/2 in. (165 mm) LCL : 3 3/8 in. (86 mm)								
52136	150BR40/A/FL/5M/130V/STD	150	E26	130	Amber	5000	C-9	12
52137	150BR40/G/FL/5M/130V/STD	150	E26	130	Green	5000	C-9	24
52068	150BR40/R/FL/5M/130V/STD	150	E26	130	Red	5000	C-9	12
52069	150BR40/Y/FL/5M/130V/STD	150	E26	130	Yellow	5000	C-9	12
<b>F10</b>								
MOL : 2 2/2 in. (76 mm) LCL : 1 29/32 in. (43 mm)								
14459	15F10/WH/1.5M/E12/130V	15	E12	130	White	1500	C-7A	250
MOL : 3 1/16 in. (78 mm) LCL : 1 29/32 in. (43 mm)								
14456	15F10/A/2.5M/E12/130V	15	E12	130	Amber	2500	C-7A	250
14460	25F10/A/2.5M/E12/130V	25	E12	130	Amber	2500	CC-2V	250
<b>F15</b>								
MOL : 4 1/4 in. (108 mm) LCL : 2 9/16 in. (65 mm)								
50756	25F15/A/1.5M/130V/STD	25	E26	130	Amber	1500	CC-2V	500
50753	25F15/WH/1.5M/130V/STD	25	E26	130	White	1500	CC-2V	500
50757	40F15/A/1.5M/130V/STD	40	E26	130	Amber	1500	CC-2V	500
50754	40F15/WH/1.5M/130V/STD	40	E26	130	White	1500	CC-2V	500
50758	60F15/A/1.5M/130V/STD	60	E26	130	Amber	1500	CC-2V	500
<b>G11</b>								
MOL : 2 2/16 in. (59 mm) LCL : 1 3/8 in. (41 mm)								
50763	7.5G11/CB/1M/130V/STD	7.5	E26	130	Ceramic blue	1000	C-5	500
50764	7.5G11/CG/1M/130V/STD	7.5	E26	130	Ceramic green	1000	C-5	500
50765	7.5G11/CO/1M/130V/STD	7.5	E26	130	Ceramic orange	1000	C-5	500
50766	7.5G11/CR/1M/130V/STD	7.5	E26	130	Ceramic red	1000	C-5	500
50760	7.5G11/WH/1M/E12/130V/STD	7.5	E12	130	White	1000	C-5	500
50762	7.5G11/WH/1M/130V/STD	7.5	E26	130	White	1000	C-5	500
50767	7.5G11/CY/1M/130V/STD	7.5	E26	130	Ceramic Yellow	1000	C-5	500
50769	7.5G11/TR/1M/130V/STD	7.5	E26	130	Transparent red	1000	C-5	500

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Case qty
<b>G13</b>								
MOL : 2 3/32 in. (61 mm) LCL : 1 21/32 in. (42 mm)								
14717	10G13/WH/3M/E12/130V	10	E12	130	White	3000	C-7A	500
<b>R20</b>								
MOL : 3 3/32 in. (101 mm) LCL : 2 3/4 in. (70 mm)								
52060	50R20/A/5M/130V/STD	50	E26	130	Amber	5000	C-9	24
52061	50R20/B/5M/130V/STD	50	E26	130	Blue	5000	C-9	24
52062	50R20/G/5M/130V/STD	50	E26	130	Green	5000	C-9	24
52063	50R20/P/5M/130V/STD	50	E26	130	Pink	5000	C-9	24
52064	50R20/R/5M/130V/STD	50	E26	130	Red	5000	C-9	24
52066	50R20/Y/5M/130V/STD	50	E26	130	Yellow	5000	C-9	24
<b>R20 Transparent</b>								
MOL : 3 3/32 in. (101 mm) LCL : 2 3/4 in. (70 mm)								
10086	50R20/TA/5M/130V/STD	50	E26	130	Transparent amber	5000	C-9	24
10085	50R20/TB/5M/130V/STD	50	E26	130	Transparent blue	5000	C-9	24
10084	50R20/TG/5M/130V/STD	50	E26	130	Transparent green	5000	C-9	200
52065	50R20/TP/5M/130V/STD	50	E26	130	Transparent pink	5000	C-9	24
10137	50R20/TR/5M/130V/STD	50	E26	130	Transparent red	5000	C-9	24
10138	50R20/TY/5M/130V/STD	50	E26	130	Transparent yellow	5000	C-9	24
<b>S11 Ceramic</b>								
MOL : 2 3/16 in. (59 mm) LCL : 1 1/8 in. (41 mm)								
50797	10S11/CB/1M/E17/130V/STD	10	E17	130	Ceramic blue	1000	C-7A	500
50793	10S11/CG/1M/E17/130V/STD	10	E17	130	Ceramic green	1000	C-7A	500
50794	10S11/CR/1M/E17/130V/STD	10	E17	130	Ceramic red	1000	C-7A	500
50796	10S11/CW/1M/E17/130V/STD	10	E17	130	Ceramic white	1000	C-7A	500
50795	10S11/CY/1M/E17/130V/STD	10	E17	130	Ceramic yellow	1000	C-7A	500
<b>S11 Transparent</b>								
MOL : 2 3/16 in. (59 mm) LCL : 1 1/8 in. (41 mm)								
50798	10S11/TB/1M/E17/130V/STD	10	E17	130	Transparent blue	1000	C-7A	500
50799	10S11/TG/1M/E17/130V/STD	10	E17	130	Transparent green	1000	C-7A	500
50800	10S11/TO/1M/E17/130V/STD	10	E17	130	Transparent orange	1000	C-7A	500
50801	10S11/TR/1M/E17/130V/STD	10	E17	130	Transparent red	1000	C-7A	500
50802	10S11/TY/1M/E17/130V/STD	10	E17	130	Transparent yellow	1000	C-7A	500
<b>S14 Ceramic</b>								
MOL : 3 3/16 in. (84 mm) LCL : 2 21/32 in. (64 mm)								
52211	11S14/CB/3M/130V/STD	11	E26	130	Ceramic blue	3000	C-9	500
52212	11S14/CG/3M/130V/STD	11	E26	130	Ceramic green	3000	C-9	500
52213	11S14/CO/3M/130V/STD	11	E26	130	Ceramic orange	3000	C-9	500
52214	11S14/CR/3M/130V/STD	11	E26	130	Ceramic red	3000	C-9	500
22004	11S14/CY/3M/130V/STD	11	E26	130	Ceramic yellow	3000	C-9	500
52215	11S14/CW/3M/130V/STD	11	E26	130	Ceramic white	3000	C-9	500
<b>S14 Transparent</b>								
MOL : 3 3/16 in. (84 mm) LCL : 2 21/32 in. (64 mm)								
52216	11S14/TA/3M/130V/STD	11	E26	130	Transparent amber	3000	C-9	500
52217	11S14/TB/3M/130V/STD	11	E26	130	Transparent blue	3000	C-9	500
52218	11S14/TG/3M/130V/STD	11	E26	130	Transparent green	3000	C-9	500
52219	11S14/TR/3M/130V/STD	11	E26	130	Transparent red	3000	C-9	500
52220	11S14/TY/3M/130V/STD	11	E26	130	Transparent yellow	3000	C-9	500
<b>T10 Transparent</b>								
MOL : 5 in. (127 mm) LCL : 2 3/4 in. (70 mm)								
52135	40T10/TB/3M/130V/STD	40	E26	130	Transparent blue	3000	C-9	12

# Coloured Lamps

Lamps pertaining to this category have line voltage compatibility and are used in general residential and commercial applications. Their special feature is to produce directional light.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life at 120 V (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>BR25</b>									
MOL : 4 <sup>25</sup> / <sub>32</sub> in. (118 mm) LCL : 3 <sup>25</sup> / <sub>32</sub> in. (85 mm)									
<sup>1</sup> 50121	100BR25/SP/5M/130V/STD	100	E26	130	Clear	5 000	C-9	770	100
<b>BR30</b>									
MOL : 5 <sup>1</sup> / <sub>8</sub> in. (130 mm) LCL : 3 <sup>25</sup> / <sub>32</sub> in. (85 mm)									
<sup>1</sup> 50219	50BR30/FL/5M/130V/STD	50	E26	130	Clear	5 000	C-9	240	60
<sup>1</sup> 50220	60BR30/FL/5M/130V/STD	60	E26	130	Clear	5 000	C-9	320	60
50077	65BR30/FL/5M/ES/130V/STD	65	E26	130	Clear	5 000	CC-6	470	60
50079	65BR30/SP/5M/ES/130V/STD	65	E26	130	Clear	5 000	CC-6	470	60
<b>BR38</b>									
MOL : 5 <sup>25</sup> / <sub>32</sub> in. (147 mm) LCL : 3 <sup>3</sup> / <sub>32</sub> in. (83 mm)									
<sup>1</sup> 50056	75BR38/SP/5M/130V/STD	75	E26	130	Clear	5 000	C-9	580	12
<sup>1</sup> 52001	120BR38/FL/5M/ES/130V/STD	120	E26	130	Clear	5 000	CC-6	895	12
<b>BR40</b>									
MOL : 6 <sup>3</sup> / <sub>16</sub> in. (167 mm) LCL : 4 <sup>1</sup> / <sub>4</sub> in. (108 mm)									
<sup>1</sup> 50080	65BR40/FL/5M/ES/130V/STD	65	E26	130	Clear	5 000	CC-6	470	12
<b>R14</b>									
MOL : 2 <sup>1</sup> / <sub>8</sub> in. (54 mm) LCL : 1 <sup>25</sup> / <sub>32</sub> in. (42 mm)									
50665	25R14/FL/1.5M/120V/STD	25	E26	120	Clear	1 500	CC-2V	150	120
50663	40R14/CL/FL/1.5M/120V/STD	40	E26	120	Clear	1 500	CC-2V	280	120
MOL : 2 <sup>9</sup> / <sub>16</sub> in. (65 mm) LCL : 1 <sup>25</sup> / <sub>32</sub> in. (50 mm)									
50666	25R14/FL/1.5M/E17/120V/STD	25	E17	120	Clear	1 500	CC-2V	150	120
<b>R16</b>									
MOL : 3 <sup>1</sup> / <sub>2</sub> in. (89 mm)									
52168	25R16/SF/1.5M/E12/130V/STD	25	E12	130	Frost	3 000	CC-2V	120	500
50134	40R16/SW/1M/120V/STD	40	E26	120	Soft white	1 000	CC-6	470	100
50135	60R16/SW/1M/125 130V/STD	60	E26	125-130	Soft white	2 500	CC-6	310	100
<b>R19</b>									
MOL : 3 <sup>25</sup> / <sub>32</sub> in. (101 mm) LCL : 3 <sup>1</sup> / <sub>32</sub> in. (77 mm)									
50136	40R19/SW/1.5M/120V/STD	40	E26	120	Soft white	1 500	CC-6	320	60
<sup>1</sup> 50138	75R19/SW/1.5M/120V/STD	75	E26	120	Soft white	1 500	CC-6	770	200
<b>R20</b>									
MOL : 3 <sup>25</sup> / <sub>32</sub> in. (99 mm) LCL : 2 <sup>15</sup> / <sub>16</sub> in. (75 mm)									
50211	30R20/SP/5M/130V/STD	30	E26	130	Clear	5 000	C-9	145	60
50215	30R20/FL/5M/130V/STD	30	E26	130	Frost	5 000	C-9	130	60
61703	45R20/FL/5M/130V/STD	45	E26	130	Frost	5 000	CC-6	255	60
61705	45R20/SP/5M/130V/STD	45	E26	130	Frost	5 000	CC-6	255	60
<sup>1</sup> 50217	75R20/FL/5M/130V/STD	75	E26	130	Clear	5 000	C-9/5	410	60
<sup>1</sup> 50213	75R20/SP/5M/130V/STD	75	E26	130	Clear	5 000	CC-6	575	200

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Reflectors

Lamps pertaining to this category have line voltage compatibility and are used in general residential and commercial applications. They produce ambient light without a beam.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>A15</b>									
MOL : 3 1/2 in. (89 mm) LCL : 2 3/8 in. (60 mm)									
50125	15A15/CL/5M/130V/STD	15	E26	130	Clear	5 000	C-9	85	60
50166	15A15/F/5M/130V/STD	15	E26	130	Frost	5 000	C-9	80	60
50145	25A15/CL/5M/130V/STD	25	E26	130	Clear	5 000	C-9	135	60
50126	25A15/F/5M/130V/STD	25	E26	130	Frost	5 000	C-9	135	60
52427	30A15/CL/5M/130V/STD	30	E26	130	Clear	5 000	C-9	175	120
50557	40A15/CL/5M/130V/STD/1BP	40	E26	130	Clear	5 000	C-9	265	120
50144	40A15/CL/5M/130V/STD	40	E26	130	Clear	5 000	C-9	265	60
50556	40A15/F/5M/130V/STD/1BP	40	E26	130	Frost	5 000	C-9	265	120
10329	40A15/SW/5M/130V/STD	40	E26	130	Soft white	5 000	C-9	240	60
50124	40A15/F/5M/130V/STD	40	E26	130	Frost	5 000	C-9	265	60
<sup>1</sup> 50554	60A15/CL/5M/130V/STD/1BP	60	E26	130	Clear	5 000	C-9	470	120
<sup>1</sup> 50555	60A15/F/5M/130V/STD/1BP	60	E26	130	Frost	5 000	C-9	470	120
<sup>1</sup> 10330	60A15/SW/5M/130V/STD	60	E26	130	Soft white	5 000	C-9	415	60
<sup>1</sup> 50127	60A15/CL/5M/130V/STD	60	E26	130	Clear	5 000	C-9	470	60
<sup>1</sup> 50146	60A15/F/5M/130V/STD	60	E26	130	Frost	5 000	C-9	470	60
<b>A19</b>									
MOL : 4 1/4 in. (108 mm) LCL : 3 3/8 in. (79 mm)									
50941	15A19/CL/6M/130V/STD	15	E26	130	Clear	6 000	C-9	80	120
50128	15A19/F/6M/130V/STD	15	E26	130	Frost	6 000	C-9	80	120
50931	25A19/CL/1M/120V/STD/4P (4 pack)	25	E26	120	Clear	1 000	C-9	150	120
50932	25A19/F/1M/120V/STD/4P (4 pack)	25	E26	120	Frost	1 000	C-9	140	120
50024	25A19/CL/6M/130V/STD/2P (2 pack)	25	E26	130	Clear	6 000	C-9	105	120
50942	25A19/CL/6M/130V/STD/4P (4 pack)	25	E26	130	Clear	6 000	C-9	105	120
50028	25A19/F/6M/130V/STD/2P (2 pack)	25	E26	130	Frost	6 000	C-9	100	120
50943	25A19/F/6M/130V/STD/4P (4 pack)	25	E26	130	Frost	6 000	C-9	100	120

<sup>1</sup>This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>A19</b>									
MOL : 4 1/4 in. (108 mm) LCL : 3 1/4 in. (79 mm)									
† 50933	40A19/CL/1M/120V/STD/4P	(4 pack) 40	E26	120	Clear	1 000	C-9	320	120
† 50934	40A19/F/1M/120V/STD/4P	(4 pack) 40	E26	120	Frost	1 000	C-9	310	120
† 50025	40A19/CL/6M/130V/STD/2P	(2 pack) 40	E26	130	Clear	6 000	C-9	230	120
† 50029	40A19/F/6M/130V/STD/2P	(2 pack) 40	E26	130	Frost	6 000	C-9	220	120
† 50944	40A19/CL/6M/130V/STD/4P	(4 pack) 40	E26	130	Clear	6 000	C-9	230	120
† 50945	40A19/F/6M/130V/STD/4P	(4 pack) 40	E26	130	Frost	6 000	C-9	220	120
† 50935	60A19/CL/1M/120V/STD/4P	(4 pack) 60	E26	120	Clear	1 000	C-9	660	120
† 50026	60A19/CL/6M/130V/STD/2P	(2 pack) 60	E26	130	Clear	6 000	C-9	440	120
† 50946	60A19/CL/6M/130V/STD/4P	(4 pack) 60	E26	130	Clear	6 000	C-9	440	120
† 50936	60A19/F/1M/120V/STD/4P	(4 pack) 60	E26	120	Frost	1 000	C-9	640	120
† 50947	60A19/F/6M/130V/STD/4P	(4 pack) 60	E26	130	Frost	6 000	C-9	430	120
† 50039	60A19/F/6M/130V/STD/2P	(2 pack) 60	E26	130	Frost	6 000	C-9	430	120
† 50938	75A19/F/1M/120V/STD/4P	(4 pack) 75	E26	120	Frost	1 000	C-9	820	120
† 10362	75A19/F/6M/130V/STD/4P	(4 pack) 75	E26	130	Frost	6 000	C-9	480	120
† 10363	75A19/CL/6M/130V/STD/4P	(4 pack) 75	E26	130	Clear	6 000	C-9	490	120
† 50027	100A19/CL/6M/130V/STD/2P	(2 pack) 100	E26	130	Clear	6 000	C-9	700	120
<b>A21</b>									
MOL : 5 3/16 in. (135 mm) LCL : 3 7/32 in. (90 mm)									
† 50116	100A21/CL/5M/130V/STD	100	E26	130	Clear	5 000	C-9	780	120
† 50515	100A21/F/5M/130V/STD	100	E26	130	Frost	5 000	C-9	780	60
† 50481	150A21/F/5M/120V/STD	150	E26	120	Frost	5 000	C-9	1 700	120
† 50085	150A21/CL/5M/130V/STD	150	E26	130	Clear	5 000	C-9	1 250	60
† 50067	150A21/F/5M/130V/STD	150	E26	130	Frost	5 000	C-9	1 250	60
<b>A23</b>									
MOL : 6 3/16 in. (157 mm) LCL : 5 1/2 in. (128 mm)									
† 50163	100A23/CL/5M/130V/STD	100	E26	130	Clear	5 000	C-9	755	60
† 50070	150A23/F/5M/130V/STD	150	E26	130	Frost	5 000	C-9	1 250	60
† 50086	200A23/CL/5M/130V/STD	200	E26	130	Clear	5 000	C-9	1 815	60
† 50068	200A23/F/5M/130V/STD	200	E26	130	Frost	5 000	C-9	1 815	60
<b>B8</b>									
MOL : 3 3/32 in. (80 mm) LCL : 1 7/32 in. (48 mm)									
50635	15B8/CL/2.5M/E12/130V/STD	15	E12	130	Clear	2 500	C-7A	70	120
50638	15B8/F/2.5M/E12/130V/STD	15	E12	130	Frost	2 500	C-7A	70	120
50636	25B8/CL/2.5M/E12/130V/STD	25	E12	130	Clear	2 500	C-7A	150	120
50639	25B8/F/2.5M/E12/130V/STD	25	E12	130	Frost	2 500	C-7A	115	120
50637	40B8/CL/2.5M/E12/130V/STD	40	E12	130	Clear	2 500	CC-2V	235	120
50640	40B8/F/2.5M/E12/130V/STD	40	E12	130	Frost	2 500	CC-2V	230	120
50645	60B8/CL/2.5M/E12/130V/STD	60	E12	130	Clear	2 500	CC-2V	455	120
<b>B10</b>									
MOL : 3 29/32 in. (99 mm) LCL : 1 29/32 in. (45 mm)									
50611	15B10/CL/3M/E12/130V/STD	15	E12	130	Clear	3 000	C-7A	75	120
50543	25B10/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	165	120
50612	25B10/F/3M/E12/130V/STD	25	E12	130	Frost	3 000	CC-2V	165	120
MOL : 3 1/2 in. (89 mm) LCL : 2 1/4 in. (54 mm)									
10499	15B10/F/3M/130V/STD	15	E26	130	Frost	3 000	C-7A	70	500
50632	15B10/CL/3M/130V/STD	15	E26	130	Clear	3 000	C-7A	75	120
50621	25B10/CL/3M/130V/STD	25	E26	130	Clear	3 000	CC-2V	165	120
MOL : 3 29/32 in. (101 mm) LCL : 1 29/32 in. (45 mm)									
50548	25B10/CL/3M/E14/130V/STD	25	E14	130	Clear	3 000	CC-2V	165	120
50551	25B10/F/3M/E14/130V/STD	25	E14	130	Frost	3 000	CC-2V	195	500

† This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>B10 Suitable for base up</b>									
MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)									
50624	25B10/F/3M/130V/STD	25	E26	130	Frost	3 000	CC-2V	165	120
50622	40B10/CL/3M/130V/STD	40	E26	130	Clear	3 000	CC-2V	280	120
50625	40B10/F/3M/130V/STD	40	E26	130	Frost	3 000	CC-2V	280	120
<sup>1</sup> 50623	60B10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-7A/3	415	120
<sup>1</sup> 50626	60B10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-7A/3	415	120
MOL : 3 9/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)									
50544	40B10/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	280	120
50613	40B10/F/3M/E12/130V/STD	40	E12	130	Frost	3 000	CC-2V	280	120
52150	40B10/WH/3M/E12/130V/STD	40	E12	130	White	3 000	C-7A	230	500
50545	60B10/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	C-7A/3	430	120
50614	60B10/F/3M/E12/130V/STD	60	E12	130	Frost	3 000	C-7A/3	430	120
MOL : 3 9/32 in. (101 mm) LCL : 1 25/32 in. (45 mm)									
50549	40B10/CL/3M/E14/130V/STD	40	E14	130	Clear	3 000	CC-2V	280	120
50552	40B10/F/3M/E14/130V/STD	40	E14	130	Frost	3 000	CC-2V	280	120
50550	60B10/CL/3M/E14/130V/STD	60	E14	130	Clear	3 000	C-7A/3	430	120
50553	60B10/F/3M/E14/130V/STD	60	E14	130	Frost	3 000	C-7A/3	430	120
<b>C7</b>									
MOL : 2 1/8 in. (54 mm) LCL : 1 1/2 in. (38 mm)									
50967	4C7/CL/3M/E12/125V/STD	4	E12	125	Clear	3 000	C-7A	25	500
22008	7C7/CL/2M/E12/120V/2P/STD	7	E12	120	Clear	2 000	C-7A	26	120
<b>CA4.5</b>									
MOL : 2 3/4 in. (70 mm) LCL : 1 3/8 in. (41 mm)									
50634	7.5CA4.5/CL/2M/E12/120V/STD	7.5	E12	120	Clear	2 000	C-7A	30	120
50633	7.5CA4.5/CL/2M/E12/130V/STD	7.5	E12	130	Clear	2 000	C-7A	25	500
52154	7.5CA4.5/F/2M/E12/130V/STD	7.5	E12	130	Frost	2 000	C-7A	30	500
52153	10CA4.5/CL/2M/E12/130V/STD	10	E12	130	Clear	2 000	C-7A	40	500
<b>CA8</b>									
MOL : 3 9/32 in. (91 mm) LCL : 1 25/32 in. (45 mm)									
52155	10CA8/CL/2.5M/E12/130V/STD	10	E12	130	Clear	2 500	C-7A	50	500
52157	10CA8/F/2.5M/E12/130V/STD	10	E12	130	Frost	2 500	C-7A	50	500
50641	15CA8/CL/2.5M/E12/130V/STD	15	E12	130	Clear	2 500	C-7A	70	120
10269	15CA8/F/2.5M/E12/130V/STD	15	E12	130	Frost	2 500	C-7A	70	500
52156	25CA8/CL/2.5M/E12/130V/STD	25	E12	130	Clear	2 500	C-7A	120	500
50643	25CA8/F/2.5M/E12/130V/STD	25	E12	130	Frost	2 500	C-7A	115	120
50642	40CA8/CL/2.5M/E12/130V/STD	40	E12	130	Clear	2 500	C-7A	215	500
50644	40CA8/F/2.5M/E12/130V/STD	40	E12	130	Frost	2 500	C-7A	215	500
<b>CA10</b>									
MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)									
51051	25CA10/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-7A	120	500
50629	25CA10/F/3M/130V/STD	25	E26	130	Frost	3 000	C-7A	115	500
50627	40CA10/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-7A	215	500
50630	40CA10/F/3M/130V/STD	40	E26	130	Frost	3 000	C-7A	205	500
<sup>1</sup> 50628	60CA10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-7A	465	500
<sup>1</sup> 50631	60CA10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-7A	470	500
MOL : 4 3/32 in. (104 mm) LCL : 1 7/8 in. (48 mm)									
50615	25CA10/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	135	120
50618	25CA10/F/3M/E12/130V/STD	25	E12	130	Frost	3 000	CC-2V	115	120
50616	40CA10/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	235	120
50619	40CA10/F/3M/E12/130V/STD	40	E12	130	Frost	3 000	CC-2V	205	120
50617	60CA10/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	CC-2V	455	120
50620	60CA10/F/3M/E12/130V/STD	60	E12	130	Frost	3 000	CC-2V	450	120

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>F15</b>									
MOL : 4 1/2 in. (115 mm) LCL : 2 9/16 in. (65 mm)									
50751	25F15/CL/2M/130V/STD	25	E26	130	Clear	2 000	CC-6	160	120
50750	40F15/CL/2M/130V/STD	40	E26	130	Clear	2 000	CC-6	305	120
<sup>1</sup> 50752	60F15/CL/2M/130V/STD	60	E26	130	Clear	2 000	CC-6	275	120
<b>G8</b>									
MOL : 1 7/32 in. (47 mm) LCL : 1 1/16 in. (33 mm)									
52164	5G8/CL/1M/E12/130V/STD	5	E12	130	Clear	1 000	C-7A	40	500
<b>G9.5</b>									
MOL : 2 1/16 in. (52 mm) LCL : 1 1/2 in. (38 mm)									
52165	7.5G9.5/CL/1M/E12/130V/STD	7	E12	130	Clear	1 000	C-7A	40	500
<b>G11</b>									
MOL : 2 3/16 in. (59 mm) LCL : 1 1/2 in. (41 mm)									
50759	7.5G11/CL/1M/E12/130V/STD	7.5	E12	130	Clear	1 000	C-5	510	500
50761	7.5G11/CL/1M/130V/STD	7.5	E26	130	Clear	1 000	C-5	40	500
<b>G13</b>									
MOL : 2 3/8 in. (60.5 mm) LCL : 1 11/16 in. (43 mm)									
50681	10G13/CL/3M/E12/130V/STD	10	E12	130	Clear	3 000	C-7A	50	500
50682	25G13/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	135	120
50683	40G13/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	250	500
50684	60G13/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	C-7A	490	500
<b>G16.5</b>									
MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)									
10334	5G16.5/CL/3M/E12/130V/STD	5	E12	130	Clear	3 000	C-7A	20	500
10268	10G16.5/CL/3M/E12/130V/STD	10	E12	130	Clear	3 000	C-7A	50	500
50660	15G16.5/CL/3M/E12/130V/STD	15	E12	130	Clear	3 000	C-7A	70	120
50662	15G16.5/WH/3M/E12/130V/STD	15	E12	130	White	3 000	C-7A	60	120
50661	15G16.5/CL/3M/130V/STD	15	E26	130	Clear	3 000	C-7A	70	500
50648	25G16.5/CL/3M/E12/130V/STD	25	E12	130	Clear	3 000	CC-2V	135	120
50652	25G16.5/WH/3M/E12/130V/STD	25	E12	130	White	3 000	CC-2V	120	120
50777	25G16.5/CL/3M/E14/130V/STD	25	E14	130	Clear	3 000	CC-6	160	500
50649	25G16.5/CL/3M/130V/STD	25	E26	130	Clear	3 000	CC-2V	135	500
50653	25G16.5/WH/3M/130V/STD	25	E26	130	White	3 000	CC-2V	120	120
50650	40G16.5/CL/3M/E12/130V/STD	40	E12	130	Clear	3 000	CC-2V	250	120
50654	40G16.5/WH/3M/E12/130V/STD	40	E12	130	White	3 000	CC-2V	230	120
50651	40G16.5/CL/3M/130V/STD	40	E26	130	Clear	3 000	CC-2V	250	120
50655	40G16.5/WH/3M/130V/STD	40	E26	130	White	3 000	CC-2V	230	120
50656	60G16.5/CL/3M/E12/130V/STD	60	E12	130	Clear	3 000	CC-2V	440	120
50658	60G16.5/WH/3M/E12/130V/STD	60	E12	130	White	3 000	CC-2V	400	120
<sup>1</sup> 50657	60G16.5/CL/3M/130V/STD	60	E26	130	Clear	3 000	CC-2V	580	500
<sup>1</sup> 50659	60G16.5/WH/3M/130V/STD	60	E26	130	White	3 000	CC-2V	440	120
MOL : 2 3/8 in. (73 mm) LCL : 2 1/16 in. (52 mm)									
50779	25G16.5/WH/3M/E14/130V/STD	25	E14	130	White	3 000	CC-6	150	500
50778	40G16.5/CL/3M/E14/130V/STD	40	E14	130	Clear	3 000	CC-6	315	500
50780	40G16.5/WH/3M/E14/130V/STD	40	E14	130	White	3 000	CC-6	295	500
50782	60G16.5/WH/3M/E14/130V/STD	60	E14	130	White	3 000	CC-6	580	500
<b>G25</b>									
MOL : 2 1/2 in. (114 mm) LCL : 3 1/2 in. (77 mm)									
50199	25G25/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	135	60
50196	25G25/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	115	60
50222	40G25/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	255	60
50155	40G25/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	230	60
<sup>1</sup> 50154	60G25/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-9	460	60
<sup>1</sup> 50197	60G25/WH/3M/130V/STD	60	E26	130	White	3 000	C-9	425	60
<sup>1</sup> 50198	100G25/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	830	60

<sup>1</sup>This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>G30</b>									
MOL : 5 3/32 in. (137 mm) LCL : 3 3/32 in. (83 mm)									
50203	25G30/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	115	100
50201	25G30/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	100	60
50204	40G30/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	230	60
50202	40G30/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	215	60
1 50157	100G30/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	850	60
<b>G40</b>									
MOL : 6 15/16 in. (176 mm) LCL : 5 29/32 in. (99 mm)									
50205	25G40/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-9	100	12
50209	25G40/WH/3M/130V/STD	25	E26	130	White	3 000	C-9	100	24
50206	40G40/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-9	230	12
50150	40G40/WH/3M/130V/STD	40	E26	130	White	3 000	C-9	215	24
50111	60G40/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-9	465	12
50158	60G40/WH/3M/130V/STD	60	E26	130	White	3 000	C-9	365	12
50207	100G40/CL/3M/130V/STD	100	E26	130	Clear	3 000	C-9	760	12
50210	100G40/WH/3M/130V/STD	100	E26	130	White	3 000	C-9	820	12
50208	150G40/CL/3M/130V/STD	150	E26	130	Clear	3 000	C-9	1 175	12
50112	150G40/WH/3M/130V/STD	150	E26	130	White	3 000	C-9	1 175	12
<b>PS25</b>									
MOL : 6 15/16 in. (176 mm) LCL : 5 1/2 in. (128 mm)									
50140	150PS25/CL/5M/130V/STD	150	E26	130	Clear	5 000	C-9	1 210	60
50072	200PS25/F/5M/130V/STD	200	E26	130	Frost	5 000	C-9	1 815	24
50071	300PS25/CL/5M/130V/STD	300	E26	130	Clear	5 000	C-9	2 725	24
50088	300PS25/F/5M/130V/STD	300	E26	130	Frost	5 000	C-9	2 725	24
<b>PS30</b>									
MOL : 8 1/16 in. (204 mm) LCL : 5 13/32 in. (137 mm)									
52428	300PS30/CL/120V/STD	300	E26	120	Clear	5 000	C-9	3 600	24
51122	300PS30/F/5M/130V/STD	300	E26	130	Frost	5 000	C-9	2 725	24
<b>PS35</b>									
MOL : 9 13/32 in. (239 mm) LCL : 6 1/2 in. (165 mm)									
50225	300PS35/CL/5M/E39/130V/STD	300	E39	130	Clear	5 000	C-9	2 725	24
50226	300PS35/F/5M/E39/130V/STD	300	E39	130	Frost	5 000	C-9	2 725	24
50227	500PS35/CL/5M/E39/130V/STD	500	E39	130	Clear	5 000	C-9	6 055	24
50228	500PS35/F/5M/E39/130V/STD	500	E39	130	Frost	5 000	C-9	6 055	24
<b>S11</b>									
MOL : 2 3/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)									
50789	5S11/CL/1M/E17/130V/STD	5	E17	130	Clear	1 000	C-7A	25	500
50143	10S11/CL/1M/E17/130V/STD	10	E17	130	Clear	1 000	C-7A	60	120
50165	10S11/F/1M/E17/130V/STD	10	E17	130	Frost	1 000	C-7A	60	500
50787	15S11/CL/1M/E17/130V/STD	15	E17	130	Clear	1 000	C-7A	60	500
50786	25S11/CL/1M/E17/130V/STD	25	E17	130	Clear	1 000	C-7A	130	500
50785	30S11/CL/1M/E17/130V/STD	30	E17	130	Clear	1 000	C-7A	240	500
50784	30S11/F/1M/E17/130V/STD	30	E17	130	Frost	1 000	C-7A	235	500
50123	40S11/CL/1M/E17/130V/STD	40	E17	130	Clear	1 000	C-7A	275	120
50783	40S11/F/1M/E17/130V/STD	40	E17	130	Frost	1 000	C-7A	295	500
<b>S14</b>									
MOL : 2 3/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)									
59542	11S14/CL/8M/130V/STD	11	E26	130	Clear	8 000	C-9	40	24
50147	11S14/CL/3M/130V/STD	11	E26	130	Clear	3 000	C-9	72	500
10158	11S14/F/3M/130V/STD	11	E26	130	Frost	3 000	C-9	50	500

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps



Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Lumens at 120 V (lm)	Case qty
<b>T6</b>									
MOL : 3 1/16 in. (78 mm) LCL : 1 3/16 in. (40 mm)									
50667	15T6/CL/7.5M/E12/130V/STD	15	E12	130	Clear	7 500	C-5A	75	120
50668	15T6/CL/7.5M/E12/145V/STD	15	E12	145	Clear	7 500	C-5A	90	120
50675	15T6/CL/5M/E17/130V/STD	15	E17	130	Clear	5 000	C-5A	70	120
50676	15T6/CL/7.5M/E17/145V/STD	15	E17	145	Clear	7 500	C-5A	90	120
<b>T6.5</b>									
MOL : 5 13/32 in. (137 mm) LCL : 3 5/32 in. (80 mm)									
52127	7T6.5/CL/40M/ES/E12/145V/STD	7	E12	145	Clear	40 000	D	40	500
52128	7T6.5/CL/40M/ES/E17/145V/STD	7	E17	145	Clear	40 000	D	40	500
51052	20T6.5/CL/5M/BA15d/130V/STD	20	BA15d	130	Clear	5 000	C-8	115	500
50679	20T6.5/F/5M/BA15d/130V/STD	20	BA15d	130	Frost	5 000	C-8	115	120
50677	20T6.5/CL/5M/E17/130V/STD	20	E17	130	Clear	5 000	C-8	115	120
50678	20T6.5/F/5M/E17/130V/STD	20	E17	130	Frost	5 000	C-8	115	120
51056	25T6.5/CL/5M/BA15d/125V/STD	25	BA15d	125	Clear	5 000	C-8	180	500
50674	25T6.5/CL/7.5M/BA15d/145V/STD	25	BA15d	145	Clear	7 500	C-8	180	120
50729	25T6.5/F/7.5M/BA15d/145V/STD	25	BA15d	145	Frost	7 500	C-8	145	500
50671	25T6.5/CL/5M/E12/130V/STD	25	E12	130	Clear	5 000	C-8	135	120
50672	25T6.5/CL/7.5M/E12/145V/STD	25	E12	145	Clear	7 500	C-8	180	120
50669	25T6.5/CL/5M/E17/130V/STD	25	E17	130	Clear	5 000	C-8	135	120
50670	25T6.5/CL/7.5M/E17/145V/STD	25	E17	145	Clear	7 500	C-8	180	120
50673	25T6.5/F/7.5M/E17/145V/STD	25	E17	145	Frost	7 500	C-8	180	500
50680	40T6.5/CL/5M/E17/130V/STD	40	E17	130	Clear	5 000	C-8	280	120
52191	40T6.5/F/5M/E17/130V/STD	40	E17	130	Frost	5 000	C-8	210	500
<b>T7</b>									
MOL : 2 3/16 in. (59 mm) LCL : 1 3/16 in. (33 mm)									
52195	15T7/CL/1.5M/BA15d/120V/STD	15	BA15d	120	Clear	1 500	C-7A	100	1 000
52196	15T7/F/1.5M/BA15d/130V/STD	15	BA15d	130	Frost	1 500	C-7A	75	1 000
52192	15T7/CL/1.5M/E12/120V/STD	15	E12	120	Clear	1 500	C-7A	100	1 000
52194	15T7/CL/1.5M/E17/120V/STD	15	E17	120	Clear	1 500	C-7A	100	1 000
52201	25T7/CL/1.5M/E12/130V/STD	25	E12	130	Clear	1 500	C-7A	115	1 000
<b>T8</b>									
MOL : 2 9/16 in. (65 mm) LCL : 1 3/8 in. (41 mm)									
52198	25T8/CL/1.5M/BA15d/120V/STD	25	BA15d	120	Clear	1 500	C-7A	220	1 000
52199	25T8/F/1.5M/BA15d/130V/STD	25	BA15d	130	Frost	1 500	C-7A	160	1 000
52200	25T8/CL/1.5M/E12/120V/STD	25	E12	120	Clear	1 500	C-7A	220	1 000
52197	25T8/CL/1.5M/E17/120V/STD	25	E17	120	Clear	1 500	C-7A	220	1 000
<b>T10</b>									
MOL : 5 in. (127 mm) LCL : 2 3/4 in. (70 mm)									
50923	15T10/CL/3M/130V/STD	15	E26	130	Clear	3 000	C-5V	75	120
50924	15T10/F/3M/130V/STD	15	E26	130	Frost	3 000	C-5V	75	120
50925	25T10/CL/3M/130V/STD	25	E26	130	Clear	3 000	C-5V	135	120
50928	25T10/F/3M/130V/STD	25	E26	130	Frost	3 000	C-5V	135	120
50926	40T10/CL/3M/130V/STD	40	E26	130	Clear	3 000	C-5V	195	120
50929	40T10/F/3M/130V/STD	40	E26	130	Frost	3 000	C-5V	195	120
<sup>1</sup> 50927	60T10/CL/3M/130V/STD	60	E26	130	Clear	3 000	C-5V	365	120
<sup>1</sup> 50930	60T10/F/3M/130V/STD	60	E26	130	Frost	3 000	C-5V	365	120
<b>T10 HO</b>									
MOL : 5 13/32 in. (137 mm) LCL : 3 23/32 in. (85 mm)									
50164	15T10/CL/3M/HO/130V/STD	15	E26	130	Clear	3 000	C-8	70	120
50149	25T10/CL/3M/HO/130V/STD	25	E26	130	Clear	3 000	C-8	175	120
50131	25T10/F/3M/HO/130V/STD	25	E26	130	Frost	3 000	C-8	175	120
50129	40T10/CL/3M/HO/130V/STD	40	E26	130	Clear	3 000	C-8	300	120
50132	40T10/F/3M/HO/130V/STD	40	E26	130	Frost	3 000	C-8	300	120
<sup>1</sup> 50130	60T10/CL/3M/HO/130V/STD	60	E26	130	Clear	3 000	C-8	530	120
<sup>1</sup> 50133	60T10/F/3M/HO/130V/STD	60	E26	130	Frost	3 000	C-8	530	120

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

# General Service Lamps