



**DIMMABLE LAMP SERIES** made available in three shapes to create ambiance and lighting effects in residential and commercial applications.

- ▶ Dimmable in a range of 100 % - 20 %\*
- ▶ Spiral and A Shape approved for use in totally enclosed fixtures.
- ▶ Operating temperatures:  
E26 base: -20 ° C/ -4 ° F to 60 ° C/140 ° F  
GU24 base: -18 ° C/0 ° F to 50 ° C/ 123 ° F

Spiral (GU24)



Spiral (E26)



A19



R30



Order code	Description	Watts (W)	Base	Colour temp. (K)	CRI	Average life (hrs)	Initial lumens (lm)	Case qty	Incandescent equivalent (W)
<b>Spiral GU24 Base</b>		13 W: MOL : 3 15/16 in. (100 mm) 23 W: MOL : 4 29/32 in. (123 mm)		Dia. : 1 15/32 in. (50 mm) Dia. : 2 1/8 in. (54 mm)					
60920	CF13/D/27K/SPIRAL/GU24/STD	13	GU24	2 700	82	10 000	800	48	60
60921	CF23/D/27K/SPIRAL/GU24/STD	23	GU24	2 700	82	10 000	1 500	48	100
<b>Spiral E26 Base</b>		14 W: MOL : 4 21/32 in. (118 mm) 23 W: MOL : 4 15/32 in. (139 mm)		Dia. : 1 25/32 in. (45 mm) Dia. : 2 15/32 in. (63 mm)					
58935	CF14/D/27K/SPIRALE/E26/STD	14	E26	2 700	82	8 000	800	48	60
59611	CF23/D/27K/SPIRAL/E26/STD	23	E26	2 700	82	8 000	1 600	48	100
<b>A Shape</b>		MOL : 3 in. (127 mm)		Dia. : 2 13/32 in. (61 mm)					
58936	CF16/D/27K/A19/E26/STD	16	E26	2 700	82	8 000	800	48	60
<b>R Shape</b>		MOL : 5 5/8 in. (143 mm)		Dia. : 3 11/16 in. (94 mm)					
58934	CF16/D/27K/R30/E26/STD	16	E26	2 700	82	8 000	700	12	65



\*When used with compatible dimmers. For more detailed information please refer to the document called "Use of dimmable lamps" on our website at [www.standardpro.com](http://www.standardpro.com).

# Dimmable Lamps

# Cold Cathode Fluorescent Lamps

CCFL are very long lasting, consume little energy, provide colour consistency and are dimmable.\*

The term "cold cathode" refers to the fact that the cathode is not independently heated. The voltage potential within the tube is sufficient to ionize the gas in the tube and cause current flow.

This technology is ideal for rapid cycling applications such as frequent on-off switching and dimming without impacting lamp life.



Order code	Description	Watts (W)	Base	Colour temp. (K)	Colour	CRI	Average life (hrs)	Initial lumens (lm)	Power factor	Case qty	Incandescent equivalent (W)
<b>A19</b> 8 W: MOL : 4 13/32 in. (115 mm)    Dia. : 2 1/8 in. (60 mm)											
58427	CCFL8/F/A19/25M/E26/STD	8	E26	2 700	Frost	82	25 000	320	>0.9	48	35-40
58428	CCFL8/B/A19/25M/E26/STD	8	E26	N/A	Blue	N/A	25 000	N/A	>0.9	48	35-40
58429	CCFL8/Y/A19/25M/E26/STD	8	E26	N/A	Yellow	N/A	25 000	N/A	>0.9	48	35-40
58430	CCFL8/R/A19/25M/E26/STD	8	E26	N/A	Red	N/A	25 000	N/A	>0.9	48	35-40
58431	CCFL8/G/A19/25M/E26/STD	8	E26	N/A	Green	N/A	25 000	N/A	>0.9	48	35-40
<b>Candle</b> 5 W: MOL : 4 13/32 in. (112 mm)    Dia. : 1 13/32 in. (37 mm) 8 W: MOL : 4 13/32 in. (112 mm)    Dia. : 1 13/32 in. (37 mm)											
58425	CCFL5/WH/CANDLE/25M/E12/STD	5	E12	2 700	White	82	25 000	200	>0.9	48	25-30
58432	CCFL8/WH/CANDLE/25M/E12/STD	8	E12	2 700	White	82	25 000	300	>0.9	48	35-40
<b>Globe G25</b> 8 W: MOL : 4 13/16 in. (122 mm)    Dia. : 3 1/8 in. (79 mm)											
58433	CCFL8/WH/G25/25M/E26/STD	8	E26	2 700	White	82	25 000	300	>0.9	24	25-30
<b>PAR38</b> 18 W: MOL : 4 3/8 in. (124 mm)    Dia. : 4 23/32 in. (120 mm)											
59615	CCFL18/27K/PAR38/25M/E26/STD	18	E26	2 700	N/A	82	25 000	800	>0.9	32	75*
59614	CCFL18/41K/PAR38/25M/E26/STD	18	E26	4 100	N/A	82	25 000	800	>0.9	32	75*
<b>R20</b> 5 W: MOL : 4 1/4 in. (108 mm)    Dia. : 2 13/32 in. (63 mm)											
58426	CCFL5/F/R20/25M/E26/STD	5	E26	2 700	Frost	82	25 000	120	>0.9	36	15-20
<b>S14</b> 3 W: MOL : 3 1/8 in. (92 mm)    Dia. : 1 23/32 in. (45 mm)											
58415	CCFL3/B/S14/25M/E26/STD	3	E26	N/A	Blue	N/A	25 000	N/A	>0.9	48	15-20
58416	CCFL3/Y/S14/25M/E26/STD	3	E26	N/A	Yellow	N/A	25 000	N/A	>0.9	48	15-20
58417	CCFL3/R/S14/25M/E26/STD	3	E26	N/A	Red	N/A	25 000	N/A	>0.9	48	15-20
58418	CCFL3/G/S14/25M/E26/STD	3	E26	N/A	Green	N/A	25 000	N/A	>0.9	48	15-20



\*When used with compatible dimmers. For more detailed information please refer to the document called "Use of dimmable lamps" on our website at [www.standardpro.com](http://www.standardpro.com).

## Dimmable CCFL Lamps