

Miniature - Miniatures



Fig.17



Fig.16



Fig.14



Fig.15

3

Line Ligne	Lamp Shape Forme lampe	Volts Tension	Amps (A) Watts Puiss. (W)	Lamp Base Culot Lampe	Internal Code Interne	Filament	Couleur Couleur	Avg. Life (Hrs) Vie moy. (Hres)	Lumens	MSCP	L.C.L. Inches - (mm) H.C.L. Pouces - (mm)	M.O.L. Inches - (mm) L.H.T.M. Pouces - (mm)	Diam. inches (mm) Pouces (mm)	Fig. # Nº Fig.
---------------	---------------------------------	------------------	---------------------------------	--------------------------------	-----------------------------	----------	--------------------	--	--------	------	--	--	-------------------------------------	-------------------------

G-4 1/2 Bulb Lampe G-4 1/2

98	G-4 1/2	4.9	0.3A	BA9s	408	C-2R Bi-Metal		50	1,2		5/8 (15.8)	1 1/16 (27)	9/16 (15)	17
99	G-4 1/2	5	0.5A	BA9s	427	C-2R		15	2,3		1/2 (12.7)	1 1/16 (27)	9/16 (15)	16
100	G-4 1/2	5.1	0.15A	BA9s	503	C-2R		100	0,6		1/2 (12.7)	1 1/16 (27)	9/16 (15)	16
101	G-4 1/2	6	0.5A	BA9s	607	C-2R		3	3,7		1/2 (12.7)	1 1/16 (27)	9/16 (15)	16
102	G-4 1/2	6.5	0.5A	BA9s	455	C-2R Bi-Metal		500	1,9		9/16 (14.2)	1 1/16 (27)	9/16 (15)	17
103	G-4 1/2	7	0.41A	BA9s	55	C-2R		500	2		9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
104	G-4 1/2	14	0.24A	BA9s	57	C-2V		500	2		9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
105	G-4 1/2	14	0.24A	BA9s	57X	C-2F		500	2		9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
106	G-4 1/2	14	0.25A	BA9s	431	C-2V		250	2,7		1/2 (12.7)	1 1/16 (27)	9/16 (15)	16
107	G-4 1/2	14	0.27A	BA9s	257	C-2R Bi-Metal		500	1,6		9/16 (14.2)	1 1/16 (27)	9/16 (15)	17
108	G-4 1/2	14	0.27A	BA9s	1895	C-2F		2000	2		9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
109	G-4 1/2	14	0.33A	BA9s	293	C-2F		7500	2		9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
110	G-4 1/2	24	0.08A	BA9s	A854	C-2F		3000			9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
111	G-4 1/2	28	0.08A	BA9s	A855	C-2F		3000			9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
112	G-4 1/2	28	0.17A	BA9s	456	C-2F		5000	2		9/16 (14.2)	1 1/16 (27)	9/16 (15)	16
113	G-4 1/2	1.25	0.22A	E10	401	S-2 Bi-Metal		15	0,09		7/8 (22.2)	1 1/16 (27)	9/16 (15)	14
114	G-4 1/2	1.25	0.6A	E10	136	S-2		75	0,2		3/4 (19)	1 1/16 (27)	9/16 (15)	15
115	G-4 1/2	2.6	0.3A	E10	406	C-2R Bi-Metal		50	0,43		7/8 (22.2)	1 1/16 (27)	9/16 (15)	14
116	G-4 1/2	4.9	0.3A	E10	27	C-2R		30	1,4		23/32 (18.3)	1 1/16 (27)	9/16 (15)	15
117	G-4 1/2	4.9	0.3A	E10	407	C-2R Bi-Metal		50	1,2		13/16 (20.6)	1 1/16 (27)	9/16 (15)	14
118	G-4 1/2	5	0.5A	E10	425	C-2R		15	2,3		23/32 (18.3)	1 1/16 (27)	9/16 (15)	15
119	G-4 1/2	5.1	0.15A	E10	502	C-2R		100	0,6		23/32 (18.3)	1 1/16 (27)	9/16 (15)	15
120	G-4 1/2	6	0.04A	E10	1483	C-6		500	0,1		13/16 (20.6)	1 1/16 (27)	9/16 (15)	15
121	G-4 1/2	6	0.25A	E10	437	C-2R		500			23/32 (18.3)	1 1/16 (27)	9/16 (15)	15
122	G-4 1/2	6	0.45A	E10	1482	C-2R		100	2,2		13/16 (20.6)	1 1/16 (27)	9/16 (15)	15
123	G-4 1/2	6	0.5A	E10	435	C-2R		500			23/32 (18.3)	1 1/16 (27)	9/16 (15)	15
124	G-4 1/2	6	2.4W	E10	3724	C-2R					23/32 (18.3)	1 1/8 (28.5)	9/16 (15)	15