




0.51" - 12.95 mm

1.02" - 25.91 mm

38033



1.31" - 33.27 mm

1.25" - 31.75 mm

38034



1.64" - 41.55 mm

1.05" - 26.50 mm

38230



1.43" - 36.32 mm

2.33" - 59.18 mm

10736



1.43" - 36.32 mm

2.75" - 69.85 mm

10737



1.26" - 32.00 mm

2.00" - 50.80 mm

38017



0.33" - 8.38 mm

1.96" - 49.78 mm

38197



1.01" - 25.65 mm

1.65" - 41.91 mm

38240



1.27" - 32.26 mm

1.66" - 42.16 mm


38241



1.26" - 32.00 mm

2.00" - 50.80 mm

38242



1.27" - 32.26 mm

1.60" - 40.64 mm

38243



0.72" - 18.29 mm

1.59" - 40.39 mm

38244



1.22" - 31.00 mm

1.66" - 42.16 mm


58791



1.22" - 31.00 mm

1.50" - 38.10 mm

58792




1.07" - 27.18 mm

0.57" - 14.48 mm

38003

Code de commande	Description	Base	Volts (V)	Watts (W)
38033	SK1062 DOUILLE POUR CIRC. 9"	G10-q	600	660
38034	MONTAGE A VIS VERTICAL	G23 / G23-2	600	75
38230	2 EXTENSIONS MONTAGE A POUSSER	GR10q	600	660
10736	T8/T12 TALL PRF TURN SCREW MNT	G13	600	660
10737	T8/T12 W/STARTER BASE SCR MNT	G13	600	660
38017	T8/T12 TALL PRF w/CN SCR/SLDE	G13	600	660
38197	T8/T12 LONGUE ENLENCEMENT RAPIDE SHT	G13	600	660
38240	T8/T12 LOW PRF SLIDE MNT STD	G13	600	660
38241	T8/T12 COURTE MONTURE A GLISS SHT STD	G13	600	660
38242	T8/T12 TALL PRF SLIDE MNT STD	G13	600	660
38243	T8/T12 LOW PRF U SLIDE MNT STD	G13	600	660
38244	T8/T12 COURTE MONTURE A GLISS U SHT STD	G13	600	660
58791	T8/T12 ROTATIVE SHUNTEE LONGUE VERROUILL	G13	600	660
58792	T8/T12 ROTATIVE SHUNTEE COURTE VERROUILL	G13	600	660
38003	T5 REAR SNP MNT LOCK w/SPG PLT	G5	600	75

*Moy. 2 broches = G13
Min. 2 broches = G5



Code de commande	Description	Base	Volts (V)	Watts (W)
38004	T5 MED SNP/SCR MNT ROT. LOCK	G5	600	75
38245	T5 SNAP-IN or SCREW MNT STD	G5	600	120
38022	T12 HO EMB RESS VERT FILS 9"	R17d	600	660
38023	T12 HO EMB FIXE VERT FILS 9"	R17d	600	660
38024	SK82 SNAP-IN STATIONARY END	R17d	600	660
38025	T12 HO SNPIN/SPRING END R17d	R17d	600	660
38026	T12 HO FIX END SLD/LCK-ON MNT	R17d	600	660
38027	T12 HO PLNG END SLD/LCK-ON MNT	R17d	600	1000
38030	SK900 BOUT FIXE HORIZONTAL	R17d	600	660
38031	SK901 BOUT HORIZONTAL aRESSORT	R17d	1000	660
59799	T8/T12 BOUT FIXE/GLISSIERE	R17d	600	660
59800	T8/T12 BOUT A RESSORT/GLISSIERE	R17d	600	660
38020	T8/T12 SLIML STAT END SLD MNT	Fa8	600	660
38021	T8/T12 SLIML PLNG END SLD MNT	Fa8	600	1 000

*Min. 2 broches = G5
1 broche = Fa8