

Code de commande	Description	Watts (W)	Culot	Volts (V)	Finition/Couleur	Vie moyenne (h)	Filament	Lumens à 120 V (lm)	Qté boîte
G30									
LHTM : 5 ³ / ₃₂ po (137 mm) HCL : 3 ⁹ / ₃₂ po (83 mm)									
50203	25G30/CL/3M/130V/STD	25	E26	130	Claire	3 000	C-9	115	100
50201	25G30/WH/3M/130V/STD	25	E26	130	Blanche	3 000	C-9	100	60
50204	40G30/CL/3M/130V/STD	40	E26	130	Claire	3 000	C-9	230	60
50202	40G30/WH/3M/130V/STD	40	E26	130	Blanche	3 000	C-9	215	60
50157	100G30/WH/3M/130V/STD	100	E26	130	Blanche	3 000	C-9	850	60
G40									
LHTM : 6 ³ / ₁₆ po (176 mm) HCL : 3 ⁹ / ₃₂ po (99 mm)									
50205	25G40/CL/3M/130V/STD	25	E26	130	Claire	3 000	C-9	100	12
50209	25G40/WH/3M/130V/STD	25	E26	130	Blanche	3 000	C-9	100	24
50206	40G40/CL/3M/130V/STD	40	E26	130	Claire	3 000	C-9	230	12
50150	40G40/WH/3M/130V/STD	40	E26	130	Blanche	3 000	C-9	215	24
50111	60G40/CL/3M/130V/STD	60	E26	130	Claire	3 000	C-9	465	12
50158	60G40/WH/3M/130V/STD	60	E26	130	Blanche	3 000	C-9	365	12
50207	100G40/CL/3M/130V/STD	100	E26	130	Claire	3 000	C-9	760	12
50210	100G40/WH/3M/130V/STD	100	E26	130	Blanche	3 000	C-9	820	12
50208	150G40/CL/3M/130V/STD	150	E26	130	Claire	3 000	C-9	1 175	12
50112	150G40/WH/3M/130V/STD	150	E26	130	Blanche	3 000	C-9	1 175	12
PS25									
LHTM : 6 ³ / ₁₆ po (176 mm) HCL : 5 ¹ / ₃₂ po (128 mm)									
50140	150PS25/CL/5M/130V/STD	150	E26	130	Claire	5 000	C-9	1 210	60
50072	200PS25/F/5M/130V/STD	200	E26	130	Givrée	5 000	C-9	1 815	24
50071	300PS25/CL/5M/130V/STD	300	E26	130	Claire	5 000	C-9	2 725	24
50088	300PS25/F/5M/130V/STD	300	E26	130	Givrée	5 000	C-9	2 725	24
PS30									
LHTM : 8 ¹ / ₁₆ po (204 mm) HCL : 5 ¹³ / ₃₂ po (137 mm)									
52428	300PS30/CL/120V/STD	300	E26	120	Claire	5 000	C-9	3 600	24
51122	300PS30/F/5M/130V/STD	300	E26	130	Givrée	5 000	C-9	2 725	24
PS35									
LHTM : 9 ³ / ₃₂ po (239 mm) HCL : 6 ¹ / ₂ po (165 mm)									
50225	300PS35/CL/5M/E39/130V/STD	300	E39	130	Claire	5 000	C-9	2 725	24
50226	300PS35/F/5M/E39/130V/STD	300	E39	130	Givrée	5 000	C-9	2 725	24
50227	500PS35/CL/5M/E39/130V/STD	500	E39	130	Claire	5 000	C-9	6 055	24
50228	500PS35/F/5M/E39/130V/STD	500	E39	130	Givrée	5 000	C-9	6 055	24
S11									
LHTM : 2 ⁵ / ₁₆ po (59 mm) HCL : 1 ¹ / ₂ po (38 mm)									
50789	5S11/CL/1M/E17/130V/STD	5	E17	130	Claire	1 000	C-7A	25	500
50143	10S11/CL/1M/E17/130V/STD	10	E17	130	Claire	1 000	C-7A	60	120
50165	10S11/F/1M/E17/130V/STD	10	E17	130	Givrée	1 000	C-7A	60	500
50787	15S11/CL/1M/E17/130V/STD	15	E17	130	Claire	1 000	C-7A	60	500
50786	25S11/CL/1M/E17/130V/STD	25	E17	130	Claire	1 000	C-7A	130	500
50785	30S11/CL/1M/E17/130V/STD	30	E17	130	Claire	1 000	C-7A	240	500
50784	30S11/F/1M/E17/130V/STD	30	E17	130	Givrée	1 000	C-7A	235	500
50123	40S11/CL/1M/E17/130V/STD	40	E17	130	Claire	1 000	C-7A	275	120
50783	40S11/F/1M/E17/130V/STD	40	E17	130	Givrée	1 000	C-7A	295	500
S14									
LHTM : 2 ⁵ / ₁₆ po (59 mm) HCL : 1 ¹ / ₂ po (38 mm)									
59542	11S14/CL/8M/130V/STD	11	E26	130	Claire	8 000	C-9	40	24
50147	11S14/CL/3M/130V/STD	11	E26	130	Claire	3 000	C-9	72	500
10158	11S14/F/3M/130V/STD	11	E26	130	Givrée	3 000	C-9	50	500

*Cet item n'est plus produit conformément à la loi sur les standards en matière d'efficacité énergétique, il sera disponible jusqu'à épuisement des stocks.

Lampes d'usage général