

Code de commande	Description	Watts (W)	Culot	Volts (V)	Finition/ Couleur	Vie moyenne (h)	Filament	Lumens à 120 V (lm)	Qté boîte
<b>B10 (Adaptées pour utilisation culot vers le haut)</b>									
LHTM : 3 1/2 po (89 mm) HCL : 2 3/8 po (54 mm)									
50624	25B10/F/3M/130V/STD	25	E26	130	Givrée	3 000	CC-2V	165	120
50622	40B10/CL/3M/130V/STD	40	E26	130	Claire	3 000	CC-2V	280	120
50625	40B10/F/3M/130V/STD	40	E26	130	Givrée	3 000	CC-2V	280	120
<sup>1</sup> 50623	60B10/CL/3M/130V/STD	60	E26	130	Claire	3 000	C-7A/3	415	120
<sup>1</sup> 50626	60B10/F/3M/130V/STD	60	E26	130	Givrée	3 000	C-7A/3	415	120
LHTM : 3 29/32 po (99 mm) HCL : 1 29/32 po (45 mm)									
50544	40B10/CL/3M/E12/130V/STD	40	E12	130	Claire	3 000	CC-2V	280	120
50613	40B10/F/3M/E12/130V/STD	40	E12	130	Givrée	3 000	CC-2V	280	120
52150	40B10/WH/3M/E12/130V/STD	40	E12	130	Blanche	3 000	C-7A	230	500
50545	60B10/CL/3M/E12/130V/STD	60	E12	130	Claire	3 000	C-7A/3	430	120
50614	60B10/F/3M/E12/130V/STD	60	E12	130	Givrée	3 000	C-7A/3	430	120
LHTM : 3 29/32 po (101 mm) HCL : 1 29/32 po (45 mm)									
50549	40B10/CL/3M/E14/130V/STD	40	E14	130	Claire	3 000	CC-2V	280	120
50552	40B10/F/3M/E14/130V/STD	40	E14	130	Givrée	3 000	CC-2V	280	120
50550	60B10/CL/3M/E14/130V/STD	60	E14	130	Claire	3 000	C-7A/3	430	120
50553	60B10/F/3M/E14/130V/STD	60	E14	130	Givrée	3 000	C-7A/3	430	120
<b>C7</b>									
LHTM : 2 3/4 po (54 mm) HCL : 1 1/2 po (38 mm)									
50967	4C7/CL/3M/E12/125V/STD	4	E12	125	Claire	3 000	C-7A	25	500
22008	7C7/CL/2M/E12/120V/2P/STD	7	E12	120	Claire	2 000	C-7A	26	120
<b>CA4.5</b>									
LHTM : 2 3/4 po (70 mm) HCL : 1 5/8 po (41 mm)									
50634	7.5CA4.5/CL/2M/E12/120V/STD	7.5	E12	120	Claire	2 000	C-7A	30	120
50633	7.5CA4.5/CL/2M/E12/130V/STD	7.5	E12	130	Claire	2 000	C-7A	25	500
52154	7.5CA4.5/F/2M/E12/130V/STD	7.5	E12	130	Givrée	2 000	C-7A	30	500
52153	10CA4.5/CL/2M/E12/130V/STD	10	E12	130	Claire	2 000	C-7A	40	500
<b>CA8</b>									
LHTM : 3 29/32 po (91 mm) HCL : 1 29/32 po (45 mm)									
52155	10CA8/CL/2.5M/E12/130V/STD	10	E12	130	Claire	2 500	C-7A	50	500
52157	10CA8/F/2.5M/E12/130V/STD	10	E12	130	Givrée	2 500	C-7A	50	500
50641	15CA8/CL/2.5M/E12/130V/STD	15	E12	130	Claire	2 500	C-7A	70	120
10269	15CA8/F/2.5M/E12/130V/STD	15	E12	130	Givrée	2 500	C-7A	70	500
52156	25CA8/CL/2.5M/E12/130V/STD	25	E12	130	Claire	2 500	C-7A	120	500
50643	25CA8/F/2.5M/E12/130V/STD	25	E12	130	Givrée	2 500	C-7A	115	120
50642	40CA8/CL/2.5M/E12/130V/STD	40	E12	130	Claire	2 500	C-7A	215	500
50644	40CA8/F/2.5M/E12/130V/STD	40	E12	130	Givrée	2 500	C-7A	215	500
<b>CA10</b>									
LHTM : 3 29/32 po (99 mm) HCL : 2 1/4 po (54 mm)									
51051	25CA10/CL/3M/130V/STD	25	E26	130	Claire	3 000	C-7A	120	500
50629	25CA10/F/3M/130V/STD	25	E26	130	Givrée	3 000	C-7A	115	500
50627	40CA10/CL/3M/130V/STD	40	E26	130	Claire	3 000	C-7A	215	500
50630	40CA10/F/3M/130V/STD	40	E26	130	Givrée	3 000	C-7A	205	500
<sup>1</sup> 50628	60CA10/CL/3M/130V/STD	60	E26	130	Claire	3 000	C-7A	465	500
<sup>1</sup> 50631	60CA10/F/3M/130V/STD	60	E26	130	Givrée	3 000	C-7A	470	500
LHTM : 4 1/2 po (104 mm) HCL : 1 7/8 po (48 mm)									
50615	25CA10/CL/3M/E12/130V/STD	25	E12	130	Claire	3 000	CC-2V	135	120
50618	25CA10/F/3M/E12/130V/STD	25	E12	130	Givrée	3 000	CC-2V	115	120
50616	40CA10/CL/3M/E12/130V/STD	40	E12	130	Claire	3 000	CC-2V	235	120
50619	40CA10/F/3M/E12/130V/STD	40	E12	130	Givrée	3 000	CC-2V	205	120
50617	60CA10/CL/3M/E12/130V/STD	60	E12	130	Claire	3 000	CC-2V	455	120
50620	60CA10/F/3M/E12/130V/STD	60	E12	130	Givrée	3 000	CC-2V	450	120

<sup>1</sup>Cet item n'est plus produit conformément à la loi sur les standards en matière d'efficacité énergétique, il sera disponible jusqu'à épuisement des stocks.

# Lampes d'usage général