

Code de commande	Description	Watts (W)	Culot	Volts (V)	Finition/ Couleur	Vie moyenne (h)	Filament	Lumens à 120 V (lm)	Qté boîte
<b>T6</b>									
LHTM : 3 1/16 po (78 mm) HCL : 1 1/16 po (40 mm)									
50667	15T6/CL/7.5M/E12/130V/STD	15	E12	130	Claire	7 500	C-5A	75	120
50668	15T6/CL/7.5M/E12/145V/STD	15	E12	145	Claire	7 500	C-5A	90	120
50675	15T6/CL/5M/E17/130V/STD	15	E17	130	Claire	5 000	C-5A	70	120
50676	15T6/CL/7.5M/E17/145V/STD	15	E17	145	Claire	7 500	C-5A	90	120
<b>T6.5</b>									
LHTM : 5 13/32 po (137 mm) HCL : 3 5/32 po (80 mm)									
52127	7T6.5/CL/40M/ES/E12/145V/STD	7	E12	145	Claire	40 000	D	40	500
52128	7T6.5/CL/40M/ES/E17/145V/STD	7	E17	145	Claire	40 000	D	40	500
51052	20T6.5/CL/5M/BA15d/130V/STD	20	BA15d	130	Claire	5 000	C-8	115	500
50679	20T6.5/F/5M/BA15d/130V/STD	20	BA15d	130	Givrée	5 000	C-8	115	120
50677	20T6.5/CL/5M/E17/130V/STD	20	E17	130	Claire	5 000	C-8	115	120
50678	20T6.5/F/5M/E17/130V/STD	20	E17	130	Givrée	5 000	C-8	115	120
51056	25T6.5/CL/5M/BA15d/125V/STD	25	BA15d	125	Claire	5 000	C-8	180	500
50674	25T6.5/CL/7.5M/BA15d/145V/STD	25	BA15d	145	Claire	7 500	C-8	180	120
50729	25T6.5/F/7.5M/BA15d/145V/STD	25	BA15d	145	Givrée	7 500	C-8	145	500
50671	25T6.5/CL/5M/E12/130V/STD	25	E12	130	Claire	5 000	C-8	135	120
50672	25T6.5/CL/7.5M/E12/145V/STD	25	E12	145	Claire	7 500	C-8	180	120
50669	25T6.5/CL/5M/E17/130V/STD	25	E17	130	Claire	5 000	C-8	135	120
50670	25T6.5/CL/7.5M/E17/145V/STD	25	E17	145	Claire	7 500	C-8	180	120
50673	25T6.5/F/7.5M/E17/145V/STD	25	E17	145	Givrée	7 500	C-8	180	500
50680	40T6.5/CL/5M/E17/130V/STD	40	E17	130	Claire	5 000	C-8	280	120
52191	40T6.5/F/5M/E17/130V/STD	40	E17	130	Givrée	5 000	C-8	210	500
<b>T7</b>									
LHTM : 2 3/16 po (59 mm) HCL : 1 3/16 po (33 mm)									
52195	15T7/CL/1.5M/BA15d/120V/STD	15	BA15d	120	Claire	1 500	C-7A	100	1 000
52196	15T7/F/1.5M/BA15d/130V/STD	15	BA15d	130	Givrée	1 500	C-7A	75	1 000
52192	15T7/CL/1.5M/E12/120V/STD	15	E12	120	Claire	1 500	C-7A	100	1 000
52194	15T7/CL/1.5M/E17/120V/STD	15	E17	120	Claire	1 500	C-7A	100	1 000
52201	25T7/CL/1.5M/E12/130V/STD	25	E12	130	Claire	1 500	C-7A	115	1 000
<b>T8</b>									
LHTM : 2 3/16 po (65 mm) HCL : 1 3/4 po (41 mm)									
52198	25T8/CL/1.5M/BA15d/120V/STD	25	BA15d	120	Claire	1 500	C-7A	220	1 000
52199	25T8/F/1.5M/BA15d/130V/STD	25	BA15d	130	Givrée	1 500	C-7A	160	1 000
52200	25T8/CL/1.5M/E12/120V/STD	25	E12	120	Claire	1 500	C-7A	220	1 000
52197	25T8/CL/1.5M/E17/120V/STD	25	E17	120	Claire	1 500	C-7A	220	1 000
<b>T10</b>									
LHTM : 5 po (127 mm) HCL : 2 3/4 po (70 mm)									
50923	15T10/CL/3M/130V/STD	15	E26	130	Claire	3 000	C-5V	75	120
50924	15T10/F/3M/130V/STD	15	E26	130	Givrée	3 000	C-5V	75	120
50925	25T10/CL/3M/130V/STD	25	E26	130	Claire	3 000	C-5V	135	120
50928	25T10/F/3M/130V/STD	25	E26	130	Givrée	3 000	C-5V	135	120
50926	40T10/CL/3M/130V/STD	40	E26	130	Claire	3 000	C-5V	195	120
50929	40T10/F/3M/130V/STD	40	E26	130	Givrée	3 000	C-5V	195	120
<sup>†</sup> 50927	60T10/CL/3M/130V/STD	60	E26	130	Claire	3 000	C-5V	365	120
<sup>†</sup> 50930	60T10/F/3M/130V/STD	60	E26	130	Givrée	3 000	C-5V	365	120
<b>T10 HO</b>									
LHTM : 5 13/32 po (137 mm) HCL : 3 13/32 po (85 mm)									
50164	15T10/CL/3M/HO/130V/STD	15	E26	130	Claire	3 000	C-8	70	120
50149	25T10/CL/3M/HO/130V/STD	25	E26	130	Claire	3 000	C-8	175	120
50131	25T10/F/3M/HO/130V/STD	25	E26	130	Givrée	3 000	C-8	175	120
50129	40T10/CL/3M/HO/130V/STD	40	E26	130	Claire	3 000	C-8	300	120
50132	40T10/F/3M/HO/130V/STD	40	E26	130	Givrée	3 000	C-8	300	120
<sup>†</sup> 50130	60T10/CL/3M/HO/130V/STD	60	E26	130	Claire	3 000	C-8	530	120
<sup>†</sup> 50133	60T10/F/3M/HO/130V/STD	60	E26	130	Givrée	3 000	C-8	530	120

<sup>†</sup>Cet item n'est plus produit conformément à la loi sur les standards en matière d'efficacité énergétique, il sera disponible jusqu'à épuisement des stocks.

# Lampes d'usage général