

**5" Angle Grinder, Paddle Switch or Thumb Switch**

**9565CV**

**NEW! 9565PCV**



*Labyrinth Construction,  
Variable Speed  
Features Electronic Current Limiter  
SJS - Super Joint System*



**9565CV**



**9565PCV**

**NEW!**

Technically advanced grinder series with electronic and mechanical safety features to protect users as well as the tool. Available in thumb switch and lock off paddle switch.

**STANDARD EQUIPMENT**

**9565CV INCLUDES:** 5" Grinding Wheel (741407-B), Inner flange (224361-6), Wheel guard (125097-9), Lock nut (224509-0), Lock nut wrench (782412-6), Side handle (152490-4)

**9565PCV INCLUDES:** 5" Grinding Wheel (741407-B), Side Handle(153489-2), Lock Nut Wrench 28(782412-6), Wheel Cover (135108-2), Inner Flange 45(224378-9), Lock Nut 5/8-45(224568-4)

**SPECIFICATIONS**

Max. Capacities:	
Grinding wheel	5" (125 mm)
Wire brush	3" (75 mm)
Diamond wheel	5" (125 mm)
Spindle thread	5/8" - 11 UNC
No load speed: 9565CV	2,800 - 10,500 RPM
9565PCV	2,800 - 11,500 RPM
AMPS (120 V): 9565CV / 9565PCV	12.0 / 13.0
Overall length: 9565CV	11-3/4" (299 mm)
Overall length: 9565PCV	12-1/8" (307 mm)
Net weight: 9565CV	4.0 lbs. (1.8 kg)
Net weight: 9565PCV	4.2 lbs. (1.9 kg)
Shipping weight: 9565CV	7.7 lbs. (3.5 kg)
Shipping weight: 9565PCV	7.2 lbs. (3.2 kg)

**5" Angle Grinder**

**GA5020**



*AC/DC,  
"SJS" Spring Clutch  
Electric Brake  
Labyrinth Construction*



**GA5020 - AC/DC TRIGGER SWITCH TYPE: "No-Lock"**  
**Newly Designed Powerful 10.5 Amp Motor**

- New motor with added resistance to heat and overload
- Labyrinth construction seals motor and bearings from contamination
- Motor winding protection to protect the wires from abrasion
- Removable side handle can be mounted on either side
- Electric Brake automatically reduces RPM after switch is released
- Super Joint System prevents Kickback and prolongs life of the grinder

**STANDARD EQUIPMENT**

**INCLUDED:** Grip (153504-2), Lock Nut Wrench (782424-9), Toolless Wheel Cover (135108-2), 5" Grinding Wheel (741407-B), Inner Flange (224399-1), Lock Nut (224568-4), Dust Cover Attachment (194428-7)

**SPECIFICATIONS**

Max. Capacities:	
Grinding wheel	5" (125 mm)
Sanding disc	5" (125 mm)
Wire cup brush	3-1/2" (90 mm)
Spindle thread	5/8" - 11 UNC
No load speed	11,000 RPM
AMPS (120 V)	10.5
Overall length	14" (356 mm)
Net weight	5.6 lbs. (2.5 kg)
Shipping weight	8.0 lbs. (3.6 kg)

**5" Angle Grinder**

**GA5020C**



**NEW!**

*"SJS" Spring Clutch  
Labyrinth Construction  
Electronic Control*



**Electronic Current Limiter With Anti-Restart, Constant Speed Control & Soft Start For Safe & Durable Operation**

- Anti-restart function prevents accidental startup for safety even if the machine is plugged to power source with the lock-on switch on
- Electric current limiter protects motor from overload
- High dust-proof construction
- Super Joint System absorbs shock caused by accidental wheel lock and protects gears
- Rubberized soft grip for more comfort and control

**STANDARD EQUIPMENT**

**INCLUDED:** Grip 36 Com.(153504-2), Vibration Proof Grip (162258-0), Lock Nut Wrench 28 (782424-9), Toolless Wheel Cover Assy 5/5" (135108-2), 5" D.C.W. 36G(A-80656), Inner Flange 45(224399-1), Lock Nut 5/8-45(224568-4)

**SPECIFICATIONS**

Max. Capacities:	
Grinding/Sanding	5" (125 mm)
Wire cup brush	3-1/2" (90 mm)
Spindle thread	5/8" - 11 UNC
No load speed:	10,000 RPM
AMPS (120 V)	12.5
Overall length	15-3/8" (390 mm)
Net weight	6.2 lbs. (2.8 kg)
Shipping weight	9.1 lbs. (4.1 kg)

**5" Angle Grinder**

**GA5010**

**GA5010Z**



*AC/DC,  
Labyrinth Construction*



**GA5010 - AC/DC TRIGGER SWITCH TYPE: "Lock-On"**  
**GA5010Z - AC/DC TRIGGER SWITCH TYPE: "No-Lock"**

- New motor with added resistance to heat and overload
- Labyrinth construction seals motor and bearings from contamination
- Motor winding protection to protect the wires from abrasion
- Removable side handle can be mounted on either side

**STANDARD EQUIPMENT**

**INCLUDED:** Grip 36 Com.(153504-2), Lock Nut Wrench (782424-9), Wheel Cover Assy (125419-3), 5" Grinding Wheel (741407-B), Inner Flange 45 (224399-1), Lock Nut 5/8-45 (224568-4)

**SPECIFICATIONS**

Max. Capacities:	
Grinding wheel	5" (125 mm)
Sanding disc	5" (125 mm)
Wire cup brush	3-1/2" (90 mm)
Spindle thread	5/8" - 11 UNC
No load speed	11,000 RPM
AMPS (120 V)	10.5
Overall length	14" (356 mm)
Net weight	5.5 lbs. (2.5 kg)
Shipping weight: GA5010	7.9 lbs. (3.5 kg)
Shipping weight: GA5010Z	7.9 lbs. (3.5 kg)

**5" Angle Grinder**

**GA5020Y**



*AC/DC,  
"SJS" Spring Clutch  
Electric Brake  
Two Stage Switch  
Labyrinth Construction*



**AC/DC TRIGGER SWITCH TYPE: "Two Stage"**  
**Newly Designed Powerful 10.5 Amp Motor**

- New motor with added resistance to heat and overload
- Labyrinth construction seals motor and bearings from contamination
- Motor winding protection to protect the wires from abrasion
- Removable side handle can be mounted on either side
- Electric Brake automatically reduces RPM after switch is released
- Super Joint System prevents Kickback and prolongs life of the grinder

**STANDARD EQUIPMENT**

**INCLUDED:** Grip (153504-2), Lock Nut Wrench (782424-9), Toolless Wheel Cover (135108-2), 5" D.C.W. 36 Grit (A-80656), Inner Flange (224399-1), Lock Nut (224568-4), Dust Cover Attachment (194428-7)

**SPECIFICATIONS**

Max. Capacities:	
Grinding wheel	5" (125 mm)
Sanding disc	5" (125 mm)
Wire cup brush	3-1/2" (90 mm)
Spindle thread	5/8" - 11 UNC
No load speed	11,000 RPM
AMPS (120 V)	10.5
Overall length	14" (356 mm)
Net weight	5.6 lbs. (2.5 kg)
Shipping weight	8.0 lbs. (3.6 kg)

**5" Angle Grinder**

**9005B / 9005BZ**



*AC/DC*



- 9005B Features lock-on button
- 9005BZ Features no lock button
- Powerful 10 AMP motor yet light weight for high production work with less fatigue

**STANDARD EQUIPMENT**

**9005B / 9005BZ INCLUDES:** 5" Grinding Wheel 24 Grit (741407-B), Wheel Guard (165369-0), Side Handle (152492-0), Inner Flange (224378-9), Lock Nut (224568-4), Lock Nut Wrench (782412-6)

**SPECIFICATIONS**

Max. Capacities:	
Grinding wheel	5" (125 mm)
Wire cup brush	3-1/2" (90 mm)
Sanding disc	5" (125 mm)
Spindle thread	5/8" - 11 UNC
No load speed	10,000 RPM
AMPS (120 V)	10.0
Overall length	14" (356 mm)
Net weight	6.6 lbs. (3.0 kg)
Shipping weight	8.5 lbs. (3.9 kg)