

Condulet® Conduit Outlet Bodies

Covers and Gaskets

Dimensions Pgs. 9 to 11 (Dimensions for Form 5 – see Section CP)

Blank Covers



Sheet Steel

Size	Form 7 Wedgenut Cat. #	Form 7 Snaptight™ Covers ‡ Cat. #	Form 7 Wedgenut w/Integral Gasket Cat. #	Form 8* Cat. #	Form 8 w/Integral Gasket Cat. #	Form 5 Cat. #
1/2	170	170-SG	170G	180	180G	K50S
3/4	270	270-SG	270G	280	280G	K75S
1	370	370-SG	370G	380	380G	K100S
1 1/4	470	470-SG	470G	480	480G	K125S
1 1/2	570	570-SG	570G	580	580G	K125S
2	670	670-SG	670G	680	680G	K200S
2 1/2	870			880		K250S
3	870			880		K250S
3 1/2	970			980		K350S
4	970			980		K350S



Sheet Aluminum

Feraloy® Iron Alloy

Cast Aluminum

Size	Mark 9 Cat. #	Mark 9 w/Integral Gasket Cat. #	Form 7 Cat. #	Form 7 w/Integral Gasket Cat. #	Series 5 Cat. #	Form 7 Wedgenut Cat. #	Form 7 Wedgenut w/Integral Gasket Cat. #	Form 8* Cat. #	Form 5 ♦ Cat. #	Form 7 Wedgenut Cat. #
1/2	190	190G	170-SA	170G-SA	150	170F	170FG	180F	K50CM	170F-SA
3/4	290	290G	270-SA	270G-SA	250	270F	270FG	280F	K75CM	270F-SA
1	390	390G	370-SA	370G-SA	350	370F	370FG	380F	K100CM	370F-SA
1 1/4	490	490G	470-SA	470G-SA	450	470F	470FG	480F	K125CM	470F-SA
1 1/2	590	590G	570-SA	570G-SA	450	570F	570FG	580F	K125CM	570F-SA
2	690	690G	670-SA	670G-SA	650	670F	670FG	680F	K200CM	670F-SA
2 1/2	889		870-SA		850D	870F		880F	K250CM	870F-SA
3	889		870-SA		850D	870F		880F	K250CM	870F-SA
3 1/2	989		970-SA		950D	970F		980F	K350CM	970F-SA
4	989		970-SA		950D	970F		980F	K350CM	970F-SA

Solid Gaskets

Neoprene



Size	Form 7 Cat. #	Form 8* Cat. #	Mark 9† Cat. #	Form 5 Cat. #	Series 5 Cat. #
1/2	GASK571	GASK851N	GASK1941	GK50N	GASK015N
3/4	GASK572	GASK852N	GASK1942	GK75N	GASK025N
1	GASK573	GASK853N	GASK1943	GK100N	GASK035N
1 1/4	GASK574	GASK854N	GASK1944	GK125N	GASK045N
1 1/2	GASK575	GASK805N	GASK1945	GK125N	GASK045N
2	GASK576	GASK806N	GASK1946	GK200N	GASK065N
2 1/2	GASK578	GASK808N	GASK808N	GK250N	GASK085N
3	GASK578	GASK808N	GASK808N	GK250N	GASK085N
3 1/2	GASK579	GASK809N	GASK8089N	GK350N	GASK095N
4	GASK579	GASK8089N	GASK809N	GK350N	GASK095N

* 1/2 – 1 1/4 are solid gaskets; 1 1/2 – 4 are open gaskets.

† 1/2 – 2 are solid gaskets; 2 1/2 – 4 are open gaskets.

* Two cover screws on 1/2" to 2" Form 8 covers and four cover screws on 2 1/2" and larger Form 8 covers.

‡ Form 7 Snaptight covers with integral sealing gasket are installed without the use of screws.

♦ Malleable Iron Covers.