



**Medium Base
Lamp Receptacle
with Strap
Shock Absorbing**

Cat. #
V84✓



Reflectors



Dome



30° Angle

Max. Lamp Size	Dome Cat. #	30° Angle Cat. #
150 watt, A-21	RD64✓	RA64✓
200 watt, A-23, A-25, PS-25 and 300 watt, PS-30	RD71✓	RA71✓

Hub Size	Cat. #
1/2	VXFT10✓
3/4	VXFT20✓



VXFT - 5 Hubs, 4 Plugs

Hub Size	Cat. #
1/2	VXFT10✓
3/4	VXFT20✓

For use when rear wiring entry is required. Use in lieu of VXF10 or VXF20.

✓ - available with Lightning Service™ See Section G for complete details

Globes† and Guards



150 and 200W globe



300W globe

Maximum Lamp Size		
150 Watt, A-21	200 Watt, A-23, A-25, PS-25	300 Watt, PS-25 PS-30‡

Color	Cat. #	Cat. #	Cat. #
Clear (heat-resisting)	G54✓	G24 ♦ ✓	G34✓ G251✓
Green	G55*✓	G25	
Blue	G56*✓	G26	
Red	G57*✓	G27	
Amber	G58*✓	G28	



Guard P50 and P21



Guard P22

Guards for Glass Globes (Not for use with plastic globes)

Cat. #	Maximum Lamp Size
P50✓	150 watt, A-21
P21✓	200 watt, A-23, A-25, PS-25
P22✓	300 watt, PS-30 (with G251 only)

Mounting Adapter Kit

• Allows for the mounting of non-Crouse-Hinds outlet boxes to the VXT20 wall mount bracket and VXH ceiling mount bracket

Cat. #
VXT-K1

Plastic Globes ①



Shatterproof polycarbonate plastic globe**

Application:

- For use in:
- food processing plants and canneries, dairies, breweries and bakeries
 - emergency lighting

Features:

- Shatterproof, which precludes contamination of food products with broken particles of glass.
- Designed to comply with U.S. Dept. of Agriculture specification for food processing plants.
- Provides protection against vandalism, with resultant lower replacement and maintenance costs.
- Particularly adaptable for use on emergency police or fire alarm boxes.
- Same size as G24 series glass globes. Existing installations can be changed to plastic globes simply by replacing globe.
- For use with 200 watt series luminaires such as VDA22, etc.
- For use without guard.

Color	Max. Wattage, Lamp Size	Cat. #
Natural	200 watt, A-23	G63 ✓
Green	200 watt, A-23	G65
Red	200 watt, A-23	G67

Note: Polycarbonate globes for non-hazardous locations only.



VXT-K1

♦ G24 is available with a TEFLON® coating for increased shatter protection by adding suffix S808.

* With G55, G56, G57, G58 color globes, maximum lamp size is 60 watt for outdoor applications.

** Prior to wash-down, globes must be cool.

† All glass globes are configured type, having fluted side and stippled bottom.

‡ Globe G251 required when guard P22 is used. Use globe G34 when guard is not used.

① Lamp must be mounted in vertical position base up to 45°C (stanchion) only.