



HYDRAULIC QUICK DISCONNECT COUPLINGS

SERIES B ISO 7241-1 INDUSTRIAL INTERCHANGE



- High flow characteristics and pressure ratings superior to Parker 60 series.
- Industry interchangeability with other manufacturer's ISO "B" couplers and nipples.
- Poppet style double shut-off.
- Proven ball lock mechanism.
- 4 To 1 safety factor (Min. Burst = W.P. X 4)
- Ideal for use with hydraulic and other fluids in both stationary and mobile industrial applications.

COUPLER SET MAXIMUM WORKING PRESSURE (PSI)					
	1/4	3/8	1/2	3/4	1
STEEL	5000	4350	4000	2600	2175
BRASS	3500	3500	3500	2500	1500
STAINLESS	5500	3750	3750	3000	3000

VALVED COUPLER - STEEL

PART No.	Body Size	Female Pipe
QD-ISOBC4-4F	1/4	1/4
QD-ISOBC6-6F	3/8	3/8
QD-ISOBC8-8F	1/2	1/2
QD-ISOBC12-12F	3/4	3/4
QD-ISOBC16-16F	1	1

VALVED COUPLER - BRASS

PART No.	Body Size	Female Pipe
QD-BISOBC4-4F	1/4	1/4
QD-BISOBC6-6F	3/8	3/8
QD-BISOBC8-8F	1/2	1/2
QD-BISOBC12-12F	3/4	3/4
QD-BISOBC16-16F	1	1

VALVED COUPLER - STAINLESS (303)

PART No.	Body Size	Female Pipe
QD-SISOBC4-4F	1/4	1/4
QD-SISOBC6-6F	3/8	3/8
QD-SISOBC8-8F	1/2	1/2
QD-SISOBC12-12F	3/4	3/4
QD-SISOBC16-16F	1	1

VALVED NIPPLE - STEEL

PART No.	Body Size	Female Pipe
QD-ISOBN4-4F	1/4	1/4
QD-ISOBN6-6F	3/8	3/8
QD-ISOBN8-8F	1/2	1/2
QD-ISOBN12-12F	3/4	3/4
QD-ISOBN16-16F	1	1

VALVED NIPPLE - BRASS

PART No.	Body Size	Female Pipe
QD-BISOBN4-4F	1/4	1/4
QD-BISOBN6-6F	3/8	3/8
QD-BISOBN8-8F	1/2	1/2
QD-BISOBN12-12F	3/4	3/4
QD-BISOBN16-16F	1	1

VALVED NIPPLE - STAINLESS (303)

PART No.	Body Size	Female Pipe
QD-SISOBN4-4F	1/4	1/4
QD-SISOBN6-6F	3/8	3/8
QD-SISOBN8-8F	1/2	1/2
QD-SISOBN12-12F	3/4	3/4
QD-SISOBN16-16F	1	1



DUST PLUG

ACCESSORIES	Size	Dust Plug	Dust Cap
	1/4	QD-PDP-9	QD-PDC-11
	3/8	QD-PDP-12	QD-PDC-14
	1/2	QD-PDP-16	QD-PDC-17
	3/4	QD-PDP-20	QD-PDC-21
	1	QD-PDP-24	QD-PDC-26



DUST CAP

AGRICULTURAL (PIONEER 4000) INTERCHANGE



- Interchangeable with Pioneer 4000 series, Safeway S20 and S40 series
- High Strength Steel Construction
- Superior "Poppet" style valves
- Nitrile NBR seals with Teflon PTFE back-up ring
- Typical applications include agricultural equipment, gravel trucks and dump trucks.

COUPLER SET					
MAXIMUM WORKING PRESSURE (PSI)					
	1/4	3/8	1/2	3/4	1
STEEL	5000	4350	3600	3600	3300

PART No.	Body Size	Female Pipe	Sleeve Style
QD-AGC4-4F	1/4 Coupler	1/4	One Way
QD-AGC6-6F	3/8 Coupler	3/8	One Way
QD-AGC8-8F	1/2 Coupler	1/2	Two Way
QD-AGC12-12F	3/4 Coupler	3/4	One Way
QD-AGC16-16F	1 Coupler	1	One Way

PART No.	Body Size	Female Pipe
QD-AGN4-4F	1/4 Nipple	1/4
QD-AGN6-6F	3/8 Nipple	3/8
QD-AGN8-8F	1/2 Nipple	1/2
QD-AGN12-12F	3/4 Nipple	3/4
QD-AGN16-16F	1 Nipple	1



DUST PLUG

ACCESSORIES	Size	Dust Plug	Dust Cap
	1/4	QD-PDP-10	QD-PDC-11
3/8	QD-PDP-13	QD-PDC-14	
1/2	QD-PDP-14	QD-PDC-15	
3/4	QD-PDP-19	QD-PDC-20	
1	QD-PDP-23	QD-PDC-24	



DUST CAP

SNOW PLOW QUICK DISCONNECT



PART No.	Description	Body Size	Female Pipe
QD-SP90	Snow Plow Set	1/4	1/4

This high quality economical coupler is at the centre of every snow plow replacement parts package.

- High strength steel construction.
- Coupler set maximum working pressure is 4000 P.S.I.

Also ask us about...

- 1/4" S.A.E. 100R7 Synflex® Hose Assemblies in various lengths and configurations.
- Steel Hydraulic Adapters and Brass Adapters to meet all your fitting needs.

SERIES A ISO 7241-1 PARKER 6600 INTERCHANGE



- Interchangeable with Parker 6600 series, Aeroquip 5600 Series, Safeway S56 Series and other manufacturer's couplers and nipples built in accordance to I.S.O. 7241-1 Series "A".
- 4 to 1 Safety factor (Min. Burst = W.P. X 4)
- High Strength Steel Construction.
- Proven ball lock mechanism.
- For use with hydraulic fluids in mobile and stationary applications.

COUPLER SET					
MAXIMUM WORKING PRESSURE (PSI)					
	1/4	3/8	1/2	3/4	1
STEEL	4600	4600	4000	4000	3000

VALVED COUPLER - STEEL

PART No.	Body Size	Female Pipe
QD-ISOAC4-4F	1/4	1/4
QD-ISOAC6-6F	3/8	3/8
QD-ISOAC8-8F	1/2	1/2
QD-ISOAC12-12F	3/4	3/4
QD-ISOAC16-16F	1	1

VALVED NIPPLE - STEEL

PART No.	Body Size	Female Pipe
QD-ISOAN4-4F	1/4	1/4
QD-ISOAN6-6F	3/8	3/8
QD-ISOAN8-8F	1/2	1/2
QD-ISOAN12-12F	3/4	3/4
QD-ISOAN16-16F	1	1



ACCESSORIES	Size	Dust Plug	Dust Cap
	1/4	QD-PDP-7	QD-PDC-9
	3/8	QD-PDP-11	QD-PDC-13
	1/2	QD-PDP-14	QD-PDC-15
	3/4	QD-PDP-19	QD-PDC-20
	1	QD-PDP-23	QD-PDC-24



HIGH PRESSURE / THREAD TO CONNECT (PARKER 3000) INTERCHANGE



- Interconnect with Parker 3000 series, Faster PVV series and other screw to connect couplings used in the hydraulic tool and rescue equipment markets.
- Zero leakage and higher flow rates than commonly used metal to metal sealing.
- High strength steel construction with heavy duty clear zinc plating for excellent corrosion resistance

VALVED COUPLER - STEEL

PART No.	Body Size	Pipe	Working Pressure (PSI)
QD-TCC4-4M	1/4 Coupler	1/4 MPT	10,000
QD-TCC6-6F	3/8 Coupler	3/8 FPT	10,000
QD-TCC6-6M	3/8 Coupler	3/8 MPT	10,000

VALVED NIPPLE - STEEL

PART No.	Body Size	Pipe	Working Pressure (PSI)
QD-TCN4-4F	1/4 Nipple	1/4 FPT	10,000
QD-TCN6-6F	3/8 Nipple	3/8 FPT	10,000

ACCESSORIES	Size	Dust Plug	Dust Cap
	1/4	QD-TCMDP-4	QD-TCMDC-4
	3/8	QD-TCMDP-6	QD-TCMDC-6