

TYPE GBL

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Lay-in feature

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation





Fig. 1



Fig. 2

Catalogue Number	Figure Number	Ground Wire Range	Bolt Size	Dimensions							Hex
				7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	
*GBL-4	1	4-14	10	7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	Slot
+GBL-4SS	1	4-14	10	7/32	5/8	31/64	1-3/32	13/64	25/64	51/64	Slot
GBL-1/0	1	1/0-14	1/4	9/32	51/64	27/32	1-5/8	7/16	5/8	1-5/32	Slot
GBL-250	2	250kcmil-6	1/4	9/32	31/64	1	2-3/16	29/64	7/8	1-23/32	7/32

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E34440

* UL 467 and UL 486A/B Listed C22.2 no. 41 C22.2 no 65.03

+ UL 467 Listed C22.2 no. 41

+ Supplied with stainless steel hardware. Meets ASTM B117-09 and is resistant to outdoor salt spray.

DE-OX Inhibitor is recommended for all aluminum terminations.

