


Turnlok® Locking Devices Heavy-Duty Ground Continuity Monitoring (GCM) Plugs & Connectors

2 Pole, 3 Wire Grounding 15, 20 & 30A; 125, 250, 277 & 347V
3 Pole, 4 Wire Grounding 20 & 30A, 125/250V


Pass & Seymour



PSL15-PGCM






PSL15-CGCM



L620-PGCM



L620-CGCM




Features – Heavy-Duty Turnlok GCM

- Integral indication of ground continuity and power status. Continuous monitoring enhances personnel safety and adds convenience.
- Dual, bright LED indicators with 360° visibility. Green LEDs indicate proper ground continuity and power status. Red LEDs indicate ground continuity loss or reversed polarity. No LED indicates open hot, open neutral, or hot to ground cross. For 250V configurations: Hot to ground cross will be indicated by a green and red LED.
- NEMA configurations always visible for fast identification without disconnecting.
- Exclusive neoprene dust cover on devices seals cable entry. Optional weatherproof boots (sold separately).
- Chemical- and impact-resistant nylon housing features horizontal, easy-grip ribs on back body.
- Exclusive, rugged two-piece cord grip (15 Amp only) accepts a wide range of cord widths. Provides uniform pressure for superior retention of conductors.
- Recessed cord-grip screw reduces screwdriver slippage, improves safety. Quick-thread tri-drive assembly and cord-grip screws come backed-out and ready-to-wire.
- Color-coded terminal screws are backed-out for fast installation.
- Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.

Catalog Number	Rating A. V.	Description	Cord Diameter	NEMA Config. No.	3rd Party Compliance	
					cULus	FSUL WC596
2 Pole, 3 Wire Grounding						
NEW PSL15-PGCM	15 125	Plug, Black & White	.230"-.720"	L5-15P	•	•
NEW PSL15-PGCMAN	15 125	Angled Plug, Black & White	.320"-.655"	L5-15P	•	•
NEW PSL15-CGCM	15 125	Connector, Black & White	.230"-.720"	L5-15R	•	•
L520-PGCM	20 125	Plug, Black & White	.385"-1.15"	L5-20P	•	•
L520-CGCM	20 125	Connector, Black & White	.385"-1.15"	L5-20R	•	•
L530-PGCM	30 125	Plug, Black & White	.385"-1.15"	L5-30P	•	•
L530-CGCM	30 125	Connector, Black & White	.385"-1.15"	L5-30R	•	•
NEW PSL615-PGCM	15 250	Plug, Black & White	.230"-.720"	L6-15P	•	•
NEW PSL615-PGCMAN	15 250	Angled Plug, Black & White	.320"-.655"	L6-15P	•	•
NEW PSL615-CGCM	15 250	Connector, Black & White	.230"-.720"	L6-15R	•	•
L620-PGCM	20 250	Plug, Black & White	.385"-1.15"	L6-20P	•	•
L620-CGCM	20 250	Connector, Black & White	.385"-1.15"	L6-20R	•	•
L630-PGCM	30 250	Plug, Black & White	.385"-1.15"	L6-30P	•	•
L630-CGCM	30 250	Connector, Black & White	.385"-1.15"	L6-30R	•	•
NEW PSL715-PGCM	15 277*	Plug, Black & White	.230"-.720"	L7-15P	•	•
NEW PSL715-PGCMAN	15 277*	Angled Plug, Black & White	.320"-.655"	L7-15P	•	•
NEW PSL715-CGCM	15 277*	Connector, Black & White	.230"-.720"	L7-15R	•	•
L720-PGCM	20 277*	Plug, Black & White	.385"-1.15"	L7-20P	•	•
L720-CGCM	20 277*	Connector, Black & White	.385"-1.15"	L7-20R	•	•
L730-PGCM	30 277*	Plug, Black & White	.385"-1.15"	L7-30P	•	•
L730-CGCM	30 277*	Connector, Black & White	.385"-1.15"	L7-30R	•	•
L3720-PGCM	20 347	Plug, Black & White	.385"-1.15"	L24-20P	•	•
L3720-CGCM	20 347	Connector, Black & White	.385"-1.15"	L24-20R	•	•
3 Pole, 4 Wire Grounding						
L1420-PGCM	20 125/250	Plug, Black & White	.385"-1.15"	L14-20P	•	•
L1420-CGCM	20 125/250	Connector, Black & White	.385"-1.15"	L14-20R	•	•
L1430-PGCM	30 125/250	Plug, Black & White	.385"-1.15"	L14-30P	•	•
L1430-CGCM	30 125/250	Connector, Black & White	.385"-1.15"	L14-30R	•	•

*AC only.



All devices listed on this page conform to NEMA WD-1 and WD-6.

H-5